

Terminations

SSMA - SMMA

DC - 18.0 GHz - 0.5 Watt High Performance

- Low VSWR
- Rugged Stainless Steel Construction
- Small Size, Light Weight
- Bead Chain available on Subminiature Models

Midwest Microwave's SSMA Subminiature and SMMA Ultraminiature series of high performance coaxial Terminations provide temperature stable, ruggedly built, low VSWR precision performance in a compact light weight package size. Bead Chains are available with the Subminiature units, but are not available with the Ultraminiature units.

SPECIFICATIONS

Impedance: 50 Ohms

Frequency: DC - 18.0 GHz

VSWR: $1.10 + 0.01 (f \text{ GHz})$

Power: 0.5 Watts max @ 25 °C

Operating Temperature Range: -65 to +125 °C





Finish: Passivated Stainless Steel

Subminiature

DC - 18.0 GHz	2180 Series	Model Numbers
Male Plug	Male Plug with Chain	
TRM-2180-MO-SSM-02	TRM-2180-MC-SSM-02	
Female Jack	Female Jack with Chain	
TRM-2180-FO-SSM-02	TRM-2180-FC-SSM-02	

Ultraminiature

DC - 18.0 GHz	2181 Series	Model Numbers
Male Plug	TRM-2181-MO-SMM-02	
Female Jack	TRM-2181-FO-SMM-02	



Note: Bead Chains are 3.5 inches long and are not available on Ultraminiature Series Models.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[TRM-2180-FC-SSM-02](#)