## **HellermannTyton**

## **Specification Sheet**

Part Number: TAG3-100

Dot matrix printable self-laminating vinyl has a smooth surface, allowing for the highest resolution and print contrast using an impact printer. The material is a conformable vinyl, allowing it to wrap and stay around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and will remain in place long term.

Tabtag dot matrix labels are specifically made for use in dot matrix printers for fast and easy printing.

Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.



Dot Matrix Label, Self-Laminating, 1.0" x 1.0" x 3.75", 8 Across, White, 2500/pkg

Article Number	595-03100

Type TAG3

Color White (WH)

Quantity Per pack

Product Description	HellermannTyton's self-laminating labels are used for marking wires
	and cable. The clear tail overlaps and protects the printed information
	from obrasion, obomicals and solvents and resists LIV expecture

and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using using any standard dot matrix printer, clear marking and high high-contrast imaging against the wire make this

the perfect choice for durable identification.

**Short Description** Dot Matrix Label, Self-Laminating, 1.0" x 1.0" x 3.75", 8 Across,

White, 2500/pkg

Global Part Name TAG3-100-WH

**Local Order Number 2** 595-03100

Fixation Method Pasting / Stick

Variant Adhesive label

Width W (Imperial) 1.0

Width W (Metric) 25.4

**Bundle Diameter Min (Imperial)** 0.44

**Bundle Diameter Min (Metric)** 11.10

**Bundle Diameter Max (Imperial)** 0.87

Bundle Diameter Max (Metric) 22.20

Thickness T (Metric) 75.0

Width of Liner (Metric) 228.60

Width of Liner (Imperial) 8.9 **Outside Diameter Max (Imperial)** 0.874 **Outside Diameter Min (Metric)** 11.1 **Outside Diameter Min (Imperial)** 0.437 **Outside Diameter Max (Metric)** 22.20 Material Type 100, Vinyl, white, self-laminating (100) **Material Shortcut** 100 Adhesive Acrylic **Halogen Free** No **Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C) **Operating Temperature** -51°F to +200°F (-46°C to +93°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes **Certification/Specification UL-Recognized** 

Yes

**UL Recognized (US)** 

Package Quantity (Imperial)2500Package Quantity (Metric)2500Customs Number3919905060Labels per Column8Labels per Row8

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HellermannTyton: