


Specification Sheet

Part Number: TAG33T1-DTH



White polyester is glossy, allowing for the highest resolution and print contrast.
The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, 3.0" x 2.0", 1 Across, PET, White, 1000/roll

Article Number	596-00039
Type	TAG33T1
Color	White (WH)
Quantity Per	roll
Product Description	HellermannTyton white polyolefin labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's polyolefin material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.
Short Description	Thermal Transfer Labels, 3.0" x 2.0", 1 Across, PET, White, 1000/roll

Global Part Name	TAG33T1-PO-WH
Width W (Imperial)	3.0
Width W (Metric)	76.2
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Width of Liner (Metric)	78.74
Width of Liner (Imperial)	3.10
Material	Polyolefin (PO)
Material Shortcut	PO
Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +140°F (-40°C to +60°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HellermannTyton:](#)

[TAG33T1-DTH](#)