

## **Specification Sheet**

Part Number: 596-00372

Pre-printed solar labels are made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

SAFETY

High abrasion and scuff resistance for high performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-Printed Header Label, SAFETY, 3.0" x 2.0", PET, Green, 250/roll

Article Number 596-00372

Type 3X2SAFETY

Color Green (GN)

Quantity Per roll

**Product Description** 

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

| Short Description         | Pre-Printed Header Label, SAFETY, 3.0" x 2.0", PET, Green, 250/roll        |
|---------------------------|--|
| Global Part Name          | 3X2SAFETY-336/926-GN   |
| Technical Description     | Pre-Printed Header Label, SAFETY, 3" X 2", Green                           |
|                           |  |
| Width W (Imperial)        | 3.0  |
| Width W (Metric)          | 76.2   |
| Thickness T (Metric)      | 64.0   |
| Height H (Imperial)       | 2.0  |
| Height H (Metric)         | 50.4   |
| Width of Liner (Metric)   | 81.2   |
| Width of Liner (Imperial) | 3.2  |
|                           |  |
|                           |  |
| Material                  | Type 336/926, Polyester, UV-stabilized, clear polyester laminate (336/926) |
| Material Shortcut         | 336/926  |
| Adhesive                  | Acrylic  |
| Halogen Free              | No   |

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

**Operating Temperature**  $-40^{\circ}\text{F to } +302^{\circ}\text{F } (-40^{\circ}\text{C to } +150^{\circ}\text{C})$ 

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification NEC2011 NEC2014 NEC2020 NEC2017

UL Recognized (US) Yes

Package Quantity (Imperial) 250

Package Quantity (Metric) 250

**Customs Number** 3919102055

Labels per Column 1

Labels per Row 1

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HellermannTyton: 596-00372