

## **Specification Sheet**


Part Number: 596-00878

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.



Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Orange, 50/roll

Article Number 596-00878

Type WESHLBL17

Color Orange (OG)

Quantity Per roll

**Product Description** 

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Orange, 50/roll
Global Part Name	WESHLBL17-443/281-OG
Technical Description	Pre-Printed Solar Label-2017 Code, "WARNING - ELECTRICAL SHOCK HAZARD", 3.75" X 2.0", Vinyl, Orange/White, 50/RL
Longth L (Imporial)	2.0
Length L (Imperial)	2.0
Length L (Metric)	50.8
Width W (Imperial)	3.75
Width W (Metric)	95.20
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8

Material Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)

443/281 **Material Shortcut** 

Adhesive Acrylic **Halogen Free** No **Adhesive Operating Temperature** -40°F to +174°F (-40°C to +79°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification UL 969 NEC2017 NEC2020 Warranty (US) Yes **UL Recognized (US)** Yes **Package Quantity (Imperial)** 50 Package Quantity (Metric) 50 **Customs Number** 3919102055 1 Labels per Column

Labels per Row

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HellermannTyton: 596-00878