RSF166 Series

Dual Switch Point Series - External Mount



- External Mount via compression seal
- High & Low level switching
- PPS material
- Versions for Filling or Emptying Control
- UL recognised components File No. E171218
- WRAS Approved

Technical Specification (Common to both Singl		t versions)	
Mechanical		Electrical		
Material	PPS	Switching power VA max.		25
Colour	Grey	Switching Voltage AC max Switching Voltage DC max		240
Temp. Range* °C	-10 / +85			120
°F	+14 / +185	Switching Currant max A		0.6
Minimum Liquid SG	0.85	All electrical ratings are for resistive		loads only.
Standard cable length	100cm	-		
* Temperature ranges refer	to wetted parts.			
Standard Parts		Upper switch	Lower switch	Total length
Single Float Versions		Level	Level	
RSF166A25B75		30mm	75mm	102mm
RSF166A25B100		30mm	100mm	127mm
RSF166A25B125		30mm	125mm	152mm
RSF166A25B150		30mm	150mm	177mm
RSF166A25B175		30mm	175mm	202mm
NOT 100/1202170		00111111	17011111	20211111
Dual Float Versions				
RSF166A50A100	Emptying Control	50mm	100mm	134mm
RSF166A50A150	Emptying Control	50mm	150mm	13411111 184mm
RSF166B50B100	1,		100mm	104111111 127mm
	Filling Control	50mm		127111111 177mm
RSF166B50B150	Filling Control	50mm	150mm	1//!!!!!

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

Mechanical Dimensions

Single Float Versions

Dual Float Versions mm max tank wall thickness Switching Level 1 MAKE ON RISE BREAK ON RISE MAKE ON RISE Types RSF166A50A100 RSF155A50A150 Types RSF166B50100 RSF155B50B150 Low Liquid Level Switching Level 2 BREAK ON RISE MAKE ON RISE Ø21.5

www.cynergy3.com

The RSF166 float switch series is designed to offer a number of switching options to meet a variety of system requirements.

These are manufactured in PPS (Polyphenylene Sulphide), which are compatible with a wide range of liquids, and are mounted externally via a nitrile compression seal and a 22mm dia hole in the tank.

The single float types are generally used in systems with PLC control of processes.

The dual float versions can be used for controlling the filling or emptying of tanks via electromechanical relays.

> Cynergy3 Components Ltd. 7 Cobham Road Ferndown Industrial Estate Wimborne, Dorset BH21 7PE Telephone +44 (0) 1202 897969

Email:sales@cynergy3.com

ISO9001 CERTIFIED

RSF166 2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sensata:

<u>RSF166A25B100</u> <u>RSF166A25B125</u> <u>RSF166A25B150</u> <u>RSF166A25B175</u> <u>RSF166A25B75</u> <u>RSF166A50A100</u> <u>RSF166A50A150</u> <u>RSF166B50B100</u> <u>RSF166B50B150</u>