

DA(UL) Series

UL Approved*, Normally Open, High Voltage Relays - 10kV, 7.5kV & 5kV



Recently approved by UL, very high isolation voltages (up to 10kV) are achieved through the use of high vacuum reed switches with either rhodium or tungsten contacts and make these relays suitable for high reliability applications, such as cardiac defibrillators, test equipment and high voltage power supplies.

A choice of 5kV, 7.5kV and 10kV isolation voltages is available

The rhodium contact relays have low contact resistance, while the tungsten contact relays can switch higher voltages.

PCB or panel mount, via nylon studs, versions are available.

Connection options, for the HV, include PCB, solder turret(wire wrap), flying lead and 0.25" spade terminals.

- Choice of 10kV, 7.5kV or 5kV Isolation
- Low contact resistance
- PCB or panel mount
- HV connections via flying leads, solder turret (wire wrap), or 1/4" spade terminals
- Excellent AC characteristics



Contact Specification	Unit	Condition	10kV		7.5kV		5kV	
Contact Form					N/O (normally open)			
Contact Material			Rhodium	Tungsten	Rhodium	Tungsten	Rhodium	Tungsten
Isolation across contacts	kV	DC or AC peak	10	10	7.5	7.5	5	5
Switching Power Max.	W		50	50	50	50	50	50
Switching Voltage Max.	V	DC or AC peak	1000	7000	1000	5000	1000	3500
Switching Current Max.	A	DC or AC peak	3	2	3	2	3	2
Carry Current Max	A	DC or AC peak	4	3	4	3	4	3
Capacitance across contacts	pF	coil to screen grounded	<0.2	<0.2	<0.2	<0.2	<0.2	<0.2
Lifetime operations		dry switching	10 ⁹	10 ⁹	10 ⁹	10 ⁹	10 ⁹	10 ⁹
		50W switching	10 ⁸	10 ⁸	10 ⁸	10 ⁸	10 ⁸	10 ⁸
Contact Resistance	mΩ	max (typical)	50 (15)	250(100)	50 (15)	250(100)	50 (15)	250(100)
Insulation Resistance	Ωmin	(typical)	10 ¹⁰	(10 ¹³)	10 ¹⁰	(10 ¹³)	10 ¹⁰	(10 ¹³)
Coil Specification			5V		12V		24V	
Must Operate Voltage	V	DC	3.7		9		20	
Must Release Voltage	V	DC	0.5		1.25		4	
Operate Time	ms	diode fitted	3.0		3.0		3.0	
Release Time	ms	diode fitted	2.0		2.0		2.0	
Resistance	Ω		28		150		780	
Note: The operate / release voltage and coil resistance will change at a rate of 0.4% per degree C. Values are stated at room temperature (20 degrees C)								
Relay Specification								
Isolation contact/coil	kV	DC or AC peak	17					
Insulation resistance contact to all terminals	Ωmin	(typical)	10 ¹⁰ (10 ¹³)					
Environmental								
Operating Temp range	°C		-20 to +70					

*Consult factory for UL ratings

These products have been UL approved for use as per pollution degree 2 classification.

If you require further information as to how this may affect product usage, please contact sales@cynergy3.com.

Part Numbering System

Reed Switch Size

Contact Form A=n/o

Contact Material

R=Rhodium,

T=Tungsten

Moulding Ref. No.

Coil Voltage

05=5Vdc, 12=12Vdc,

24=24Vdc

Isolation between

Contacts

10=10kV

75=7.5kV

05=5kV

D A T 7 12 10 F U

"U" indicates UL approved

Mounting or Connection Style

No suffix indicates PCB mount

F=PCB mount & coil connection with Flying lead HV connection

P=Panel mount with wire wrap terminals

S=PCB mount & coil connection with stud fixing & 1/4" spade HV connection

T=PCB mount & coil connection with stud fixing & wire wrap HV connection

Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE, UK
Telephone: +44 (0)1202 897969
Email: c3w_sales@sensata.com

ISO9001 CERTIFIED

cynergy3-da-ul-v2




Made in the UK

www.cynergy3.com


MECHANICAL

STANDARD

(e.g. DAT71210U)




CIRCUIT DIAGRAMS (ALL VARIANTS)



NOTE: COIL POLARITY IS NOT SIGNIFICANT


PANEL MOUNT

(e.g. DAT71210PU)



FLYING LEAD


(e.g. DAT71210FU)



NOTE: PINS WHICH ARE NOT NUMBERED HAVE NO ELECTRICAL CONNECTION.

TURRET (Wire Wrap)

(e.g. DAT71210TU)




NOTE: PINS WHICH ARE NOT NUMBERED HAVE NO ELECTRICAL CONNECTION.

SPADE TYPE

(e.g. DAT71210SU)

'S' Suffix denotes the 0.250" 'Push On' blade connectors, M4 fixing bolts and Epoxy potting.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sensata:

[DAT72410U](#) [DAT72405U](#) [DAT72410FU](#) [DAT71210U](#) [DAT71205U](#) [DAT70510U](#) [DAR72410U](#) [DAR71210U](#)
[DAR70510U](#)