

## | UF08B

### ULTRASONIC FLOW METER



This innovative design provides a high accuracy, non-invasive, flow measurement device at a fraction of the cost of other current non-invasive systems. The unique measurement technique automatically compensates for viscosity and temperature variations. The measurement of flow is by ultrasonic transit time in-line cell.

The flow path is designed to minimize pressure drop and, having no moving parts within, will not clog or jam. The sensor also allows contaminants to pass through without affecting its performance.

The sensor is supplied with pulse and analogue outputs, which are selectable by connection wires.

#### Features

- Non-invasive sensor technology
- Fully electronic, no moving parts
- Automatic viscosity and temperature compensation
- Pulse or analogue output selectable
- Low pressure drop
- LED indication of no liquid & of flow rate

## SPECIFICATIONS

### Technical

<b>Max. Flow l/min (Q4)</b>		8	
<b>Transitional Flow (Q2)</b>		0.4	
<b>Min. Flow l/min (Q1)</b>		0.1	
<b>Output Selectable</b>	Pulse		Analogue

### Performance

<b>Accuracy for Flow Rates Between Q2 and Q4</b>	3% of reading
<b>Accuracy for Flow Rates Between Q1 and Q2</b>	5% of reading
<b>Resolution Better Than</b>	0.001 l/min
<b>Reverse Flow</b>	0-8 l/min
<b>Response Time</b>	Better than 0.1s

### Interface

<b>Connection 8 Wires</b>	RED supply +ve, BLACK ground, Blue NPN output, Yellow Data in, White PNP output, Orange Voltage output, Brown Current output, Green Ground connected internally to black		
<b>Supply</b>	8 - 24VDC (input current <15mA @ 24VDC)		
<b>Output Selectable</b>	1000 pulses/L	0-5Vdc	4-20mA

## Operation

<b>Principle</b>	Ultrasonic transit time in-line flow cell
<b>Temp. Range (fluid)</b>	-10°C to +85°C
<b>Continuous Fluid Sound</b>	Maintains performance regardless of fluid type, temperature or viscosity for speed measurement fluids with sound speeds 1250 - 1750 m/s
<b>Green LED Definitions</b>	Flashing with 5 second break = power present, no liquid present Constant flashing = power present, flow present Always on = power present, liquid present, no flow


## Physical Characteristics

<b>Flow Tube Material</b>	Glass filled plastic, Grivory HT1V-4FWA Black 9225 (FDA and EU approved for foodstuffs)
<b>Flow Tube Internal Diameter</b>	7mm
<b>Connection Thread</b>	3/8" straight tube
<b>Internal Bore of Connection</b>	7mm
<b>Suitable Pushfit Adapter (to fit 3/8" OD Tube)</b>	John Guest Speedfit PI0412S
<b>Maximum Pressure</b>	10 bar
<b>Case Material</b>	ABS black, Polylac PA-757
<b>Case Integrity</b>	Ultrasonically welded
<b>Connection</b>	8 core, PVC sheathed, 100cm long standard
<b>Environmental Protection</b>	IP66



## DIMENSIONS

All dimensions are in millimeters.





## ORDERING OPTIONS

Example : UF08B100

	UF	08	B	100
Series				
Flow Range				
8 = 0 to 8/Lmin				
Output				
B = selectable				
Cable Length (cms)				

Made in the UK

Page 3

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

### CONTACT US

+44 (0)1202 897969  
c3w\_sales@sensata.com  
Cynergy3 Components Ltd.  
7 Cobham Road,  
Ferndown Industrial Estate,  
Wimborne, Dorset,  
BH21 7PE, United Kingdom

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Sensata:](#)

[UF08B100](#)