

date 09/12/2023

page 1 of 4

MODEL: CPT-3010-90T | DESCRIPTION: PIEZO BUZZER TRANSDUCER

FEATURES

- piezo
- 90 dB @ 10 cm
- through hole





SPECIFICATIONS


| parameter | conditions/description | min | typ | max | units |
|---------------------------|-------------------------|--------|--------|--------|-------|
| rated voltage | Vp-p ↑ | | 5 | | Vp-p |
| operating voltage | 0V | | | 30 | Vp-p |
| current consumption | at rated voltage | | | 1.5 | mA |
| rated frequency | | 2,000 | 2,500 | 3,000 | Hz |
| sound pressure level | at 10 cm, rated voltage | 90 | | | dB |
| electrostatic capacitance | at 120 Hz | 21,000 | 30,000 | 39,000 | pF |
| dimensions | Ø30 x 12 | | | | mm |
| weight | | | 4.4 | | g |
| material | ABS 757 (UL94HB) | | | | |
| terminal | pin (tin plated brass) | | | | |
| operating temperature | | -20 | | 70 | °C |
| storage temperature | | -30 | | 80 | °C |
| washable | no | | | | |
| RoHS | yes | | | | |


SOLDERABILITY

1. All specifications measured at 25±2°C, humidity at 45-60%, unless otherwise noted.

| parameter | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for maximum 5 seconds | 330 | 350 | 370 | °C |
| wave soldering | for maximum 5 seconds | 255 | 260 | 265 | °C |

MECHANICAL DRAWING






Ø2.5(pad)

Recommended PCB Layout Top View

Ø1(hole)

FREQUENCY RESPONSE CURVE



REVISION HISTORY

| rev. | description | date |
|------|-----------------|------------|
| 1.0 | initial release | 09/12/2023 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Devices:

CPT-3010-90T