

Additional Resources: Product Page | PCB Footprint

date 09/12/2024

page 1 of 3

MODEL: PJ-059A | DESCRIPTION: DC POWER JACK

FEATURES

- 2.0 mm center pin
- 2.5 A rating
- right-angle orientation
- through hole
- locking type
- · tapered pins





SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				2.5	А
contact resistance				30	mΩ
insulation resistance	at 500 Vdc	100			МΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

SOLDERABILITY


parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5 ±0.5 seconds	255	260	265	°C


MECHANICAL DRAWING


units: mm tolerance: X. ±0.50 mm X.X ±0.30 mm X.XX ±0.20 mm X.XXX ±0.10 mm PCB: ±0.05 mm












MATING PLUG Jack Insertion Depth: 9.5 mm



SCHEMATIC 03 02 Model PJ-059A Center Pin Ø2.0 mm

REVISION HISTORY

rev.	description	date	
1.0	initial release	07/30/2007	
1.01	applied new spec template	01/06/2014	
1.02	increased voltage rating	04/14/2016	
1.03	brand update	10/30/2019	
1.04	product reengineered for improved manufacturability and production yield, see PCN for details	02/27/2023	
1.05	CUI Devices rebranded to Same Sky	09/12/2024	

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Devices:

PJ-059A