# **CUI** DEVICES

**date** 10/11/2019

page 1 of 3

MODEL: SP-3544-WT | DESCRIPTION: AUDIO PLUG

#### **FEATURES**

- 4 conductor
- designed for overmolding





### **SPECIFICATIONS**

00					
parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance	between plug and jack			50	mΩ
insulation resistance	at 500 Vdc	100			МΩ
voltage withstand	for 1 minute			250	Vac
insertion force	when mating with a standard jack	0.3		4	kgf
withdrawal force	when mating with a standard jack	0.3		4	kgf
operating temperature		-25		70	°C
operating humidity				85	%
life			5,000		cycles
flammability rating	see material table				
RoHS	yes				


## **SOLDERABILITY**

parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 1 second	380	400	420	°C

# **MECHANICAL DRAWING**

units: mm tolerance:  $X \le 1.0$ :  $\pm 0.1$  mm  $1.0 < X \le 6.0$ :  $\pm 0.2$  mm  $6.0 < X \le 18.0$ :  $\pm 0.3$  mm  $18.0 < X \le 40.0$ :  $\pm 0.4$  mm X > 40.0:  $\pm 0.5$  mm unless otherwise noted

ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	insulator	POM (UL94HB)	white
2	ring 1	brass	nickel
3	ring 2	brass	nickel
4	sleeve	brass	nickel
5	tip contact	brass	nickel



Additional Resources: Product Page | 3D Model

CUI Devices | MODEL: SP-3544-WT | DESCRIPTION: AUDIO PLUG date 10/11/2019 | page 3 of 3

### **REVISION HISTORY**

rev.	description	date
1.0	initial release	06/18/2018
1.01	brand update	10/11/2019

The revision history provided is for informational purposes only and is believed to be accurate.

# **CUI** DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

**CUI Devices**:

SP-3544-WT