


SERIES: VGS-200C | DESCRIPTION: AC-DC POWER SUPPLY
FEATURES

- UL/EN/IEC 62368 certified
- designed to meet IEC/EN 61558, IEC/EN 60335, and GB4943 system requirements
- short-circuit, over-current, over-voltage, over-temperature protections
- output adjustable via trimpot +/- 10%



MODEL	output voltage		output current	output power	ripple and noise ¹	efficiency ²
	typ (Vdc)	range (Vdc)	max (A)	max (W)	max (mVp-p)	typ (%)
VGS-200C-5	5	4.5~5.5	30.0	150.0	150	87.0
VGS-200C-12	12	10.2~13.8	17.0	204.0	150	87.5
VGS-200C-15	15	13.5~18.0	14.0	210.0	150	88.0
VGS-200C-24	24	21.6~28.8	8.8	211.2	150	88.5
VGS-200C-36	36	32.4~39.6	5.9	212.4	200	89.0
VGS-200C-48	48	43.2~52.8	4.4	211.2	200	89.5

Notes: 1. Ripple and noise are measured at 20 MHz BW with 47 uF aluminum electrolytic capacitor and 0.1 uF ceramic capacitor on the output.
 2. Measured at 230 Vac.

PART NUMBER KEY


INPUT

parameter	conditions/description	min	typ	max	units
voltage range	ac input, low voltage (switch in position of 115)	90		132	Vac
	ac input, high voltage (switch in position of 230)	180		264	Vac
	dc input, (switch in position of 230)	240		373	Vdc
frequency range		47		63	Hz
current	at 115 Vac			5	A
	at 230 Vac			3	A
inrush current	at 115 Vac, cold start		60		A
	at 230 Vac, cold start		60		A
no load power consumption	at 230 Vac, 25 °C			0.75	W

OUTPUT

parameter	conditions/description	min	typ	max	units
capacitive load	5 V model			10,000	μF
	12 V model			4,000	μF
	15 V model			3,300	μF
	24 V model			1,500	μF
	36 V model			1,500	μF
	48 V model			470	μF
initial set point accuracy	5 V model, full load range		±3		%
	12 V model, full load range		±1.5		%
	all other models, full load range		±1		%
line regulation	rated load		±0.5		%
load regulation	5 V model, 0~100% load		±2		%
	12 V model, 0~100% load		±1		%
	all other models, 0~100% load		±0.5		%
switching frequency			65		kHz
hold-up time	at 115 Vac	12			ms
	at 230 Vac	16			ms

PROTECTIONS

parameter	conditions/description	min	typ	max	units
over current protection	auto recovery	110		185	%
over voltage protection	5 V model, output shut down, latching			8.0	Vdc
	12 V model, output shut down, latching			18.0	Vdc
	15 V model, output shut down, latching			22.0	Vdc
	24 V model, output shut down, latching			33.6	Vdc
	36 V model, output shut down, latching			46.8	Vdc
	48 V model, output shut down, latching			60.0	Vdc
short circuit protection	continuous, auto recovery, hiccup				
over temperature protection	latching				

SAFETY & COMPLIANCE

parameter	conditions/description	min	typ	max	units
isolation voltage	input to output, 1 min, <10 mA	3,000			Vac
	input to ground, 1 min, <10 mA	2,000			Vac
	output to ground, 1 min, <5 mA	500			Vac
safety approvals	certified to 62368: IEC/EN/UL designed to meet 60335: IEC/EN designed to meet 61558: IEC/EN designed to meet 4943: GB				
conducted emissions	CISPR32/EN55032 CLASS A				
radiated emissions	CISPR32/EN55032 CLASS A				

SAFETY & COMPLIANCE (CONTINUED)

parameter	conditions/description	min	typ	max	units
ESD	IEC/EN 61000-4-2 Contact $\pm 6\text{KV}$ /Air $\pm 8\text{KV}$, perf. Criteria A				
radiated immunity	IEC/EN61000-4-3 10V/m, perf. Criteria A				
EFT/burst	IEC/EN61000-4-4 $\pm 2\text{KV}$, perf. Criteria A				
surge	IEC/EN61000-4-5 line to line $\pm 2\text{KV}$ /line to ground $\pm 4\text{KV}$, perf. Criteria A				
conducted immunity	IEC/EN61000-4-6 10Vr.m.s, perf. Criteria A				
voltage dips and interruption	IEC/EN61000-4-11 0%, 70%, perf. Criteria B				
RoHS compliant	yes				
MTBF	as per MIL-HDBK-217F at 25 °C	300,000			hrs

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-30		70	°C
storage temperature		-40		85	°C
operating humidity	non-condensing	10		95	%
storage humidity	non-condensing	20		90	%
temperature coefficient				± 0.03	%/°C

MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	179.00 x 99.00 x 30.00				mm
weight			520		g
cooling	natural convection				
case material	metal (AL1100, SGCC)				

MECHANICAL DRAWING

units: mm [inch]


tolerance: ± 1.00 [± 0.039]



wire range: 22~12 AWG

connector tightening torque: M3.5, 0.8 N·m

PIN OUT	
PIN	Function
1	+Vo
2	+Vo
3	-Vo
4	-Vo
5	$\perp$
6	AC (N)
7	AC (L)


Note: At least one position ①~⑧ must be securely connected to the GND. $\perp$

Switch	AC input	DC input
	90-132 Vac	---
	180-264 Vac	240-373 Vdc




Position	Screw Spec.	L (max)	Torque (max)
① ~ ⑧	M4	4 mm	0.9 N·m

DERATING CURVES



EFFICIENCY CURVES



REVISION HISTORY

rev.	description	date
1.0	initial release	03/09/2021
1.01	derating and efficiency curves updated	01/31/2022

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CUI Inc.:](#)

[VGS-200C-12](#) [VGS-200C-12-A](#) [VGS-200C-12-B](#) [VGS-200C-15](#) [VGS-200C-15-A](#) [VGS-200C-15-B](#) [VGS-200C-24](#)
[VGS-200C-24-A](#) [VGS-200C-24-B](#) [VGS-200C-36](#) [VGS-200C-36-A](#) [VGS-200C-36-B](#) [VGS-200C-48](#) [VGS-200C-48-A](#)
[VGS-200C-48-B](#) [VGS-200C-5](#) [VGS-200C-5-A](#) [VGS-200C-5-B](#)