

HDSP-301x/303x Series**HDSP-561x/563x Series****10-mm and 13-mm Slim Font Seven-Segment Displays****Description**

The Broadcom® HDSP-301x/303x Series and HDSP-561x/563x Series slim font seven-segment displays incorporate a slim font character design. This slim font features narrow width, specially mitered segments to give a fuller appearance to the illuminated character. Faces of these displays are painted a neutral gray for enhanced on/off contrast.

All devices are available in either common anode or common cathode configuration with right hand decimal point.


Features

- Excellent appearance
- Slim font design
- Mitered corners, evenly illuminated segments
- Gray face for optimum on/off contrast
- Choice of colors: GaP HER, GaP green, GaP yellow, and AlInGaP deep red
- Choice of character size: 10 mm and 13 mm
- Characterized for luminous intensity

Ordering Information

GaP HER HDSP-	GaP Green HDSP-	GaP Yellow HDSP-	AlInGaP Deep Red HDSP-	Description
301E	301G	301Y	301A	Common Anode, 10-mm Display
303E	303G	303Y	303A	Common Cathode, 10-mm Display
561E	561G	561Y	561A	Common Anode, 13-mm Display
563E	563G	563Y	563A	Common Cathode, 13-mm Display

Figure 1: HDSP-301x/303x Series




Notes:

All dimensions are in millimeters (inches).
Tolerance is 0.25 mm (0.01 inch) unless otherwise stated.

Pin	Function
1	G
2	F
3	Common A/C
4	E
5	D
6	DP
7	C
8	Common A/C
9	B
10	A

Figure 2: HDSP-561x/563x Series



Notes:

All dimensions are in millimeters (inches).

Tolerance is 0.25 mm (0.01 inch) unless otherwise stated.

Pin	Function
1	E
2	D
3	Common A/C
4	C
5	DP
6	B
7	A
8	Common A/C
9	F
10	G

Absolute Maximum Ratings

Description	HER	Green	Yellow	Deep Red	Unit
Average Power per Segment or DP	105	105	105	52	mW
Peak Forward Current per Segment or DP ^a	90	90	90	60	mA
DC Forward Current per Segment or DP ^b	30	30	30	20	mA
Operating Temperature Range	–40 to +80	–40 to +80	–40 to +80	–40 to +85	°C
Storage Temperature Range	–40 to +80	–40 to +80	–40 to +80	–40 to +85	°C
Reverse Voltage per Segment or DP	Not designed for reverse bias operation.				
Wave Soldering Temperature for 3 Seconds 1.59 mm Below Body	250	250	250	250	°C

a. Duty factor = 10%, frequency = 1 kHz, T_A = 25°C.

b. Derate linearly as shown in [Figure 3](#), [Figure 6](#) (HER, green, yellow), and [Figure 12](#) (deep red).

Electrical/Optical Characteristics at T_A = 25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
HER						
Device Series HDSP-301/303E						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I _V	1.100	1.800	—	mcd	I _F = 10 mA
Forward Voltage/Segment ^d	V _F	—	1.90	2.50	V	I _F = 20 mA
Peak Wavelength	λ _p	—	635	—	nm	I _F = 20 mA
Dominant Wavelength ^e	λ _d	—	625	—	nm	I _F = 20 mA
Reverse Current ^f	I _R	—	—	100	μA	V _R = 5V
HER						
Device Series HDSP-561/563E						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I _V	1.100	1.800	—	mcd	I _F = 10 mA
Forward Voltage/Segment ^d	V _F	—	1.90	2.50	V	I _F = 20 mA
Peak Wavelength	λ _p	—	635	—	nm	I _F = 20 mA
Dominant Wavelength ^e	λ _d	—	625	—	nm	I _F = 20 mA
Reverse Current ^f	I _R	—	—	100	μA	V _R = 5V
Green						
Device Series HDSP-301/303G						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I _V	1.800	2.800	—	mcd	I _F = 10 mA
Forward Voltage/Segment ^d	V _F	—	2.25	2.50	V	I _F = 20 mA
Peak Wavelength	λ _p	—	568	—	nm	I _F = 20 mA
Dominant Wavelength ^e	λ _d	—	573	—	nm	I _F = 20 mA
Reverse Current ^f	I _R	—	—	100	μA	V _R = 5V

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Green						
Device Series HDSP-561/563G						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I_V	1.800	2.800	—	mcd	$I_F = 10 \text{ mA}$
Forward Voltage/Segment ^d	V_F	—	2.25	2.50	V	$I_F = 20 \text{ mA}$
Peak Wavelength	λ_p	—	568	—	nm	$I_F = 20 \text{ mA}$
Dominant Wavelength ^e	λ_d	—	573	—	nm	$I_F = 20 \text{ mA}$
Reverse Current ^f	I_R	—	—	100	μA	$V_R = 5\text{V}$
Yellow						
Device Series HDSP-301/303Y						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I_V	1.100	1.800	—	mcd	$I_F = 10 \text{ mA}$
Forward Voltage/Segment ^d	V_F	—	2.15	2.50	V	$I_F = 20 \text{ mA}$
Peak Wavelength	λ_p	—	589	—	nm	$I_F = 20 \text{ mA}$
Dominant Wavelength ^e	λ_d	—	590	—	nm	$I_F = 20 \text{ mA}$
Reverse Current ^f	I_R	—	—	100	μA	$V_R = 5\text{V}$
Yellow						
Device Series HDSP-561/563Y						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I_V	1.800	2.800	—	mcd	$I_F = 10 \text{ mA}$
Forward Voltage/Segment ^d	V_F	—	2.15	2.50	V	$I_F = 20 \text{ mA}$
Peak Wavelength	λ_p	—	589	—	nm	$I_F = 20 \text{ mA}$
Dominant Wavelength ^e	λ_d	—	590	—	nm	$I_F = 20 \text{ mA}$
Reverse Current ^f	I_R	—	—	100	μA	$V_R = 5\text{V}$
Deep Red						
Device Series HDSP-301/303A						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I_V	0.280	0.450	—	mcd	$I_F = 1 \text{ mA}$
Forward Voltage/Segment ^d	V_F	—	2.0	2.6	V	$I_F = 20 \text{ mA}$
Peak Wavelength	λ_p	—	660	—	nm	$I_F = 20 \text{ mA}$
Dominant Wavelength ^e	λ_d	—	640	—	nm	$I_F = 20 \text{ mA}$
Reverse Current ^f	I_R	—	—	100	μA	$V_R = 5 \text{ V}$
Deep Red						
Device Series HDSP-561/563A						
Luminous Intensity/Segment (Digit Average) ^{a,b,c}	I_V	0.280	0.450	—	mcd	$I_F = 1 \text{ mA}$
Forward Voltage/Segment ^d	V_F	—	2.0	2.6	V	$I_F = 20 \text{ mA}$
Peak Wavelength	λ_p	—	660	—	nm	$I_F = 20 \text{ mA}$
Dominant Wavelength ^e	λ_d	—	640	—	nm	$I_F = 20 \text{ mA}$
Reverse Current ^f	I_R	—	—	100	μA	$V_R = 5 \text{ V}$

- The luminous intensity, I_V , is measured at the mechanical axis of the package.
- The optical axis is closely aligned with the mechanical axis of the package.
- Tolerance is $\pm 15\%$.
- Forward voltage tolerance is $\pm 0.1\text{V}$.
- The dominant wavelength, λ_d is derived from the CIE Chromaticity Diagram and represents the perceived color of the device.
- Indicates product final test condition. Long-term reverse bias is not recommended.

Intensity Bin Limits (mcd)

Green

HDSP-301G/303G/561G/563G

IV Bin Category	Min.	Max.
K	1.800	3.600
L	2.800	5.600

Yellow

HDSP-301Y/303Y

IV Bin Category	Min.	Max.
I	1.100	2.200
K	1.800	3.600

Yellow

HDSP-561Y/563Y

IV Bin Category	Min.	Max.
K	1.800	3.600
L	2.800	5.600

HER

HDSP-301E/303E

IV Bin Category	Min.	Max.
I	1.100	2.200
K	1.800	3.600

Deep Red

HDSP-301A/303A/561A/563A

IV Bin Category	Min.	Max.
F	0.280	0.560
G	0.450	0.900

HER

HDSP-561E/563E

IV Bin Category	Min.	Max.
K	2.001	3.2
L	3.201	5.05

Tolerance is $\pm 10\%$.

Color Categories

Color	Bin	Dominant Wavelength (nm)	
		Min.	Max.
Green	3	570.00	574.50
	4	567.00	571.50
Yellow	2	586.50	590.00
	3	584.00	587.50

HDSP-301x/303x Series

Figure 3: Maximum Allowable DC Current vs. Ambient Temperature




Figure 4: Forward Current vs. Forward Voltage





Figure 5: Relative Luminous Intensity vs. DC Forward Current



HDSP-561x/563x Series

Figure 6: Maximum Allowable DC Current vs. Ambient Temperature




Figure 7: Forward Current vs. Forward Voltage





Figure 8: Relative Luminous Intensity vs. DC Forward Current



Deep Red Graphs

Figure 9: Spectral Power Distribution




Figure 11: Relative Luminous Intensity vs. Forward Current




Figure 10: Forward Current vs. Forward Voltage





Figure 12: Maximum Forward Current vs. Ambient Temperature



Precautionary Notes


Soldering and Handling Precautions

- Set and maintain the wave soldering parameters according to the recommended temperature and dwell time. Perform daily checks on the profile to ensure that it is always conforming to the recommended conditions. Exceeding these conditions will over-stress the LEDs and cause premature failures.
- Use only bottom preheaters to reduce thermal stress experienced by the LEDs.
- Recalibrate the soldering profile before loading a new type of a PCB. PCBs with different sizes and designs (component density) will have different heat capacities and might cause a change in temperature experienced by the PCB if the same wave soldering setting is used.
- Do not perform wave soldering more than once.
- Any alignment fixture used during wave soldering must be loosely fitted and must not apply stress on the LEDs. Use non-metal material because it will absorb less heat during the wave soldering process.
- At elevated temperatures, the LEDs are more susceptible to mechanical stress. Allow the PCB to be sufficiently cooled to room temperature before handling. Do not apply stress to the LED when it is hot.
- Use wave soldering to solder the LED. Use hand soldering only for rework or touch up if unavoidable, but it must be strictly controlled to following conditions:
 - Soldering iron tip temperature = 315°C maximum.
 - Soldering duration = 2 seconds maximum.
 - Number of cycle = 1 only.
 - Power of soldering iron = 50W maximum.
- For ESD-sensitive devices, apply proper ESD precautions at the soldering station. Use only an ESD-safe soldering iron.
- Do not touch the LED package body with the soldering iron except for the soldering terminals because it may cause damage to the LED.
- Confirm beforehand whether the functionality and performance of the LED is affected by soldering with hand soldering.
- Keep the heat source at least 1.6 mm away from the LED body during soldering.
- Design an appropriate hole size to avoid problems during insertion.
- Cleaning agents from the ketone family (acetone, methyl ethylketone, and so on) and from the chlorinated hydrocarbon family (methylene chloride, trichloroethylene, carbon tetrachloride, and so on) are

not recommended for cleaning the LED displays. All of these various solvents attack or dissolve the encapsulating epoxies used to form the package of plastic LED parts.

- For the purpose of cleaning, wash with DI water only. The cleaning process should take place at room temperature only. Clear any water or moisture from the LED display immediately after washing.
- Use of *No clean* solder paste is recommended for soldering.

Figure 13: Recommended Wave Soldering Profile



NOTE: Figure 13 refers to measurements with thermocouple mounted at the bottom of the PCB.

Application Precautions

- The drive current of the LED must not exceed the maximum allowable limit across temperatures as stated in the data sheet. Constant current driving is recommended to ensure consistent performance.
- Circuit design must cater to the whole range of forward voltage (V_F) of the LEDs to ensure the intended drive current can always be achieved.
- The LED exhibits slightly different characteristics at different drive currents, which may result in a larger variation of performance (such as intensity, wavelength, and forward voltage). Set the application current as close as possible to the test current to minimize these variations.
- The LED is not intended for reverse bias. Use other appropriate components for such purposes. When driving the LED in matrix form, ensure that the reverse bias voltage does not exceed the allowable limit of the LED.

- Avoid rapid change in ambient temperatures, especially in high-humidity environments, because they cause condensation on the LED.
- If the LED is intended to be used in a harsh or outdoor environment, protect the LED against damages caused by rain, water, dust, oil, corrosive gases, external mechanical stresses, and so on.

Eye Safety Precautions

LEDs may pose optical hazards when in operation. Do not look directly at operating LEDs because it might be harmful to the eyes. For safety reasons, use appropriate shielding or personal protective equipment.

Disclaimer

Broadcom's products and software are not specifically designed, manufactured, or authorized for sale as parts, components, or assemblies for the planning, construction, maintenance, or direct operation of a nuclear facility or for use in medical devices or applications. The customer is solely responsible, and waives all rights to make claims against Broadcom or its suppliers, for all loss, damage, expense, or liability in connection with such use.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries, and/or the EU.

Copyright © 2005-2021 Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Inc. and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.



Lead (Pb) Free
RoHS Compliant

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Broadcom Limited:

[HDSP-301A](#) [HDSP-301E](#) [HDSP-301G](#) [HDSP-301Y](#) [HDSP-303A](#) [HDSP-303E](#) [HDSP-303G](#) [HDSP-303Y](#) [HDSP-561A](#) [HDSP-561E](#) [HDSP-561G](#) [HDSP-561Y](#) [HDSP-563A](#) [HDSP-563E](#) [HDSP-563G](#) [HDSP-563Y](#)