

2N2904 2N2904A  
2N2905 2N2905A

# PNP SILICON TRANSISTORS



TO-39 CASE



www.centrasemi.com

## DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N2904, 2N2905 series types are PNP silicon transistors manufactured by the epitaxial planar process, designed for small signal, general purpose and switching applications.

## MARKING: FULL PART NUMBER

**MAXIMUM RATINGS:** ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)

|  | SYMBOL         | 2N2904<br>2N2905 | 2N2904A<br>2N2905A | UNITS              |
|--|----------------|------------------|--------------------|--------------------|
| Collector-Base Voltage                         | $V_{CBO}$      | 60               | 60                 | V                  |
| Collector-Emitter Voltage                      | $V_{CEO}$      | 40               | 60                 | V                  |
| Emitter-Base Voltage                           | $V_{EBO}$      |                  | 5.0                | V                  |
| Continuous Collector Current                   | $I_C$          |                  | 0.6                | A                  |
| Power Dissipation                              | $P_D$          |                  | 0.8                | W                  |
| Power Dissipation ( $T_C=25^{\circ}\text{C}$ ) | $P_D$          |                  | 3.0                | W                  |
| Operating and Storage Junction Temperature     | $T_J, T_{stg}$ | -65 to +200      |                    | $^{\circ}\text{C}$ |

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^{\circ}\text{C}$ )

| SYMBOL        | TEST CONDITIONS  | 2N2904<br>2N2905  |     | 2N2904A<br>2N2905A |     | UNITS |
|---------------|--|-------------------|-----|--------------------|-----|-------|
|               |  | MIN               | MAX | MIN                | MAX |       |
| $I_{CBO}$     | $V_{CB}=50\text{V}$  | -                 | 20  | -                  | 10  | nA    |
| $I_{CEV}$     | $V_{CE}=30\text{V}, V_{EB}=0.5\text{V}$                    | -                 | -   | -                  | 50  | nA    |
| $BV_{CBO}$    | $I_C=10\mu\text{A}$  | 60                | -   | 60                 | -   | V     |
| $BV_{CEO}$    | $I_C=10\text{mA}$  | 40                | -   | 60                 | -   | V     |
| $BV_{EBO}$    | $I_E=10\mu\text{A}$  | 5.0               | -   | 5.0                | -   | V     |
| $V_{CE(SAT)}$ | $I_C=150\text{mA}, I_B=15\text{mA}$                        | -                 | 0.4 | -                  | 0.4 | V     |
| $V_{CE(SAT)}$ | $I_C=500\text{mA}, I_B=50\text{mA}$                        | -                 | 1.6 | -                  | 1.6 | V     |
| $V_{BE(SAT)}$ | $I_C=150\text{mA}, I_B=15\text{mA}$                        | -                 | 1.3 | -                  | 1.3 | V     |
| $V_{BE(SAT)}$ | $I_C=500\text{mA}, I_B=50\text{mA}$                        | -                 | 2.6 | -                  | 2.6 | V     |
|               |  | 2N2904<br>2N2904A |     | 2N2905<br>2N2905A  |     |       |
|               |  | MIN               | MAX | MIN                | MAX |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=100\mu\text{A}$ (2N2904, 2N2905)   | 20                | -   | 35                 | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=100\mu\text{A}$ (2N2904A, 2N2905A) | 40                | -   | 75                 | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=1.0\text{mA}$ (2N2904, 2N2905)     | 25                | -   | 50                 | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=1.0\text{mA}$ (2N2904A, 2N2905A)   | 40                | -   | 100                | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=10\text{mA}$ (2N2904, 2N2905)      | 35                | -   | 75                 | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=10\text{mA}$ (2N2904A, 2N2905A)    | 40                | -   | 100                | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=150\text{mA}$                      | 40                | 120 | 100                | 300 |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=500\text{mA}$ (2N2904, 2N2905)     | 20                | -   | 30                 | -   |       |
| $h_{FE}$      | $V_{CE}=10\text{V}, I_C=500\text{mA}$ (2N2904A, 2N2905A)   | 40                | -   | 50                 | -   |       |

R2 (6-April 2015)

2N2904 2N2904A  
2N2905 2N2905A


PNP SILICON TRANSISTORS



ELECTRICAL CHARACTERISTICS - Continued: ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)

| SYMBOL    | TEST CONDITIONS   | MIN | MAX | UNITS |
|-----------|---|-----|-----|-------|
| $f_T$     | $V_{CE}=20\text{V}$ , $I_C=50\text{mA}$ , $f=100\text{MHz}$             | 200 |     | MHz   |
| $C_{ob}$  | $V_{CB}=10\text{V}$ , $f=100\text{kHz}$                                 |     | 8.0 | pF    |
| $t_{on}$  | $V_{CC}=30\text{V}$ , $I_C=150\text{mA}$ , $I_B=15\text{mA}$            |     | 45  | ns    |
| $t_{off}$ | $V_{CC}=6.0\text{V}$ , $I_C=150\text{mA}$ , $I_{B1}=I_{B2}=15\text{mA}$ |     | 180 | ns    |

TO-39 CASE - MECHANICAL OUTLINE



| DIMENSIONS |        |       |             |      |
|------------|--------|-------|-------------|------|
| SYMBOL     | INCHES |       | MILLIMETERS |      |
|            | MIN    | MAX   | MIN         | MAX  |
| A (DIA)    | 0.335  | 0.370 | 8.51        | 9.40 |
| B (DIA)    | 0.315  | 0.335 | 8.00        | 8.51 |
| C          | -      | 0.040 | -           | 1.02 |
| D          | 0.240  | 0.260 | 6.10        | 6.60 |
| E          | 0.500  | -     | 12.70       | -    |
| F (DIA)    | 0.016  | 0.021 | 0.41        | 0.53 |
| G (DIA)    | 0.200  |       | 5.08        |      |
| H          | 0.100  |       | 2.54        |      |
| I          | 0.028  | 0.034 | 0.71        | 0.86 |
| J          | 0.029  | 0.045 | 0.74        | 1.14 |

TO-39 (REV: R1)

LEAD CODE:

- 1) Emitter
- 2) Base
- 3) Collector

MARKING: FULL PART NUMBER

R2 (6-April 2015)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centalsemi.com](http://www.centalsemi.com)

**Worldwide Field Representatives:**  
[www.centalsemi.com/wwreps](http://www.centalsemi.com/wwreps)

**Worldwide Distributors:**  
[www.centalsemi.com/wwdistributors](http://www.centalsemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centalsemi.com/terms](http://www.centalsemi.com/terms)



<https://www.centalsemi.com>

# Product End of Life Notification

|                    |          |
|--------------------|----------|
| PDN ID:            | PDN01261 |
| Notification Date: | 7/25/23  |
| Last Buy Date:     | 1/25/24  |
| Last Shipment Date | 7/25/24  |

Summary: The following PNP transistors are discontinued and are now classified as End of Life (EOL).

Although Central Semiconductor makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Portfolio Management. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

**\* All Plating types (PBFREE, TIN/LEAD) for each item listed are included in this notice.**

| Central Part Number | Suggested Replacement |
|---------------------|-----------------------|
| BFX87               | N/A                   |
| BFX88               | N/A                   |
| 2N2904              | N/A                   |
| 2N2904A             | N/A                   |
| 2N2927              | N/A                   |
| 2N3072              | N/A                   |
| 2N3120              | N/A                   |
| 2N3133              | N/A                   |
| 40406               | N/A                   |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my.centalsemi.com/submit-inquiry?type=ER> to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor:

[2N2905A TIN/LEAD](#) [2N2904A TIN/LEAD](#)