CMLT3820G

SURFACE MOUNT SILICON VERY LOW V_{CE(SAT)} NPN TRANSISTOR



SOT-563 CASE

APPLICATIONS:

- DC/DC Converters
- Voltage Clamping
- Protection Circuits
- Battery powered Cell Phones, Pagers, Digital Cameras, PDAs, Laptops, etc.

Central semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLT3820G is a very low $V_{\text{CE}(\text{SAT})}$ NPN Transistor, designed for applications where small size and efficiency are the prime requirements. Packaged in a space saving SOT-563 surface mount package, this component provides performance characteristics suitable for the most demanding size constrained applications.

MARKING CODE: 38G

FEATURES:

- Device is Halogen Free by design
- High Current (IC=1.0A)
- VCE(SAT)=0.28V MAX @ IC=1.0A
- SOT563 surface mount package
- Complementary PNP device CMLT7820G

| MAXIMUM RATINGS: (T _A =25°C) | SYMBOL | | UNITS |
|--|-----------------------------------|-------------|-------|
| Collector-Base Voltage | V _{CBO} | 80 | V |
| Collector-Emitter Voltage | V _{CEO} | 60 | V |
| Emitter-Base Voltage | V_{EBO} | 5.0 | V |
| Continuous Collector Current | I _C | 1.0 | Α |
| Peak Collector Current | I _{CM} | 2.0 | Α |
| Continuous Base Current | Ι _Β | 300 | mA |
| Power Dissipation | P_{D} | 250 | mW |
| Operating and Storage Junction Temperature | T _J , T _{stg} | -65 to +150 | °C |
| Thermal Resistance | Θ_{JA} | 500 | °C/W |

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

| SYMBOL | TEST CONDITIONS | MIN | MAX | UNITS |
|-----------------------|--|-----|-------|-------|
| I _{CBO} | V _{CB} =60V | | 100 | nA |
| I _{EBO} | V _{EB} =5.0V | | 100 | nA |
| BV _{CBO} | I _C =100μA | 80 | | V |
| BV CEO | I _C =10mA | 60 | | V |
| BVEBO | I _E =100μA | 5.0 | | V |
| VCE(SAT) | I _C =100mA, I _B =1.0mA | | 0.115 | V |
| VCE(SAT) | I _C =500mA, I _B =50mA | | 0.15 | V |
| VCE(SAT) | I _C =1.0A, I _B =100mA | | 0.28 | V |
| V _{BE} (SAT) | I _C =1.0A, I _B =50mA | | 1.1 | V |
| V _{BE} (ON) | V_{CE} =5.0V, I_{C} =1.0A | | 0.9 | V |
| h _{FE} ` ´ | V_{CE} =5.0V, I_{C} =1.0mA | 200 | | |
| hFE | V_{CE} =5.0V, I_{C} =500mA | 200 | | |
| h _{FE} | V_{CE} =5.0V, I_{C} =1.0A | 100 | | |
| f_{T} | V _{CE} =10V, I _C =50mA | 150 | | MHz |
| C _{ob} | V_{CB} =10V, I_E =0, f=1.0MHz | | 10 | pF |


R4 (29-June 2015)


CMLT3820G

SURFACE MOUNT SILICON VERY LOW V_{CE(SAT)} NPN TRANSISTOR




SOT-563 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION



| DIMENSIONS | | | | | | | |
|-------------------|--------|-------|-------------|------|--|--|--|
| | INCHES | | MILLIMETERS | | | | |
| SYMBOL | MIN | MAX | MIN | MAX | | | |
| Α | 0.0027 | 0.007 | 0.07 | 0.18 | | | |
| В | 0.008 | | 0.20 | | | | |
| С | 0.017 | 0.024 | 0.45 | 0.60 | | | |
| D | 0.059 | 0.067 | 1.50 | 1.70 | | | |
| Е | 0.020 | | 0.50 | | | | |
| F | 0.059 | 0.067 | 1.50 | 1.70 | | | |
| G | 0.043 | 0.051 | 1.10 | 1.30 | | | |
| Н | 0.006 | 0.012 | 0.15 | 0.30 | | | |
| SOT-563 (REV: R2) | | | | | | | |

LEAD CODE:

- 1) Collector
- 2) Collector
- 3) Base
- 4) Emitter
- 5) Collector
- 6) Collector

Pins 1, 2, 5 and 6 are common.

MARKING CODE: 38G

R4 (29-June 2015)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- · PbSn plating options
- Package details
- · Application notes
- · Application and design sample kits
- · Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110

Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (000)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: CMLT3820G TR PBFREE