SURFACE MOUNT SILICON HIGH SPEED SWITCHING DIODE



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPD914 is a ultra-high speed silicon switching diode manufactured by the epitaxial planar process, in an epoxy molded surface mount package, designed for high speed switching applications.

MARKING CODE: C5D



SOT-23 CASE

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Continuous Reverse Voltage	v_R	75	V
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
Continuous Forward Current	Ι _Ε	250	mA
Peak Repetitive Forward Current	I _{FRM}	250	mA
Peak Forward Surge Current, tp=1.0µs	I _{FSM}	4.0	Α
Peak Forward Surge Current, tp=1.0ms	I _{FSM}	2.0	Α
Peak Forward Surge Current, tp=1.0s	I _{FSM}	1.0	Α
Power Dissipation	P_{D}	350	mW
Operating and Storage Junction Temperature	T _J , T _{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W


ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_{R}	V _R =20V		25	nA
I_{R}	V _R =75V		5.0	μΑ
BV_R	I _R =100μA	100		V
V_{F}	I _E =10mA		1.0	V
CJ	V _R =0, f=1.0MHz		4.0	pF
t _{rr}	$I_R = I_F = 10 \text{mA}, I_{rr} = 1.0 \text{mA}, R_I = 100 \Omega$		4.0	ns

SURFACE MOUNT SILICON HIGH SPEED SWITCHING DIODE




SOT-23 CASE - MECHANICAL OUTLINE





PIN CONFIGURATION



LEAD CODE:


- 1) Anode
- 2) No Connection
- 3) Cathode

MARKING CODE: C5D

DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.003	0.007	0.08	0.18			
В	0.006	-	0.15	-			
С	-	0.005	-	0.13			
D	0.035	0.043	0.89	1.09			
E	0.110	0.120	2.80	3.05			
F	0.075		1.90				
G	0.037		0.95				
Н	0.047	0.055	1.19	1.40			
	0.083	0.098	2.10	2.49			
J	0.014	0.020	0.35	0.50			


SOT-23 (REV: R3)


R7 (12-January 2016)







TYPICAL ELECTRICAL CHARACTERISTICS















TYPICAL ELECTRICAL CHARACTERISTICS





OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: CMPD914 TR PBFREE