

SURFACE MOUNT NPN LOW NOISE SILICON TRANSISTOR



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPT2484 type is an NPN silicon low noise transistor manufactured by the epitaxial planar process, epoxy molded in a surface mount package, designed for low noise amplifier applications.

MARKING CODE: C1U

MAXIMUM RATINGS: (T _A =25°C)	SYMBOL		UNITS
Collector-Base Voltage	V _{CBO}	60	V
Collector-Emitter Voltage	VCEO	60	V
Emitter-Base Voltage	V _{EBO}	6.0	V
Continuous Collector Current	Ι _C	50	mA
Power Dissipation	PD	350	mW
Operating and Storage Junction Temperature	т _Ј , Т _{stg}	-65 to +150	°C
Thermal Resistance	ΘJΑ	357	°C/W

ELECTRICAL CHARACTERISTICS: (TA=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
ICBO	V _{CB} =45V		10	nA
ICBO	V _{CB} =45V, T _A =150°C		10	μΑ
IEBO	V _{EB} =5.0V		10	nA
BVCBO	Ι _C =10μΑ	60		V
BVCEO	I _C =10mA	60		V
BVEBO	I _E =10µA	5.0		V
V _{CE(SAT)}	I _C =1.0mA, I _B =100μA		0.35	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =1.0mA		0.95	V
h _{FE}	V _{CE} =5.0V, I _C =1.0mA	250		
h _{FE}	V _{CE} =5.0V, I _C =10mA		800	
Cob	V _{CB} =5.0V, I _E =0, f=1.0MHz		6.0	pF
C _{ib}	V _{EB} =0.5V, I _C =0, f=1.0MHz		6.0	pF
NF	V _{CE} =5.0V, I _C =10μA, R _S =10kΩ,			
	f=1.0kHz, BW=200Hz		3.0	dB

R5 (1-February 2010)









SURFACE MOUNT NPN LOW NOISE SILICON TRANSISTOR

SOT-23 CASE - MECHANICAL OUTLINE





LEAD CODE:
1) Base
2) Emittor

2) Emitter
3) Collector

MARKING CODE: C1U

DIMENSIONS							
	INCHES		MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
А	0.003	0.007	0.08	0.18			
В	0.006	-	0.15	-			
С	-	0.005	-	0.13			
D	0.035	0.043	0.89	1.09			
E	0.110	0.120	2.80	3.05			
F	0.075		1.90				
G	0.037		0.95				
Н	0.047	0.055	1.19	1.40			
	0.083	0.098	2.10	2.49			
J	0.014	0.020	0.35	0.50			

SOT-23 (REV: R3)

R5 (1-February 2010)

www.centralsemi.com

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- · Environmental regulation compliance
- Customer specific screening
- · Up-screening capabilities

· Custom product packing

Custom bar coding for shipments

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

REQUESTING PRODUCT PLATING

- If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when 1. ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's LIMITATIONS AND DAMAGES DISCLAIMER. which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: CMPT2484 TR CMPT2484 BK