

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

BSS44
BSS46

PNP SILICON TRANSISTOR

JEDEC TO-39 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR BSS44, BSS46, types are Silicon PNP Transistors designed for switching and general amplifier applications where a high collector current (5.0 AMPS) is required.

MAXIMUM RATINGS (T_A=25°C)

	SYMBOL	BSS44	BSS46	UNIT
Collector-Base Voltage	V _{CB0}	65	85	V
Collector-Emitter Voltage	V _{CE0}	60	80	V
Emitter-Base Voltage	V _{EB0}	6.0	6.0	V
Collector Current	I _C	5.0	5.0	A
Power Dissipation	P _D	1.0	1.0	W
Power Dissipation (T _C =25°C)	P _D	5.0	5.0	W
Operating and storage Junction Temperature	T _J , T _{stg}	-65 TO +200		°C
Thermal Resistance	θ _{JA}	200		°C/W
Thermal Resistance	θ _{JC}	35		°C/W

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	BSS44		BSS46		UNIT
		MIN	MAX	MIN	MAX	
I _{CB0}	V _{CB} =60V		500		500	nA
I _{CB0}	V _{CB} =60V, T _A =100°C		200		200	μA
I _{CES}	V _{CE} =60V		500		500	nA
I _{CES}	V _{CE} =60V, T _A =100°C		200		200	μA
I _{EB0}	V _{EB} =5.0V		100		100	nA
BV _{CB0}	I _C =5.0mA	65		85		V
BV _{CE0}	I _C =100mA	60		85		V
BV _{EB0}	I _E =1.0mA	6.0		6.0		V
V _{CE} (SAT)	I _C =500mA, I _B =50mA	100 TYP		-		mV
V _{CE} (SAT)	I _C =5.0A, I _B =0.5A		1.0		1.4	V
V _{BE} (SAT)	I _C =500mA, I _B =50mA	750 TYP		-		mV
V _{BE} (SAT)	I _C =5.0A, I _B =0.5A		1.6		1.6	V
h _{FE}	V _{CE} =2.0V, I _C =500mA	30		25		
h _{FE}	V _{CE} =2.0V, I _C =2.0A	40		30		
h _{FE}	V _{CE} =2.0V, I _C =5.0A	50 TYP		-		
f _T	V _{CE} =5.0V, I _C =500mA	70		70		MHz
C _{ob}	V _{CB} =10V, I _E =0, f=1.0MHz		100		100	pF
C _{ib}	V _{EB} =0.5V, I _C =0, f=1.0MHz	700 TYP		700 TYP		pF
t _{on}	V _{CC} =20V, I _C =0.5A, I _{B1} =I _{B2} =50mA	65 TYP		-		ns
t _{off}	V _{CC} =20V, I _C =0.5A, I _{B1} =I _{B2} =50mA	450 TYP		-		ns
t _{on}	V _{CC} =20V, I _C =1.0A, I _{B1} =I _{B2} =50mA	-			0.3	μs
t _{off}	V _{CC} =20V, I _C =1.0A, I _{B1} =I _{B2} =50mA	-			1.0	μs

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Central Semiconductor:](#)

[BSS44 TIN/LEAD](#)