


PNP TRANSISTOR





www.centralsemi.com

DESCRIPTION:

Semiconductor Corp.

<u>Cen</u>

The CENTRAL SEMICONDUCTOR 2N1131 is a silicon PNP transistor mounted in a hermetically sealed package designed for medium current switching applications.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T_A=25°C unless otherwise noted)

		SYMBOL		UNITS		
Collector-Base Voltage		VCBO	50	V		
Collector-Emitter Voltage (R_{BE} =10 Ω)		VCER	50	V		
Collector-Emitter Voltage		V _{CEO}	35	V		
Emitter-Base Voltage		V _{EBO}	5.0	V		
Continuous Collector Current		IC	0.6	А		
Power Dissipation (T _C =25°C)		PD	2.0	W		
Power Dissipation		PD	0.6	W		
Operating and Storage Junction Temperature		т _Ј , т _{stg}	-65 to +200	°C		
ELECTRICAL CHARACTERISTICS: (TA=25°C unless otherwise noted)						
SYMBOL	TEST CONDITIONS V _{CB} =30V	MIN	MAX 1.0	UNITS μΑ		
I _{CBO}	V _{CB} =30V, T _A =150°C		100	μA		
I _{CBO}	V _{CB} =50V		100	μA		
I _{CBO}	02		100	μA		
I _{EBO}	V _{EB} =2.0V	50	100	•		
BVCBO	I _C =100μA	50		V		
BVCER	I _C =100mA, R _{BE} =10Ω	50		V		
BVCEO	I _C =100mA	35		V		
BVEBO	Ι _Ε =100μΑ	5.0		V		
V _{CE(SAT)}	I _C =150mA, I _B =15mA		1.5	V		
V _{BE(SAT)}	I _C =150mA, I _B =15mA		1.3	V		
h _{FE}	V _{CE} =10V, I _C =5.0mA	15				
h _{FE}	V _{CE} =10V, I _C =150mA	20	45			
fT	V _{CE} =10V, I _C =50mA, f=20MHz	50		MHz		
Cob	V _{CB} =10V, I _E =0, f=100kHz		45	pF		
C _{ib}	V_{EB} =0.5V, I _C =0, f=100kHz		80	pF		


R0 (3-April 2013)



2N1131

SILICON PNP TRANSISTOR

TO-39 CASE - MECHANICAL OUTLINE



DIMENSIONS					
	INCHES		MILLIMETERS		
SYMBOL	MIN	MAX	MIN	MAX	
A (DIA)	0.335	0.370	8.51	9.40	
B (DIA)	0.315	0.335	8.00	8.51	
С	-	0.040	-	1.02	
D	0.240	0.260	6.10	6.60	
E	0.500	-	12.70	-	
F (DIA)	0.016	0.021	0.41	0.53	
G (DIA)	0.200		5.08		
Н	0.100		2.54		
	0.028	0.034	0.71	0.86	
J	0.029	0.045	0.74	1.14	
TO-39 (REV R1)					

TO-39 (REV: R1)

LEAD CODE:

1) Emitter

2) Base

3) Collector

MARKING: FULL PART NUMBER

www.centralsemi.com

R0 (3-April 2013)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- · Consolidated shipping options

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities

ss your design challenges.

· Custom product packing

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits

Custom bar coding for shipments

Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <u>www.centralsemi.com/terms</u>





http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01215
Notification Date:	2/23/22
Last Buy Date:	
Last Shipment Date	2/23/23

Summary: The 2N1131 transistor is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

Central Part Number	Suggested Replacement
2N1131	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit https://my.centralsemi.com/submit-inquiry?type=ER to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: 2N1131 TIN/LEAD