

Unregulated DC/DC Converter

TEA 1 Series, 1 Watt

- **Highly cost efficient design**
- **I/O isolation: 1'500 VDC**
- **Operating temperature range
-40 to +85 °C without derating**
- **5 VDC (±10%) input voltage range**
- **Unregulated outputs**
- **Efficiency up to 79%**
- **Industry standard SIP-4 package**
- **3-year product warranty**



The TEA 1 is an unregulated 1 Watt DC/DC SIP-4 converter series which is specifically designed to offer a low-cost solution while keeping a high quality standard. This new series focuses on a simple but effective design approach, which minimizes component and labor cost and is complemented with a complete automatization of the manufacturing process. An operating temperature range from -40°C to 85°C without derating and an I/O-isolation of 1'500 VDC enables this series to cover many different applications. The industry standard package of this converter offers a broad application range in any space, cost critical application and is especially suited for high volume projects where simple but reliable products are needed.

Models

Order Code	Input Voltage Range	Output Voltage nom.	Output Current max.	Efficiency typ.
TEA 1-0505	4.5 - 5.5 VDC (5 VDC nom.)	5 VDC	200 mA	79 %

Input Specifications

Input Current	- At no load	25 mA typ.
Surge Voltage		9 VDC max. (1 s max.)
Recommended Input Fuse		500 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)
Input Filter		Internal Capacitor

Output Specifications

Voltage Set Accuracy		±3% max. (at 60 % load)
Regulation	- Input Variation (1% Vin step)	1.5% max.
(Unregulated)	- Load Variation	See application note: www.tracopower.com/overview/tea1
Ripple and Noise	- 20 MHz Bandwidth	100 mVp-p max. 50 mVp-p typ.
Capacitive Load		2'200 µF max.
Minimum Load		10 % of Iout max.
Temperature Coefficient		±0.02 %/K max.
Start-up Time		30 ms max.
Short Circuit Protection		Limited 1 s max., Automatic recovery

Safety Specifications

Standards	- IT / Multimedia Equipment	Designed for IEC/EN/UL 62368-1 (not certified)
-----------	-----------------------------	--

General Specifications

Relative Humidity		95% max. (non condensing)
Temperature Ranges	- Operating Temperature	-40°C to +95°C
	- Case Temperature	+105°C max.
	- Storage Temperature	-55°C to +125°C
Power Derating	- High Temperature	5 %/K above 85°C
		See application note: www.tracopower.com/overview/tea1
Cooling System		Natural convection (20 LFM)
Switching Frequency		150 kHz max. (Royer) 80 kHz typ. (Royer)
Insulation System		Functional Insulation
Isolation Test Voltage	- Input to Output, 60 s	1'500 VDC
Isolation Resistance	- Input to Output, 500 VDC	1'000 MΩ min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V	30 pF max.
Reliability	- Calculated MTBF	2'000'000 h (MIL-HDBK-217F, ground benign)
Washing Process		Not allowed
Housing Material		Plastic (UL 94 V-0 rated)
Potting Material		Epoxy (UL 94 V-0 rated)
Pin Material		Phosphor Bronze (C5191)
Pin Foundation Plating		Nickel (1 µm min.)
Pin Surface Plating		Tin (3 µm min.), bright
Housing Type		Plastic Case
Mounting Type		PCB Mount
Connection Type		THD (Through-Hole Device)
Footprint Type		SIP4
Soldering Profile		Lead-Free Wave Soldering 265 °C / 5 s max.
Weight		1.6 g

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Environmental Compliance - REACH Declaration

www.tracopower.com/info/reach-declaration.pdf

REACH SVHC list compliant

REACH Annex XVII compliant

www.tracopower.com/info/rohs-declaration.pdf

Exemptions: 7a, 7c-l

(RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).)

a68ee0c2-0c08-47b2-ab89-1d2d64913973

- RoHS Declaration


- SCIP Reference Number

Supporting Documents

Overview Link (for additional Documents)

www.tracopower.com/overview/tea1

Outline Dimensions



Dimensions in mm (inch)

Tolerances: $x.x \pm 0.5$ ($x.xx \pm 0.02$)

$$x.xx \pm 0.25 \text{ (} x.xxx \pm 0.01 \text{)}$$

Pin dimension tolerance: ± 0.1 (± 0.004)

Pinout	
Pin	Function
1	−Vin (GND)
2	+Vin (Vcc)
3	−Vout
4	+Vout

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TRACO Power:](#)

[TEA 1-0505](#)