

Dual Path Highband RF Receiver

1400MHz to 2700MHz

GENERAL DESCRIPTION

This document describes the specifications for the F1180 Dual Path RF Receiver consisting of an RF Amplifier w/bypass function, Digital Step Attenuator (DSA), & RF Mixer in each signal path. Applications include Multi-mode, Multi-carrier BaseStation Receivers & Repeaters. The F1180 supports the following frequencies: RF from 1400MHz to 2700MHz, LO from 1350MHz to 2900MHz, and IF from 25MHz to 400MHz. Refer to the Part # Matrix below describing the complete series.

The F1180 RF front-end offers 16.5dB gain with 3.5dB NF and +38dBm OIP3 performance at 2100MHz. The digital step attenuator provides 30dB adjustment range in 2dB steps via the SPI interface controller. For strong signal conditions, each RF amplifier can be configured to be internally bypassed via the SPI interface. The RF front-end output and mixer input signals are bonded to separate pins to allow interstage image-reject filtering.

Each of the dual mixer paths provide 8.2dB power gain, 10.5dB NF and +35dBm OIP3 performance. An external LO signal is applied to the mixer LO port.

This device is packaged in a 7mm x 7mm, 48-pin Thin QFN with 50 ohm single-ended RF & LO inputs and 200 ohm differential IF output impedance for ease of integration into the receiver lineup.

COMPETITIVE ADVANTAGE


This device integrates the critical elements and features necessary for high performance 3G and 4G receivers in TDD and FDD wireless infrastructure

- ✓ The Amplifier bypass option improves SNR in signal blocking conditions and reduces power consumption.
- ✓ The on-chip 4-bit RF digital step attenuator (DSA) has very low insertion loss and low distortion.
- ✓ The device is optimized for < 1.9 Watts of power consumption with both paths on.
- ✓ The device has fast-settling independent power down modes for each channel for TDD applications.
- ✓ The mixer provides outstanding linearity and 2x2 performance (OIP3 > 35 dBm).

FEATURES

- Dual Path RF amp, DSA, RF Mixer & IF amp for Diversity / MIMO Receivers
- for Diversity / MIMO Receivers
- RF: 1400MHz to 2700MHz
- LO: 1350MHz to 2900MHz
- IF: 25MHz to 400MHz
- Bypassable RF amplifiers for blockers
- 16.5dB RF front-end power gain
- +38dBm RF front-end OIP3 (Bypass OFF)
- +40dBm RF front-end OIP3 (Bypass ON)
- 3.5dB front-end NF at 2100MHz
- 8.2dB mixer power gain
- +35dBm mixer OIP3
- 50 Ω RF & LO impedance
- 200 Ω differential IF output impedance
- Independent CHA, CHB path standby mode
- 30dB gain control range, 2dB steps
- 3 bit SPI control
- $I_{CC} = 365mA$
- 7mm x 7mm, 48-pin TQFN package

FUNCTIONAL BLOCK DIAGRAM



PART# MATRIX

Part#	RF freq range (MHz)	UTRA bands	IF freq range (MHz)	LO freq range (MHz)
F1130	400 - 1100	5,6,8,12,13,14,17,18,19,20, 26	25 - 400	500 - 1300
F1180	1400 - 2700	1,2,3,4,7,9,10,11,15,16,21,23,24,25,33,34,35,36,37,39,40,41	25 - 400	1350 - 2900

**Dual Path Highband RF Receiver****1400MHz to 2700MHz****ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Min	Max	Units
VCC to GND	V _{CC}	-0.3	+5.5	V
SPI DATA, SPI LE, SPI CLK, STBY_A, STBY_B	V _{Logic}	-0.3	V _{CC} + 0.25	V
IFOUT_A+, IFOUT_A-, IFOUT_B+, IFOUT_B-	I _{IF}	1.00	V _{CC} + 0.30	V
LO_IN, RFIN_A, RFIN_B, MIXRFIN_A, MIXRFIN_B	V _{Cntd}	-0.3	+0.30	V
LO_BIAS	V _{LO}	+2.1	+4.0	V
RFA_BIAS, RFB_BIAS	V _{RFIN}	-0.3	+1.50	V
RFAMP_BIAS, IFA_BIAS, IFB_BIAS	V _{Bias}	-0.3	+2.20	V
RF Input Power applied for 24 hours maximum – Bypass OFF	P _{RFIN_A} P _{RFIN_B}		+24	dBm
RF Input Power applied for 24 hours maximum – Bypass ON	P _{RFIN_A} P _{RFIN_B}		+22	dBm
RF Input Power to Mixer applied for 24 hours maximum	P _{RFMIX_A} P _{RFMIX_B}		+21	dBm
Continuous Power Dissipation	P _{diss}		2.15	W
Junction Temperature	T _j		150	°C
Storage Temperature Range	T _{st}	-65	150	°C
Lead Temperature (soldering, 10s)			260	°C
ElectroStatic Discharge – HBM (JEDEC/ESDA JS-001-2012)			1500 (Class 1C)	Volts
ElectroStatic Discharge – CDM (JEDEC 22-C101F)			750 (Class C4)	Volts

Stresses above those listed above may cause permanent damage to the device. Functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

PACKAGE THERMAL AND MOISTURE CHARACTERISTICS

θ_{JA} (Junction – Ambient)	32 °C/W
θ_{JC} (Junction – Case) [The Case is defined as the exposed paddle]	3 °C/W
Moisture Sensitivity Rating (Per J-STD-020)	MSL1

**Dual Path Highband RF Receiver****1400MHz to 2700MHz****F1180 RECOMMENDED OPERATING CONDITIONS**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Supply Voltage(s)	V_{CC}	All VCC pins	4.75		5.25	V
Operating Temperature Range	T_{CASE}	Case Temperature	-40		+105	°C
RF Freq Range	F_{RF}		1400		2700	MHz
LO Freq Range	F_{LO}		1350		2900	MHz
LO Power	P_{LO}		-3		+3	dBm
IF Freq Range	F_{IF}		25		400	MHz
RF Amplifier Source Impedance	Z_{RFIN_A} Z_{RFIN_B}	Single Ended		50		Ω
RF Amplifier Load Impedance	Z_{RFOUT_A} Z_{RFOUT_B}	Single Ended		50		Ω
Mixer RF Source Impedance	$Z_{MXRRFIN_A}$ $Z_{MXRRFIN_B}$	Single Ended		50		Ω
Mixer LO Source Impedance	$Z_{MXRLOIN_A}$ $Z_{MXRLOIN_B}$	Single Ended		50		Ω
Mixer IF Load Impedance	$Z_{MXRIFOUT_A}$ $Z_{MXRIFOUT_B}$	Differential		200		Ω



Dual Path Highband RF Receiver

1400MHz to 2700MHz

F1180 SPECIFICATION

Specifications apply at $V_{CC} = +5.00V$, $T_{CASE} = +25^{\circ}C$, $F_{RF} = 2100\text{ MHz}$, $F_{IF} = 200\text{MHz}$, $F_{LO} = 1900\text{ MHz}$, $PLO = 0\text{dBm}$, For bypass ON, RF VGA input = +5dBm, for Bypass OFF, RF VGA input = -20dBm/tone, Attenuator = 0dB, STBY_A, STBY_B = GND unless otherwise noted. Trace, Connector, and external transformer losses are de-embedded.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
General						
Logic Input High	V_{IH}	All Control Pins	1.17			V
Logic Input Low	V_{IL}	All Control Pins			0.67	V
Logic Current	I_{IH}, I_{IL}	All Control Pins	-140		+20	μA
Standby Mode Logic	STBY	STBY = V_{IH}	Power OFF			
		STBY = V_{IL}	Power ON			
Supply Current	$I_{CC\ ON}$	Bypass OFF, 2 Channels		365	410¹	mA
	I_{CC_OFF1}	Bypass ON, 1 Channels (CHA or CHB)		295	330	
	I_{CC_OFF2}	Bypass ON, 2 Channels (CHA and CHB)		230	260	
	I_{CC_STBY}	Standby Mode		20	26	
RF Switching time ³	τ_{RF}	10% to 90% risetime		250		ns
DSA Settling time ³	τ_{SET}	10% to 90% risetime		100		ns
Turn ON time ³	τ_{ON}	10% to 90% risetime		225		ns
Turn OFF time ³	τ_{OFF}	10% to 90% risetime		25		ns
Control Interface	SPI _{BIT}			14		bit
Serial Clock Speed	SPI _{CLK}			24		MHz

Note 1: Items in min/max columns in **bold italics** are Guaranteed by Test.

Note 2: Items in min/max columns that are not bold/italics are Guaranteed by Design Characterization.

Note 3: Speeds are measured after SPI programming is completed (data latched with LE = HIGH).

Note 4: Gain across the entire frequency band is affected by the inclusion of the RF switch.

Dual Path Highband RF Receiver
1400MHz to 2700MHz
F1180 SPECIFICATION (CONTINUED)

Specifications apply at $V_{CC} = +5.00V$, $T_{CASE} = +25^{\circ}C$, $F_{RF} = 2100\text{ MHz}$, $F_{IF} = 200\text{ MHz}$, $F_{LO} = 1900\text{ MHz}$, $PLO = 0\text{ dBm}$, For bypass ON, RF VGA input = +5dBm, for Bypass OFF, RF VGA input = -20dBm/tone, Attenuator = 0dB, STBY_A, STBY_B = GND unless otherwise noted. Trace, Connector, and external transformer losses are de-embedded.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
RF VGA – Bypass OFF						
Gain ⁴	G _{VGA}	F _{RF} = 1400 MHz		18.6		dB
		F _{RF} = 2100 MHz	15	16.5	18	
		F _{RF} = 2700 MHz		14.9		
Gain Flatness	G _{VGA_FLAT}	F _{RF} = 1400 MHz to 2700 MHz over any 100 MHz bandwidth		± 0.3		dB
Gain Variation	G _{VGA_T}	T _{case} = -40 to +105 °C		-0.4 to +0.1		dB
Noise Figure	NF _{VGA}	F _{RF} = 1400 MHz		3.3		dB
		F _{RF} = 2100 MHz		3.5		
		F _{RF} = 2700 MHz		3.7		
Input 1 dB Pwr Compression	IP1dB _{LBVGA}			1.0		dBm
Output Third Order Intercept Point	OIP3 _{VGA}	Pout = 0 dBm/Tone, 1 MHz tone separation	34 ²	38		dBm
RF VGA – Bypass ON						
Gain	G _{BYPASS}		-4	-3		dB
Gain Flatness	G _{BYPASS_FLAT}	F _{RF} = 1400 MHz to 2700 MHz over any 100 MHz bandwidth		± 0.1		dB
Gain Variation	G _{BYPASS_T}	T _{case} = -40 to +105 °C		± 0.25		dB
Input 1 dB Pwr Compression	IP1dB _{LBBYPASS}			23		dBm
Output Third Order Intercept Point	OIP3 _{BYPASS_0}	Attenuation = 0dB 1 MHz tone separation	38	40		dBm
Output Third Order Intercept Point	OIP3 _{BYPASS_6}	Attenuation = 6dB 1 MHz tone separation	32	34		dBm
RF VGA – Bypass ON or OFF						
DSA Gain Control Range	DSA _{RANGE}			30		dB
DSA Gain Step	DSA _{STEP}			2		dB
DSA Glitching	ATTN _A		-2.3		+1	dB
Gain Accuracy	DSA _{ACC}	ATTN ≤ 6dB	-0.4		+0.4	dB
		ATTN > 6dB	±(0.05 + 0.05*ATTN) Max			
Channel Isolation	ISO _{A/B}	RFA Input to RFB Output RFB Input to RFA Output	40	48		dB
VGA Input Match	S11 _{VGA}			-15		dB
VGA Output Match	S22 _{VGA}			-17		dB
Isolation between VGA R _{Fout} and Mixer R _{Fin}	ISO _{VGA/MIX}	No Connection between ports	45	48		dB



Dual Path Highband RF Receiver

1400MHz to 2700MHz

F1180 SPECIFICATION (CONTINUED)

Specifications apply at $V_{CC} = +5.00V$, $T_{CASE} = +25^{\circ}C$, $F_{RF} = 2100\text{ MHz}$, $F_{IF} = 200\text{MHz}$, $F_{LO} = 1900\text{ MHz}$, $PLO = 0\text{dBm}$, For bypass ON, RF VGA input = +5dBm, for Bypass OFF, RF VGA input = -20dBm/tone, Attenuator = 0dB, STBY_A, STBY_B = GND unless otherwise noted. Trace, Connector, and external transformer losses are de-embedded.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
RF VGA – Bypass OFF to ON						
Gain Range Accuracy ⁵	GRANGE _{12dB_1}	Attenuator = 12dB	6.2	7.3	8.2	dB
		Attenuator = 12dB Voltage Extremes Temperature Extremes	6.5	7.3	8.2	
	GRANGE _{12dB_2}	Attenuator = 12dB $F_{RF} = 1.5\text{ GHz}$	8.5	9.3	10.0	
	GRANGE _{12dB_3}	Attenuator = 12dB $F_{RF} = 1.8\text{ GHz}$	7.5	8.1	8.8	
	GRANGE _{12dB_4}	Attenuator = 12dB $F_{RF} = 2.6\text{ GHz}$	5.4	6.3	7.1	

Note 5: Gain difference between (bypass OFF + X dB attenuation) to (bypass ON + 0dB attenuation)

Dual Path Highband RF Receiver
1400MHz to 2700MHz
F1180 SPECIFICATION (CONTINUED)

Specifications apply at $V_{CC} = +5.00V$, $T_{CASE} = +25^{\circ}C$, $F_{RF} = 2100\text{ MHz}$, $F_{IF} = 200\text{ MHz}$, $F_{LO} = 1900\text{ MHz}$, $PLO = 0\text{ dBm}$, For bypass ON, RF VGA input = +5dBm, for Bypass OFF, RF VGA input = -20dBm/tone, Attenuator = 0dB, STBY_A, STBY_B = GND unless otherwise noted. Trace, Connector, and external transformer losses are de-embedded.

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Mixer						
Gain	G_{MXR}		7.2	8.2	9.2	dB
Gain Flatness	G_{MXR_FLAT}	$F_{RF} = 1400\text{ MHz to }2700\text{ MHz}$ over any 100 MHz bandwidth		± 0.25		dB
IF Gain Flatness Bandwidth	G_{IF_FLAT1}	Fixed LO Flatness = 0.5 dB		100		MHz
	G_{IF_FLAT2}	Fixed LO Flatness = 0.8 dB		150		MHz
Gain Variation	G_{MXR_T}	$T_{case} = -40\text{ to }+105^{\circ}C$		-0.9 to 0.7		dB
Noise Figure	NF_{MXR}			10.5		dB
Blocking Noise Figure	NF_{MXR_BLK}	+100 MHz offset Pin (Blocker) = + 4dBm		15		dB
Input 1 dB Compression	$IP1dB_{MXR}$		7	9		dBm
Output Third Order Intercept Point	$OIP3_{MXR}$	1 MHz tone separation	32	35		dBm
Output Second Order Intercept Point	$OIP2_{MXR}$	1 MHz tone separation		58		dBm
2RF – 2LO rejection	$2x2_{MXR}$	$F_{RF} - F_{IF}/2$		65		dBc
3RF – 3LO rejection	$3x3_{MXR}$	Frequency = $F_{RF} - 2*F_{IF}/3$		72		dBc
Second Harmonic	$HD2_{MXR}$			67		dBc
Third Harmonic	$HD3_{MXR}$			82		dBc
Settling Time	τ_{MXR_SET}	Pin = -13 dBm STBY VIH to VIL Time for IF to settle to 0.1 dB of final value		170		ns
Mixer RF Input Match	$S11_{MXR_RF}$			-16		dB
Mixer LO Input Match	$S11_{MXR_LO}$			-14		dB
Mixer IF Output Match	$S22_{MXR_IF}$			-19		dB
Channel Isolation	ISO_{IF}	IFOUT_A to IFOUT_B		63		dBc
RF to IF Isolation	ISO_{RI}	Pin = -10 dBm Ratio of IF level to RF leakage at IF port		48		dBc
LO to RF Leakage	ISO_{LR}			-33		dBm
LO to IF Leakage	ISO_{LI}			-30		dBm

Note 1: Items in min/max columns in **bold italics** are Guaranteed by Test.

Note 2: Items in min/max columns that are not bold/italics are Guaranteed by Design Characterization.

Note 3: Speeds are measured after SPI programming is completed (data latched with LE = HIGH).


Note 4: Gain across the entire frequency band is affected by the inclusion of the RF switch.

Dual Path Highband RF Receiver
1400MHz to 2700MHz
Serial Control Mode

Data is clocked in LSB first via serial mode. Serial data is formatted as a 14-bit word. The 14-bit word contains logic for bypass mode, 4-bit attenuator setting, and guard bit. Each word contains the following sequence:

Table 1 - 14 Bit SPI Word Sequence

D13	RX Path 2 bypass mode
D12	Guard bit
D11	RX Path 1 bypass mode
D10	Guard bit
D9	Attenuator 2
D8	Attenuator 2
D7	Attenuator 2
D6	Attenuator 2
D5	Guard bit
D4	Attenuator 1
D3	Attenuator 1
D2	Attenuator 1
D1	Attenuator 1
D0	Guard bit


Figure 1 - Serial Register Timing Diagram
PIN 8 LATCH ENABLE (LE):

When LE is high ($> V_{IH}$), the CLK input is disabled. IDT recommends keeping LE high to reduce F1180 sensitivity to CLK bus noise when SPI is not being programmed. When LE is low ($< V_{IL}$), the DATA word can be programmed into the shift registers. The programmed word is then latched into F1180 on the LE rising edge (refer to Figure 1). End of data occurs after 14th bit.

Table 2 – Attenuator Data Word Bit Sequence


Attenuation Setting	Attenuator 1 D4, D3, D2, D1	Attenuator 2 D9, D8, D7, D6
Insertion Loss	0000	0000
2 dB	0001	0001
4 dB	0010	0010
6 dB	0011	0011
8 dB	0100	0100
10 dB	0101	0101
12 dB	0110	0110
14 dB	0111	0111
16 dB	1000	1000
18 dB	1001	1001
20 dB	1010	1010
22 dB	1011	1011
24 dB	1100	1100
26 dB	1101	1101
28 dB	1110	1110
30 dB	1111	1111

Table 3 - RF Bypass Data Word Bit Sequence

RF Switch ByPass Mode	RX1 D11	RX2 D13
OFF	0	0
ON	1	1

DEFAULT REGISTER SETTING:

After power on, the default setting for the VGA is Bypass OFF mode with attenuation set to 30dB. This means the amplifier is in the signal path.

SPI TIMING:

Figure 2 - SPI Timing Diagram
Table 4 - SPI Preset Timing Parameters Calculated for 24 MHz

Parameter	Symbol	Min	Typ	Max	Units
Clock Frequency			24		MHz
Data Setup			20.83		ns
Data Hold			20.83		ns
Data to CLK Setup Time		5			ns
Data to CLK Hold Time		5			ns
Data Valid			30.83		ns
LE to CLK Setup Time		5			ns
CLK to LE Setup Time		5			ns
LE Pulse Time			20		ns

Dual Path Highband RF Receiver**1400MHz to 2700MHz****TYPICAL OPERATING CONDITIONS (TOC)**

Unless otherwise noted for the TOC graphs on pages XX to YY, the following conditions apply.


- **$V_{CC} = +5.00\text{ V}$**
- **$T_{CASE} = +25\text{ }^{\circ}\text{C}$**
- **$F_{RF} = 2100\text{ MHz}$**
- **$F_{IF} = 200\text{ MHz}$**
- **$F_{LO} = 1900\text{ MHz}$**
- **$P_{LO} = 0\text{ dBm}$**
- **RF VGA output = -5 dBm/tone**
- **RF Mixer output = 0 dBm/tone**
- **Attenuator = 0 dB**
- **STBY_A, STBY_B = GND**

Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS OFF: TYPICAL OPERATING CONDITIONS (- 1 -)


Gain vs. T_{case} [G_{VGA}]




Gain vs. V_{cc} [G_{VGA}]




Output IP3 vs. T_{case} [$OIP3_{VGA}$]




Output IP3 vs. V_{cc} [$OIP3_{VGA}$]



Channel Isolation vs. T_{case} [$ISO_{A/B}$]



Channel Isolation vs. V_{cc} [$ISO_{A/B}$]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS OFF: TYPICAL OPERATING CONDITIONS (- 2 -)


Gain Accuracy [DSA_{ACC} 1400MHz]




OIP3 vs. Attenuation [1400MHz]




Gain Accuracy [DSA_{ACC} 2100MHz]




OIP3 vs. Attenuation [2100MHz]



Gain Accuracy [DSA_{ACC} 2700MHz]



OIP3 vs. Attenuation [2700MHz]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS OFF: TYPICAL OPERATING CONDITIONS (- 3 -)


Gain vs. Input Power [1400MHz]




OIP3 vs. Input Power [1400MHz]




Gain vs. Input Power [2100MHz]




OIP3 vs. Input Power [2100MHz]



Gain vs. Input Power [2700MHz]



OIP3 vs. Input Power [2700MHz]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS OFF: TYPICAL OPERATING CONDITIONS (- 4 -)


Input Match – [S11_{VGA}]



Output Match – [S22_{VGA}]



Noise Figure [NF_{VGA}], +25 °C




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS ON: TYPICAL OPERATING CONDITIONS (- 5 -)


Gain vs. T_{case} [G_{BYPASS}]




Gain vs. V_{cc} [G_{BYPASS}]




Output IP3 vs. T_{case} [$OIP3_{BYPASS_0}$]




Output IP3 vs. V_{cc} [$OIP3_{BYPASS_0}$]



Channel Isolation vs. T_{case} [$ISO_{A/B}$]



Channel Isolation vs. V_{cc} [$ISO_{A/B}$]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS ON: TYPICAL OPERATING CONDITIONS (- 6 -)


Gain Accuracy [DSA_{ACC} 1400MHz]




OIP3 vs. Attenuation [1400MHz]




Gain Accuracy [DSA_{ACC} 2100MHz]




OIP3 vs. Attenuation [2100MHz]



Gain Accuracy [DSA_{ACC} 2700MHz]



OIP3 vs. Attenuation [2700MHz]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA BYPASS ON: TYPICAL OPERATING CONDITIONS (- 7 -)


Gain vs. Input Power [1700MHz]




Input Match - S11_{VGA}




Gain vs. Input Power [2100MHz]



Output Match - S22_{VGA}



Gain vs. Input Power [2400MHz]



Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA: TYPICAL OPERATING CONDITIONS (- 8 -)


Amplifier Bypass ON Switching Time [τ_{RF}]




Amplifier Bypass OFF Switching Time [τ_{RF}]




Amplifier Turn OFF (STBY) Time [τ_{OFF}]




Amplifier Turn ON (STBY) Time [τ_{ON}]



Attenuator Settling Speed [Min to Max, τ_{SET}]



Attenuator Settling Speed [Max to Min, τ_{SET}]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 9 -)


Gain vs. T_{case} [G_{Mixer} HS Injection]




Gain vs. T_{case} [G_{Mixer} LS Injection]




Gain vs. V_{cc} [G_{Mixer} HS Injection]




Gain vs. V_{cc} [G_{Mixer} LS Injection]



Gain vs. LO Power [G_{Mixer} HS Injection]



Gain vs. LO Power [G_{Mixer} LS Injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 10 -)


OIP3 vs. T_{case} [OIP3_{MXR} HS injection]




OIP3 vs. T_{case} [OIP3_{MXR} LS injection]




OIP3 vs. V_{cc} [OIP3_{MXR} HS injection]




OIP3 vs. V_{cc} [OIP3_{MXR} LS injection]



OIP3 vs. LO Power [OIP3_{MXR} HS injection]



OIP3 vs. LO Power [OIP3_{MXR} LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 11 -)


OIP2 vs. T_{case} [OIP2_{MXR}, HS injection]




OIP2 vs. T_{case} [OIP2_{MXR}, LS injection]




OIP2 vs. V_{cc} [OIP2_{MXR}, HS injection]




OIP2 vs. V_{cc} [OIP2_{MXR}, LS injection]



OIP2 vs. LO Power [OIP2_{MXR}, HS injection]



OIP2 vs. LO Power [OIP2_{MXR}, LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 12 -)


IP1dB vs. T_{case} [IP1dB_{MXR}, HS injection]




IP1dB vs. T_{case} [IP1dB_{MXR}, LS injection]




IP1dB vs. V_{cc} [IP1dB_{MXR}, HS injection]




IP1dB vs. V_{cc} [IP1dB_{MXR}, LS injection]



IP1dB vs. LO Power [IP1dB_{MXR}, HS injection]



IP1dB vs. LO Power [IP1dB_{MXR}, LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 13 -)


2x2 Rejection vs. T_{case} [$2x2_{MXR}$ HS rejection]




2x2 Rejection vs. T_{case} [$2x2_{MXR}$ LS rejection]




2x2 Rejection vs. V_{cc} [$2x2_{MXR}$ HS rejection]




2x2 Rejection vs. V_{cc} [$2x2_{MXR}$ LS rejection]



2x2 Rejection vs. LO Power [$2x2_{MXR}$ HS rejection]



2x2 Rejection vs. LO Power [$2x2_{MXR}$ LS rejection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 14 -)


3x3 Rejection vs. T_{case} [3x3_{MXR}, HS rejection]




3x3 Rejection vs. T_{case} [3x3_{MXR}, LS rejection]




3x3 Rejection vs. V_{cc} [3x3_{MXR}, HS rejection]




3x3 Rejection vs. V_{cc} [3x3_{MXR}, LS rejection]



3x3 Rejection vs. LO Power [3x3_{MXR}, HS rejection]



3x3 Rejection vs. LO Power [3x3_{MXR}, LS rejection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 15 -)


HD2 vs. T_{case} [HD2_{MXR}, HS injection]




HD2 vs. T_{case} [HD2_{MXR}, LS injection]




HD2 vs. V_{cc} [HD2_{MXR}, HS injection]




HD2 vs. V_{cc} [HD2_{MXR}, LS injection]



HD2 vs. LO Power [HD2_{MXR}, HS injection]



HD2 vs. LO Power [HD2_{MXR}, LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 16 -)


HD3 vs. T_{case} [HD3_{MXR}, HS injection]




HD3 vs. T_{case} [HD3_{MXR}, LS injection]




HD3 vs. V_{cc} [HD3_{MXR}, HS injection]




HD3 vs. V_{cc} [HD3_{MXR}, LS injection]



HD3 vs. LO Power [HD3_{MXR}, HS injection]



HD3 vs. LO Power [HD3_{MXR}, LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 17 -)


LO to IF Leakage vs. T_{case} [ISO_{LIF} HS injection]




LO to IF Leakage vs. T_{case} [ISO_{LIF} LS injection]




RF to IF Rejection vs. T_{case} [ISO_{RIF} HS injection]




RF to IF Rejection vs. T_{case} [ISO_{RIF} LS injection]



Channel Isolation vs. T_{case} [ISO_{IF} HS injection]



Channel Isolation vs. T_{case} [ISO_{IF} LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 18 -)


IF Gain flatness vs. T_{case} [G_{MIXR_Tr} HS injection]




IF Gain flatness vs. T_{case} [G_{MIXR_Tr} LS injection]




IF Gain flatness vs. V_{cc} [G_{MIXR_Tr} HS injection]




IF Gain flatness vs. V_{cc} [G_{MIXR_Tr} LS injection]



IF Gain flatness vs. LO Power [G_{MIXR_Tr} HS injection]



IF Gain flatness vs. LO Power [G_{MIXR_Tr} LS injection]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 19 -)


Noise Figure vs. T_{case} [NF_{MXR}, HS Injection]




Mixer RF Input Return Loss [S11_{MXR RF}]




Noise Figure vs. T_{case} [NF_{MXR} LS, Injection]




Mixer LO Port Return Loss [S11_{MXR LO}]



Noise Figure with Blocker [NF_{MXR BLK}]



Mixer IF Output Return Loss [S22_{MXR IF}]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

MIXER: TYPICAL OPERATING CONDITIONS (- 20 -)

Mixer STBY ON time [Min to Max, τ_{MXR_SET}]



Mixer STBY OFF time [Max to Min, τ_{MXR_SET}]




Dual Path Highband RF Receiver


1400MHz to 2700MHz

VGA & MIXER: TYPICAL OPERATING CONDITIONS (- 21 -)


Current Consumption vs. T_{case} [HS injection]




Current consumption vs. T_{case} [LS injection]




Current consumption vs. V_{cc} [HS injection]




Current consumption vs. V_{cc} [LS injection]



Current consumption vs. LO Power [HS injection]



Current consumption vs. LO Power [LS injection]




Dual Path Highband RF Receiver

1400MHz to 2700MHz

VGA & MIXER: TYPICAL OPERATING CONDITIONS (- 22 -)

RF Amplifier to Mixer Isolation





Dual Path Highband RF Receiver

1400MHz to 2700MHz


PACKAGE DRAWING

(7mm x 7mm 48-pin TQFN), Use Exposed PAD (EPAD) Option P1

All dimension are in mm.



SIDE VIEW




COMMON DIMENSION

SYMBOL	DIMENSION		
	MIN	NOM	MAX
D2	SEE EPAD OPTION		
E2	SEE EPAD OPTION		
L	0.30	0.40	0.50
D	6.90	7.00	7.10
E	6.90	7.00	7.10
e	0.50 BSC		
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
b	.20	.25	.30

EPAD OPTIONS:

SYMBOL	P1 (mm)			P2 (mm)		
	MIN	NOM	MAX	MIN	NOM	MAX
D2	5.55	5.65	5.75	3.05	3.15	3.25
E2	5.55	5.65	5.75	3.05	3.15	3.25

Dual Path Highband RF Receiver
1400MHz to 2700MHz
LAND PATTERN DIMENSION


EPAD 5.65 mm SQ


NOTES:

1. ALL DIMENSIONS ARE IN MM. ANGLES IN DEGREES.
2. TOP DOWN VIEW. AS VIEWED ON PCB.
3. COMPONENT OUTLINE IS SHOWN FOR REFERENCE IN GREEN.
4. LAND PATTERN IN BLUE. NSMD PATTERN ASSUMED.
5. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR SURFACE MOUNT DESIGN AND LAND PATTERN.

Dual Path Highband RF Receiver

1400MHz to 2700MHz

PIN DIAGRAM




**Dual Path Highband RF Receiver****1400MHz to 2700MHz****PIN DESCRIPTION**

Pin	Name	Function
1, 12, 23, 32, 38	VCC	Power Supply. Bypass to GND with capacitors shown in the Typical Application Circuit as close as possible to pin.
2, 4, 9, 11, 13, 15, 17, 18, 19, 20, 22, 28, 31, 33, 39, 41, 42, 43, 44, 46, 48	GND	Ground these pins.
3	RFIN_A	Channel-A VGA RF Input. Internally matched to 50Ω. AC coupled. DO NOT apply DC to this pin. Place coupling capacitor as close to the pin as possible.
5	RFAMP_BIAS	Connect a resistor to GND (refer to BOM)
6	SPI Data	Data: 1.8V CMOS compatible.
7	SPI CLK	Clock: 1.8V CMOS compatible.
8	SPI LE	Latch Enable: 1.8V CMOS compatible. See Serial Interface Section for pin description.
10	RFIN_B	Channel-B VGA RF Input. Internally matched to 50Ω. AC coupled. DO NOT apply DC to this pin. Place coupling capacitor as close to the pin as possible.
14	RFB_BIAS	Connect a resistor to GND (refer to BOM).
16	RFOUT_B	Channel-B VGA RF Output. Internally matched to 50Ω. AC coupled. DO NOT apply DC to this pin. Place coupling capacitor as close to the pin as possible.
21	MIXRFIN_B	Channel-B Mixer RF Input. Internally matched to 50Ω. DO NOT apply DC to this pin.
24	IFB_BIAS	Connect a resistor to GND (refer to BOM).
25	STBY_B	Standby Diversity Channel (Low = device power ON, High = device power OFF with SPI still powered ON)
26	IFOUT_B+	Channel-B Mixer Differential IF- Output. Connect pullup inductor from this pin to VCC.
27	IFOUT_B-	Channel-B Mixer Differential IF+ Output. Connect pullup inductor from this pin to VCC.
29	LO_BIAS	Connect a resistor to GND (refer to BOM).
30	LO_IN	Mixer Local Oscillator Input. Connect the LO to this port through the recommended coupling capacitor.
34	IFOUT_A-	Channel-A Mixer Differential IF- Output. Connect pullup inductor from this pin to VCC.
35	IFOUT_A+	Channel-A Mixer Differential IF+ Output. Connect pullup inductor from this pin to VCC.
36	STBY_A	Standby Main Channel (Low = device power ON, High = device power OFF with SPI still powered ON).
37	IFA_BIAS	Connect a resistor to GND (refer to BOM).
40	MIXRFIN_A	Channel-A Mixer RF Input. Internally matched to 50Ω. DO NOT apply DC to this pin.
45	RFOUT_A	Channel-A RF VGA Output. Internally matched to 50Ω. AC coupled. DO NOT apply DC to this pin. Place coupling capacitor as close to the pin as possible.
47	RFA_BIAS	Connect a resistor to GND (refer to BOM).
	— EP	Exposed Pad. Internally connected to GND. Solder this exposed pad to a PCB pad that uses multiple ground vias to provide heat transfer out of the device into the PCB ground planes. These multiple via grounds are also required to achieve the noted RF performance.

Dual Path Highband RF Receiver


EVKIT PICTURE

1400MHz to 2700MHz



Dual Path Highband RF Receiver EVKIT / APPLICATIONS CIRCUIT

1400MHz to 2700MHz






IDTF1180NBGI Datasheet

Dual Path Highband RF Receiver EVKIT BOM

1400MHz to 2700MHz

Item #	Part Reference	QTY	DESCRIPTION	Mfr. Part #	Mfr.
1	C2, 8, 14, 17, 20, 26, 28, 34	8	CAP CER 10000PF 16V 10% X7R 0402	GRM155R71C103KA01D	Murata
2	C1, 9, 15, 18, 21, 27, 29, 35	8	CAP CER 0.1UF 16V 10% X7R 0402	GRM155R71C104KA88D	Murata
3	C3, 7, 12, 13, 19, 30, 31	7	CAP CER 39PF 50V 5% C0G 0402	GRM1555C1H390JZ010	Murata
4	C22-25	4	CAP CER 1000PF 50V C0G 0402	GRM1555C1H102JA01D	Murata
5	R2	1	RES 12.4K OHM 1/10W 1% 0402 SMD	ERJ-2RKF1242X	Panasonic
6	R3, 5, 6, 26	4	RES 3.00K OHM 1/10W 1% 0402 SMD	ERJ-2RKF3001X	Panasonic
7	R19, 33	2	RES 3.83K OHM 1/10W 1% 0402 SMD	ERJ-2RKF3831X	Panasonic
8	R22, 30	2	RES 62.0 OHM 1/10W 1% 0402 SMD	ERJ-2RKF62R0X	Panasonic
9	R11-15, 17, 18, 24, 25, 27, 28	11	RES 0.0 OHM 1/10W 0402 SMD	ERJ-2GE0R00X	Panasonic
10	L1, 2, 10, 11	4	0805LS (2012) Ceramic Chip Inductor	0805LS-102XJLB	COILCRAFT
11	T1, 2	2	4:1 Center Tap Balun	TC4-1TG2+	Mini Circuits
12	J11, 12, 14	3	CONN HEADER VERT SGL 2POS GOLD	961102-6404-AR	3M
13	J10	1	CONN HEADER VERT DBL 4POS GOLD	67997-108HLF	FCI
14	J15	1	CONN HEADER VERT DBL 7POS GOLD	67996-114HLF	FCI
15	J1-4, 6, 8, 9	7	SMA_END_LAUNCH (Big)	142-0701-851	Emerson Johnson
16	J5, 7, 13	3	SMA_END_LAUNCH (Small)	142-0711-821	Emerson Johnson
17	U1	1	Dual Path RF Receiver 400-1100MHz	AV650B00_6ZNA	IDT
18		1	Printed Circuit Board	F1130 EVKIT REV 01	
19			Bill Of Material	0	
20	C4-6, R1, 7-10, 20, 21, 23, 29, 31, 32	0	Do not populate	N/A	N/A

TOP MARKINGS



Dual Path Highband RF Receiver

1400MHz to 2700MHz

APPLICATIONS INFORMATION


F1180 has been optimized for use in high performance RF applications from 1400 MHz to 2700 MHz.

Power Supplies

A common VCC power supply should be used for all pins requiring DC power. All supply pins should be bypassed with external capacitors to minimize noise and fast transients. Supply noise can degrade noise figure and fast transients can trigger ESD clamps and cause them to fail. Supply voltage change or transients should have a slew rate smaller than $1V/20\mu S$. In addition, all control pins should remain at 0V (+/-0.3V) while the supply voltage ramps or while it returns to zero.

Control Pin Interface

If control signal integrity is a concern and clean signals cannot be guaranteed due to overshoot, undershoot, ringing, etc., the following circuit at the input of each control pin is recommended. This applies to SPI and control pins 6, 7, 8, 25, and 36 as shown below. Note the recommended resistor and capacitor values do not necessarily match the EV kit BOM for the case of poor control signal integrity. For multiple devices driven by a single control line, the component values will need to be adjusted accordingly so as not to overload the control line.



F1180 Digital Pin Voltage & Resistance Values (pins not connected)

The following table list the resistance between various pins and ground when no DC power is applied. When the device is powered up with +5 Volts DC these same pins should have the measured voltage to ground.

Pin	Name	DC voltage (volts)	Resistance (ohms)
6	DATA	5	57K
7	CLK	5	57K
8	LE	5	57K
25	STBY_B	5	57K
36	STBY_A	5	57K

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers skilled in the art designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only for development of an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising out of your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Rev.1.0 Mar 2020)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Renesas Electronics:](#)

[F1180EVBI](#) [F1180NBGI](#) [F1180NBGI8](#)