



PTX130W is a powerful and efficient NFC controller for NFC wireless charging of battery powered devices. It not only provides wireless charging capabilities, but also serves as a complete NFC reader, complying with all NFC standards.


- Industry best output power, harvesting 1W on the listener, enabling fast charging
- Power negotiation for power dissipation optimization
- Data exchange between poller and listener allowing additional functionalities
- Simple antenna structure using standard single layer FPC technology



Features and Benefits


Market Requirement	Differentiator	Customer Benefits
High harvesting power capability	Able to harvest up to 1W on the listener Twice more than best competitor solution	Allows fast charging and charging of batteries with higher capacity
More flexibility in positioning Poller and Listener	Direct antenna connection with removal of EMI filters enable constant system matching	 More placement flexibility between charger and device antennas Allows to remove bulky magnets
Simple integration Consistent manufacturing: Same performance across devices	DiRAC: Direct antenna connection reducing the BoM count and area	 50% less effort for RF matching and certification of a device Less components allow to assure marginal NFC performance variation between devices during production
Compliant with international regulations	 NFC WLC is based on NFC globally adopted standard Architecture relies on patented Sinewave PA (removing EMI filters) 	 NFC is compliant with international regulation Faster time through certification enabled by signal's 3rd harmonics reduction due to NFC architecture
FW upgrade via NFC	 Data exchange based on globally adopted standard Transparent data channel between Poller and Listener based on globally adopted NFC standards 	 Enabling additional use cases: FW upgrade through NFC on non BLE/WiFi connected device (either on poller or listener side) General data exchange between Poller and Listener

PTX130W Block Diagram



Features:


- Low Power Detection with 100µA current consumption (2Hz polling)
- On impedance change detection
- Operation according to NFC Forum Wireless charging Renesas Electronics provides turnkey NFC wireless charging solution, combining PTX130W NFC wireless charging poller with PTX30W NFC wireless charging listener.



PTX130W/PTX30W NFC WLC Evaluation Kit

Evaluation Kit Development Features

- NFC Wireless Charging evaluation kit for high-efficiency, high-power PTX130W NFC WLC IC
- Fully integrated high-power harvesting WLC Listener (PTX30W) with integrated PMIC and LD0
- Support of NFC Forum NFC Wireless Charging protocol
- Easy-to-use, ready-to-go SW integration
- Reader functions supporting all type of NFC and standard protocols
- Bi-directional transparent data channel
- EMI filter less (DiRAC®) for high-power end-application
- RF-design supported with Config Tool and SDKs



PTX130W NFC board

Typical Applications

- Personal safety tracker
- Stylus
- Smart Ring
- Smart Glasses
- Wearable Devices
- Hearing Aid
- Medical Sensors



For more details, please visit: renesas.com/PTX130W

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Renesas Electronics:

PTX130WDQ56D13