

RX65N Group

Cloud Kit for RX65N Microcontroller Group
CK-RX65N
Quick Start Guide

Renesas RX Family
RX600 Series

All information contained in these materials, including products and product specifications, represents information on the product at the time of publication and is subject to change by Renesas Electronics Corp. without notice. Please review the latest information published by Renesas Electronics Corp. through various means, including the Renesas Electronics Corp. website (<http://www.renesas.com>).

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
4. You shall be responsible for determining what licenses are required from any third parties, and obtaining such licenses for the lawful import, export, manufacture, sales, utilization, distribution or other disposal of any products incorporating Renesas Electronics products, if required.
5. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
6. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.

7. No semiconductor product is absolutely secure. Notwithstanding any security measures or features that may be implemented in Renesas Electronics hardware or software products, Renesas Electronics shall have absolutely no liability arising out of any vulnerability or security breach, including but not limited to any unauthorized access to or use of a Renesas Electronics product or a system that uses a Renesas Electronics product. RENESAS ELECTRONICS DOES NOT WARRANT OR GUARANTEE THAT RENESAS ELECTRONICS PRODUCTS, OR ANY SYSTEMS CREATED USING RENESAS ELECTRONICS PRODUCTS WILL BE INVULNERABLE OR FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION ("Vulnerability Issues"). RENESAS ELECTRONICS DISCLAIMS ANY AND ALL RESPONSIBILITY OR LIABILITY ARISING FROM OR RELATED TO ANY VULNERABILITY ISSUES. FURTHERMORE, TO THE EXTENT PERMITTED BY APPLICABLE LAW, RENESAS ELECTRONICS DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT AND ANY RELATED OR ACCOMPANYING SOFTWARE OR HARDWARE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.
8. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
9. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
11. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
12. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
13. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
14. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.5.0-1 October 2020)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/.

General Precautions in the Handling of Microprocessing Unit and Microcontroller Unit Products

The following usage notes are applicable to all Microprocessing unit and Microcontroller unit products from Renesas. For detailed usage notes on the products covered by this document, refer to the relevant sections of the document as well as any technical updates that have been issued for the products.

1. Precaution against Electrostatic Discharge (ESD)

A strong electrical field, when exposed to a CMOS device, can cause destruction of the gate oxide and ultimately degrade the device operation. Steps must be taken to stop the generation of static electricity as much as possible, and quickly dissipate it when it occurs. Environmental control must be adequate. When it is dry, a humidifier should be used. This is recommended to avoid using insulators that can easily build up static electricity. Semiconductor devices must be stored and transported in an anti-static container, static shielding bag or conductive material. All test and measurement tools including work benches and floors must be grounded. The operator must also be grounded using a wrist strap. Semiconductor devices must not be touched with bare hands. Similar precautions must be taken for printed circuit boards with mounted semiconductor devices.

2. Processing at power-on

The state of the product is undefined at the time when power is supplied. The states of internal circuits in the LSI are indeterminate and the states of register settings and pins are undefined at the time when power is supplied. In a finished product where the reset signal is applied to the external reset pin, the states of pins are not guaranteed from the time when power is supplied until the reset process is completed. In a similar way, the states of pins in a product that is reset by an on-chip power-on reset function are not guaranteed from the time when power is supplied until the power reaches the level at which resetting is specified.

3. Input of signal during power-off state

Do not input signals or an I/O pull-up power supply while the device is powered off. The current injection that results from input of such a signal or I/O pull-up power supply may cause malfunction and the abnormal current that passes in the device at this time may cause degradation of internal elements. Follow the guideline for input signal during power-off state as described in your product documentation.

4. Handling of unused pins

Handle unused pins in accordance with the directions given under handling of unused pins in the manual. The input pins of CMOS products are generally in the high-impedance state. In operation with an unused pin in the open-circuit state, extra electromagnetic noise is induced in the vicinity of the LSI, an associated shoot-through current flows internally, and malfunctions occur due to the false recognition of the pin state as an input signal become possible.

5. Clock signals

After applying a reset, only release the reset line after the operating clock signal becomes stable. When switching the clock signal during program execution, wait until the target clock signal is stabilized. When the clock signal is generated with an external resonator or from an external oscillator during a reset, ensure that the reset line is only released after full stabilization of the clock signal. Additionally, when switching to a clock signal produced with an external resonator or by an external oscillator while program execution is in progress, wait until the target clock signal is stable.

6. Voltage application waveform at input pin

Waveform distortion due to input noise or a reflected wave may cause malfunction. If the input of the CMOS device stays in the area between V_{IL} (Max.) and V_{IH} (Min.) due to noise, for example, the device may malfunction. Take care to prevent chattering noise from entering the device when the input level is fixed, and also in the transition period when the input level passes through the area between V_{IL} (Max.) and V_{IH} (Min.).

7. Prohibition of access to reserved addresses

Access to reserved addresses is prohibited. The reserved addresses are provided for possible future expansion of functions. Do not access these addresses as the correct operation of the LSI is not guaranteed.

8. Differences between products

Before changing from one product to another, for example to a product with a different part number, confirm that the change will not lead to problems. The characteristics of a microprocessing unit or microcontroller unit products in the same group but having a different part number might differ in terms of internal memory capacity, layout pattern, and other factors, which can affect the ranges of electrical characteristics, such as characteristic values, operating margins, immunity to noise, and amount of radiated noise. When changing to a product with a different part number, implement a system-evaluation test for the given product.

Renesas CK-RX65N Disclaimer

By using this CK-RX65N, the User accepts the following terms, which are in addition to, and control in the event of disagreement, with Renesas' General Terms and Conditions available at [renesas.com/legal-notices](https://www.renesas.com/legal-notices).

The CK-RX65N is not guaranteed to be error free, and the entire risk as to the results and performance of the CK-RX65N is assumed by the User. The CK-RX65N is provided by Renesas on an "as is" basis without warranty of any kind whether express or implied, including but not limited to the implied warranties of good workmanship, fitness for a particular purpose, title, merchantability, and non-infringement of intellectual property rights. Renesas expressly disclaims any implied warranty.

Renesas does not consider the CK-RX65N to be a finished product and therefore the CK-RX65N may not comply with some requirements applicable to finished products, including, but not limited to recycling, restricted substances and electromagnetic compatibility regulations. Refer to Certifications section, for information about certifications and compliance information for the CK-RX65N. It is the kit User's responsibility to make sure the kit meets any local requirements applicable to their region.

Renesas or its affiliates shall in no event be liable for any loss of profit, loss of data, loss of contract, loss of business, damage to reputation or goodwill, any economic loss, any reprogramming or recall costs (whether the foregoing losses are direct or indirect) nor shall Renesas or its affiliates be liable for any other direct or indirect special, incidental or consequential damages arising out of or in relation to the use of this CK-RX65N, even if Renesas or its affiliates have been advised of the possibility of such damages.

Renesas has used reasonable care in preparing the information included in this document, but Renesas does not warrant that such information is error free nor does Renesas guarantee an exact match for every application or parameter to part numbers designated by other vendors listed herein. The information provided in this document is intended solely to enable the use of Renesas products. No express or implied license to any intellectual property right is granted by this document or in connection with the sale of Renesas products. Renesas reserves the right to make changes to specifications and product descriptions at any time without notice. Renesas assumes no liability for any damages incurred by you resulting from errors in or omissions from the information included herein. Renesas cannot verify, and assumes no liability for, the accuracy of information available on another company's website.

Precautions

This Cloud Kit is only intended for use in a laboratory environment under ambient temperature and humidity conditions. A safe separation distance should be used between this and any sensitive equipment. Its use outside the laboratory, classroom, study area, or similar such area invalidates conformity with the protection requirements of the Electromagnetic Compatibility Directive and could lead to prosecution.

The product generates, uses, and can radiate radio frequency energy and may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation. If this equipment causes harmful interference to radio or television reception, which can be determined by turning the equipment off or on, you are encouraged to try to correct the interference by one or more of the following measures:

- Ensure attached cables do not lie across the equipment.
- Reorient the receiving antenna.
- Increase the distance between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that which the receiver is connected.
- Power down the equipment when not in use.
- Consult the dealer or an experienced radio/TV technician for help.

Note: It is recommended that wherever possible shielded interface cables are used.

The product is potentially susceptible to certain EMC phenomena. To mitigate against them it is recommended that the following measures be undertaken:

- The user is advised that mobile phones should not be used within 10 m of the product when in use.
- The user is advised to take ESD precautions when handling the equipment.

The Cloud Kit does not represent an ideal reference design for an end product and does not fulfill the regulatory standards for an end product.

Renesas RX Family

CK-RX65N

Contents

1. Introduction.....	7
1.1 Assumptions and Advisory Notes.....	7
2. Kit Contents.....	7
3. Overview of the Quick Start Example Project.....	8
3.1 Quick Start Example Project Flow.....	8
4. Running the Quick Start Example Project.....	9
4.1 Connecting and Powering Up the CK-RX65N Board	9
4.2 Running the Quick Start Example Project.....	10
5. Customizing the Quick Start Example Project.....	16
5.1 Downloading and Installing Software and Development Tools	16
5.2 Downloading and Importing the Quick Start Example Project.....	17
5.3 Modifying, Generating, and Building the Quick Start Example Project.....	22
5.4 DHCP and Static IP settings	24
5.5 Setting Up Debug Connection between the CK-RX65N board and Host PC.....	24
5.6 Downloading and Running the Modified Quick Start Example Project	25
5.7 Firewall Dialogue	26
6. Next Steps.....	27
7. Website and Support	27
Revision History	28

Figures

Figure 1. CK-RX65N Kit Contents	7
Figure 2. Quick Start Example Project Flow.....	8
Figure 3. Connecting the CK-RX65N Board to the Host PC via USB Serial Port	9
Figure 4. USB Serial Device in Windows Device Manager	10
Figure 5. Selecting the Serial Port on Tera Term.....	11
Figure 6. Select Communication Settings	11
Figure 7. Welcome and Main Menu.....	12
Figure 8. Kit Information	12
Figure 9. Loading Sensor List.....	13
Figure 10. Sensor List with All Data	13

Figure 11. Web Server.....	14
Figure 12. Using DHCP	14
Figure 13. Using Static IP	15
Figure 14. Browser View.....	15
Figure 15. Next Steps	16
Figure 16. Creating a New Workspace.....	17
Figure 17. Launching the Workspace.....	17
Figure 18. Importing the Project	18
Figure 19. Importing Existing Projects into the Workspace.....	18
Figure 20. Clicking Next to Import Existing Projects into the Workspace	19
Figure 21. Selecting the Root Directory.....	20
Figure 22. Finishing Importing the Quick Start Example Project.....	21
Figure 23. Opening the Configurator	22
Figure 24. Opening the Configurator	22
Figure 25. Modifying the Configuration Settings	23
Figure 26. Generate Code from Smart Configurator	23
Figure 27. Building the Project	23
Figure 28. Successful Build Output	23
Figure 29. DHCP Setting in FreeRTOS_Kernel Component.....	24
Figure 30. Changing the MAC, IP, and netmask.....	24
Figure 31. Connecting the CK-RX65N Board to the Host PC via USB Debug Port.....	24
Figure 32. Selecting the Debug Option	25
Figure 33. Selecting the Debug Image	25
Figure 34. Opening the Debug Perspective	26
Figure 35. Executing the Project	26

1. Introduction

This Quick Start Guide (QSG) provides:

- An overview of the Quick Start example project that the CK-RX65N board comes pre-programmed with.
- Instructions for running the Quick Start example project.
- Instructions for importing, modifying, and building the Quick Start example project using Flexible Integration Technology (FIT) and e² studio Integrated Development Environment (IDE).

1.1 Assumptions and Advisory Notes

1. Tool experience: It is assumed that the user has prior experience working with IDEs such as e² studio and terminal emulation programs such as Tera Term.
2. Subject knowledge: It is assumed that the user has basic knowledge about microcontrollers, embedded systems, and FIT to modify the example project described in this document.
3. Prior to running the Quick Start example project or programming the CK-RX65N board, default jumper settings must be used. Refer to the CK-RX65N user's manual for the default jumper settings.
4. The screen shots provided throughout this document are for reference. The actual screen content may differ depending on the version of software and development tools used.

2. Kit Contents

The following components are included in the kit:

1. CK-RX65N v1 board
2. RYZ014A PMOD (CAT-M1 Cellular Kit)
3. SIM card (CAT-M1 Cellular Kit)
4. USB Micro B to USB A adapter cable
5. USB Micro B to USB A cable x2
6. Antenna (CAT-M1 Cellular Kit)




Figure 1. CK-RX65N Kit Contents

3. Overview of the Quick Start Example Project

The Quick Start example project allows the user to change the frequency of the on-board user LED3 (blue) using the user button (S2). The supported frequencies are 1 Hz, 5 Hz, and 10 Hz.

When the CK-RX65N board running the Quick Start example project is connected to a host PC via USB as a Full Speed CDC Device, the kit information, MCU die temperature, and user LED blinking frequency are displayed on a terminal console.

3.1 Quick Start Example Project Flow




Figure 2. Quick Start Example Project Flow

4. Running the Quick Start Example Project

This section lists the requirements and instructions to power up the CK-RX65N board and run the Quick Start example project.

Hardware Requirements

- CK-RX65N board
- Micro USB device cable x2
- A PC with at least 2 USB ports
- A router with at least 1 available full duplex Ethernet port*
- Ethernet cable

* The PHY implemented on the Cloud Kit does not support half-duplex operation.

Software Requirements

- Windows® 10 operating system
- USB Serial Drivers (included in Windows 10)
- Tera Term (or similar) terminal console application

4.1 Connecting and Powering Up the CK-RX65N Board

1. Check that:
 - A. J25 is set to link pins 2-3
 - B. J24 link is closed
 - C. J16 is set to link pins 2-3 (RUN)
2. Connect J14 and J20 on the CK-RX65N board to USB ports on the host PC using the 2 micro USB cables supplied.
3. Power LED (LED1) on the CK-RX65N board lights up white, indicating that the CK-RX65N board is powered on.

Note: If the CK-RX65N board is not powered through the Debug port (J14) the current available to the board may be limited to 100 mA.

When using the supplied RYZ014A Pmod module with other code (found here: [RYZ014A - LTE Cat-M1 Cellular IoT Module | Renesas](#)) be aware that this Pmod has a maximum operating current of 480 mA dependent upon the LTE band, Tx/Rx settings, and network coverage. Please ensure that the host board can supply sufficient power or provide supplemental USB power via CN4 on the Pmod to avoid RF instability.




Figure 3. Connecting the CK-RX65N Board to the Host PC via USB Serial Port

4.2 Running the Quick Start Example Project

To run the Quick Start example project, use the following instructions:

1. On power up or RESET, the four user LEDs will take on the following states:
 - LED2 RGB – Off
 - LED3 Green – Steady, full intensity
 - LED4 Blue – Blinking at 1 Hz frequency
 - LED6 Red – Off
2. Press the user button (S2) on the CK-RX65N board to change the blinking frequency of the user LED4 (blue). With every press of the first user button (S2), the frequency will switch from 1 Hz to 5 Hz to 10 Hz and cycle back.
3. On the host PC, open Windows Device Manager. Expand **Ports (COM & LPT)**, locate **USB Serial Device (COMxx)** and note down the COM port number for reference in the next step.




Figure 4. USB Serial Device in Windows Device Manager

4. Open Tera Term, select **Serial** and **COMxx: USB Serial Device (COMxx)** and click **OK**.




Figure 5. Selecting the Serial Port on Tera Term

5. Using the **Setup** menu pull-down, select **Serial port...** and ensure that the Baud rate is set to 115200, data is set to 8 bit, parity is set to none, and stop is set to 1 bit, as shown below.




Figure 6. Select Communication Settings

6. Complete the connection. The 'welcome and main menu' screen will be displayed.




Figure 7. Welcome and Main Menu

7. Press **1** to display the **Kit Information** including the kit name, part number, MCU ID, MCU die temperature, and the user LED's current blinking frequency.




Figure 8. Kit Information

8. Press **space** to return to the 'welcome and main menu' screen.
9. Press **2** to display the **Sensor Data**. It will display a list of all of the on board sensors along with their readings. Some of these sensors may take some time to provide data, the data will be output as soon as it is available.




Figure 9. Loading Sensor List

The following figure shows the output when all data is available.




Figure 10. Sensor List with All Data

10. Press **space** to return to the 'welcome and main menu' screen.
11. Press **3** to display the **Web Server**. This application hosts a web server on the CK-RX65N kit showing communication with the host PC as a remote client.




Figure 11. Web Server

12. Connect the Ethernet cable and press **tab**.
The CK-RX65N as supplied, is configured to use DHCP for IP address resolution. Upon successful connection, the following is displayed.





Figure 12. Using DHCP

If the DHCP fails to resolve a route or the DHCP server has been disabled, the application uses the static IP defined in the project. The following should be displayed.



```
COM4 - Tera Term VT
File Edit Setup Control Window KanjiCode Help
which requires rebuilding the code and reprogramming the kit
Kit IP Address: <192.168.42.100>
Kit IP Mask is: <255.255.255.0>
Kit IP Gateway: <192.168.42.1>

> Ensure that the host PC is using the same Gateway address. Check that
at least one bit of the IP address of the PC is different where the
binary mask bits are zero. For example, if the Mask is 255.255.255.0,
the final number of the IP address must be different from that of the
kit, and both addresses must not match with any other device on the
network

Connecting...
Connection successful

Kit IP address: <192.168.42.100>

> Open the web browser
Type the kit IP address in the address bar
The kit information will be displayed in the web browser

> Press space bar to return to MENU
```

Figure 13. Using Static IP

Note: If desired, the user may configure DHCP/static IP and MAC address using the project configuration (see section 5.4). Save the configuration and re-build, download the project to see the effects of the changes.

13. Once a successful network connection is established, open the web browser on the host PC. Type the IP address of the CK-RX65N kit as shown in the Tera Term window in the address bar of the web browser. The following should be displayed in the web browser.




Figure 14. Browser View

14. In Tera Term, press **space** to return to the 'welcome and main menu' screen.
15. Press **4** to display **Next Steps**.




Figure 15. Next Steps

Press **space** to return to the 'welcome and main menu' screen.

5. Customizing the Quick Start Example Project

This section lists the requirements and instructions for customizing the Quick Start example project.

Hardware Requirements

- CK-RX65N board
- Micro USB device cable x2
- A PC with at least 2 USB ports
- A router with at least 1 available full duplex Ethernet port*
- Ethernet cable

Software Requirements

- Windows® 10 operating system
- e² studio IDE
- Quick Start example project

5.1 Downloading and Installing Software and Development Tools

Before the Quick Start example project can be modified, it is necessary to download and install software and development tools on the host PC.

E2OB USB drivers, and e² studio are bundled in a downloadable platform installer available on the Renesas website at renesas.com/rx/ck-rx65n.

There is no need to download and install software, development tools, and drivers separately.

5.2 Downloading and Importing the Quick Start Example Project

1. Download and extract the Quick Start example project to a local directory on the host PC.
 - The Quick Start example project (source code and project files) is available in the CK-RX65N Example Projects Bundle that is available in the Downloads tab of CK-RX65N webpage at renesas.com/rx/ck-rx65n
 - Download and extract the example projects bundle (r20an0680eu0100-ck-rx65n-exampleprojects.zip) to a local directory on the host PC.
 - Browse to the Quick Start example project at r20an0680eu0100-ck-rx65n-exampleprojects\ck_rx65n_quickstart\quickstart_ck_rx65n_ep
2. Launch e² studio.
3. Browse to the Workspace where the project file is to be imported. Enter the name in the Workspace dialog box to create a new workspace.




Figure 16. Creating a New Workspace

4. Click **Launch**.




Figure 17. Launching the Workspace

5. Click **Import** from the **File** drop-down menu.




Figure 18. Importing the Project

6. In the **Import** dialog box, select **General**, and then select **Existing Projects into Workspace**.




Figure 19. Importing Existing Projects into the Workspace

7. Click **Next**.




Figure 20. Clicking Next to Import Existing Projects into the Workspace

8. Click **Select root directory** and click **Browse** to go to the location of the Quick Start example project folder.




Figure 21. Selecting the Root Directory

9. Select the Quick Start example project and click **Finish**.




Figure 22. Finishing Importing the Quick Start Example Project

5.3 Modifying, Generating, and Building the Quick Start Example Project

This section provides instructions to modify the Quick Start example project. The Quick Start example project can be modified by editing the source code and reconfiguring the properties of the MCU peripherals, pins, clocks, interrupts, and so forth.

Note: The specific modifications that can be performed to the Quick Start example project are not prescribed in this QSG.

1. Once the Quick Start example project is imported, click the **quickstart_ck_rx65n_ep.scfg** file to open the configurator. The configurator provides an easy to use interface to configure the properties of the MCU peripherals.




Figure 23. Opening the Configurator

2. For example, in the **Components** tab of the configurator, the user can click to select a module to modify its configuration settings, as required. Figure 25 illustrates modifying the **IRQ** configuration.

Note: To access the component properties, the **view** must be set to **Smart Configurator**. Using the Open Perspective button, if necessary.




Figure 24. Opening the Configurator




Figure 25. Modifying the Configuration Settings

3. After the desired modifications are made, click **Generate Code**.




Figure 26. Generate Code from Smart Configurator

4. Modify the source files in the **/src** folder as needed and save the changes.
 5. Build the project by clicking the build icon.




Figure 27. Building the Project

6. A successful build produces an output as follows.

```

Converting the DWARF information....
Constructing the output ELF image....
Saving the ELF output file rx65n_ck_quickstart.x
'Build complete.'

12:42:49 Build Finished. 0 errors, 0 warnings. (took 23s.930ms)

```

Figure 28. Successful Build Output

5.4 DHCP and Static IP settings

To modify the Ethernet based sample to enable/disable DHCP modify the file `src/frtos_config/FreeRTOSIPConfig.h` and set `ipconfigUSE_DHCP` as either 1 or 0 to enable or disable

```

/* If ipconfigUSE_DHCP is 1 then FreeRTOS+TCP will attempt to retrieve an IP
 * address, netmask, DNS server address and gateway address from a DHCP server. If
 * ipconfigUSE_DHCP is 0 then FreeRTOS+TCP will use a static IP address. The
 * stack will revert to using the static IP address even when ipconfigUSE_DHCP is
 * set to 1 if a valid configuration cannot be obtained from a DHCP server for any
 * reason. The static configuration used is that passed into the stack by the
 * FreeRTOS IPInit() function call. */
#define ipconfigUSE_DHCP 1
#define ipconfigDHCP_REGISTER_HOSTNAME 1
#define ipconfigDHCP_USES_UNICAST 1
#define ipconfigDHCP_SEND_DISCOVER_AFTER_AUTO_IP 1

```

Figure 29. DHCP Setting in FreeRTOS_Kernel Component

If DHCP is disabled, set the static IP address, net-mask and gateway address, to suit your local network.

In `quickstart_ck_rx65n_ep.scfg`, go to the components tab and select `freeRTOS_Kernel`. In that section, you can change the MAC address, IP address, and netmask as shown in the following figure.




Figure 30. Changing the MAC, IP, and netmask

5.5 Setting Up Debug Connection between the CK-RX65N board and Host PC

To program the modified Quick Start example project on to the CK-RX65N board, a debug connection is necessary between the CK-RX65N board and host PC.

1. Connect the USB cable to micro-B USB debug port (J14) of the CK-RX65N board.




Figure 31. Connecting the CK-RX65N Board to the Host PC via USB Debug Port

2. Verify that the debug LED (LED5) stops blinking and lights up green indicating that the E2OB drivers are detected by the CK-RX65N board.

5.6 Downloading and Running the Modified Quick Start Example Project

1. In e² studio, click the drop-down menu for the debug icon, select **Debug Configurations** option.




Figure 32. Selecting the Debug Option

2. In the dialogue, on the left-hand pane, expand the **Renesas GDB Hardware Debugging** and select the built image to debug. In this case, the **rx65n_ck_quickstart HardwareDebug**.




Figure 33. Selecting the Debug Image

5.7 Firewall Dialogue

1. A firewall warning may be displayed for '**e2-server-gdb.exe**'. Check the '**Private networks, such as my home or work network**' box and click '**Allow access**'.
2. A user account control dialog may be displayed. Enter the administrator password and click **Yes**.
3. A "confirm Perspective Switch" dialog box may appear. Click **Yes**.




Figure 34. Opening the Debug Perspective

4. Press **F8** or click **Resume** icon to begin executing the project.




Figure 35. Executing the Project

5. The modified Quick Start example project is programmed into the CK-RX65N board and is running. The project can be paused, stopped, or resumed using the debug controls.

6. Next Steps

1. To learn more about the CK-RX65N kit, refer to the CK-RX65N user's manual and design package available in the Documents and Download tabs respectively of the CK-RX65N webpage at renesas.com/rx/ck-rx65n
2. Renesas provides several example projects that demonstrate different capabilities of the RX MCUs. These example projects can serve as a good starting point for users to develop custom applications. Example projects (source code and project files) for CK-RX65N kit are available in the CK-RX65N Example Projects Bundle. The example projects bundle is available in the Downloads tab of CK-RX65N webpage.
 - Download and extract the example projects bundle (r20an0680eu0100-ck-rx65n-exampleprojects.zip) to a local directory on the host PC.
 - Refer to the list of all example projects (r20an0680eu0100-ck-rx65n-exampleprojects.pdf) available inside the example projects bundle.
 - Browse to the desired example project (for example: adc_ck_rx65n_ep) in the example projects bundle (r20an0680eu0100-ck-rx65n-exampleprojects\ck_rx65n\adc\adc_ck_rx65n_ep)
 - If needed RX Driver Package can be downloaded separately from the RDP repository on GitHub at: github.com/renesas/rx-driver-package
 - The archived versions of the source code of the example projects are available the example project repository.

7. Website and Support

Visit the following URLs to learn about the kit and the RX family of microcontrollers, download tools and documentation, and get support.

CK-RX65N Resources	renesas.com/rx/ck-rx65n
RX Product Information	renesas.com/rx
RX Product Support Forum	renesas.com/rx/forum
Renesas Support	renesas.com/support
Cloud Solutions	renesas.com/cloudsolutions

Revision History

Rev.	Date	Description	
		Page	Summary
1.00	May.26.22	—	Initial release

CK-RX65N – Quick Start Guide

Publication Date: May.26.22

Published by: Renesas Electronics Corporation

CK-RX65N – Quick Start Guide

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Renesas Electronics:](#)

[RTK5CK65N0S04000BE](#)