
Technical Data Sheet

Rosenberger

Cable assembly RPC-1.00 Jack - RTK 047-F - RPC-1.85 Jack

L70-386-XXX



All dimensions are in mm; tolerances: ± 3mm for A ≤ 300 mm; ± 1% for A > 300 mm *) If length "A" ≤ 90 mm marking is mount centric ± 5mm

Available variants

| Type | max. Insertion loss | Marking | Weight (g) / pce | |
|-------------|--|---------------------------------------|--|--|
| L70-386-XXX | $\leq (0.0020 * \sqrt{f[GHz]} + 0.00008 * f[GHz]) \frac{dB}{mm}$ | ROSENBERGER YYYY-WW L70-386-XXX sssss | $0.0056 \frac{g}{mm} * A[mm] + 4.60 g$ | |

Maximum possible length = 6000mm XXX - length in mm = AWW - week sssss - serial no.

Weight: Note:

First constant = Cable weight per mm; Second Constant = Connector left and Connector right weight per pce

Assembly parts

RPC-1.00 Jack Connector left Connector right RPC-1.85 Jack Cable RTK 047-F Armour none

Electrical data

Impedance 50 Ω

Frequency DC to 70 GHz

Return loss¹ ≥ 17 dB, DC to 50 GHz ≥ 14 dB, 50 to 70 GHz Insertion loss¹

Individual testing and documentation:

Measurement plot with all 4 S - Parameters (S11; S22; S21; S12) is included with the cable assembly and on the backside the care and handling instruction is printed.

see table available variants

Mechanical data

Minimum bend radius static 7.0 mm Minimum bend radius dynamic 14.0 mm

Environmental data

Temperature range - 40 °C to +85 °C **RoHS** compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|----------------|----------|------------|----------|------|---------------------------|------------------|----------|
| Marcel Panicke | 21.10.19 | Ronny Mark | 12.01.23 | b00 | 22-2195 | Marion Striegler | 11.01.23 |

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.com

Tel. : +49 8684 18-0 Email: info@rosenberger.com Page 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Rosenberger: L70-386-140