



USB A jack		Magnetic Connector		
Pin	name	cable color	description	Pin
1	VBUS	Red	+5V	2
2	D-	White	Data-	5
3	D+	Green	Data+	3
4	GND	Black	Signal Ground	4
shell	-	-	-	1

All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to

MF2K201-400L  
USB Standard-A

**Flammability**

**Connector parts**

Insulator  
Assembly parts

**Category**

material acc. to UL94 V-0  
material acc. to UL94 V-1/V-2

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

**Material and plating**

**Connector parts (MF)**

	Material	Plating / Colour
Insulator	PBT GF30	black
Housing	PBT GF30	black
Housing insert	PA	black
Piston	Brass	min 0,25 µm Au over 2,5 µm Ni
Ferrule	Brass	min 0,25 µm Au over 2,5 µm Ni
Spring	Stainless steel	
Tension relief	TPE	black
Magnet	NdFeB N52	Ni
Silicone Tube	Silicone	

**Connectors**

USB plug type A

**Electrical data**

According to USB 2.0  
Peak current 500mA

**Mechanical data**

Mating cycles min. 10.000  
Disengagement force > 10 N  
Force measured during vertical disengagement with counter connector  
Magnetic pole north to interface

**Environmental data**

Temperature range -25°C to +75°C  
RoHS compliant

**Suitable cables**

USB 2.0 Standard cable

**Available versions**

Type	Length A [mm]	pieces per box	g/piece
L99-838-500	500 +80/-80	100	25
L99-838-1500	1500 +80/-80	200	54
L99-838-1800	1800 +80/-80	200	62

**Packing**

Single packing 1 pcs per box

**Caution**

„The magnetic field of the assembled magnets is very strong. These magnets can particularly impact the function of cardiac pacemakers, implanted cardioverter-defibrillators (e.g. by unintentional actuation of reed switch), hearing aids, data storage media, monitors, and debit- and credit cards. Therefore keep sufficient safety distance from such or similar devices to prevent malfunction and danger to health. In case of any further questions please contact our customer service center.“

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
G. Lapper	03.04.2012	C. Kainzmaier	02.07.19	d00	19-1168	A. Streibl	02.07.19

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rosenberger:](#)

[L99-838-1500](#) [L99-838-500](#)