




### General Description

Silego GreenPAK SLG7NT4505 is a low power and small form device. The SoC is housed in a 2mm x 2mm TDFN package which is optimal for using with small devices.

### Features

- Low Power Consumption
- 3.3V Supply
- Pb-Free / RoHS Compliant
- Halogen-Free
- TDFN-8 Package

### Pin Configuration



### Output Summary

- 2 Outputs — Open Drain NMOS 1X

**SILEGO****SLG7NT4505****1 Hz Interrupt Generator****Pin Configuration**

Pin #	Pin Name	Type	Pin Description
1	VDD	Power	3.3V Supply Voltage
2	NMI_GATE	Digital Input	Digital Input without Schmitt trigger
3	MBL_PGOOD_MR	Digital Input	Digital Input without Schmitt trigger
4	SENSE	Analog Input/Output	Analog Input/Output
5	GND	GND	Ground
6	SMC_INIT_CLK	Digital Output	Open Drain NMOS 1X
7	SMC_RST_N	Digital Output	Open Drain NMOS 1X
8	EX_VREF	Analog Input/Output	Analog Input/Output
Exposed Bottom Pad	GND	GND	Ground

**Ordering Options & Configuration**

Part Number	Package Type
SLG7NT4505V	V = TDFN-8
SLG7NT4505VTR	VTR = TDFN-8 – Tape and Reel (3k units)



### Absolute Maximum Ratings

Parameter	Min.	Max.	Unit
$V_{DD}$ to GND	-0.3	4.6	V
Voltage at input pins	-0.3	4.6	V
Current at input pin	-1.0	1.0	mA
Storage temperature range	-65	150	°C
Junction temperature	--	150	°C
ESD Human Body Model	2000	--	V
ESD Machine Model	200	--	V

### Electrical Characteristics

Symbol	Parameter	Condition / Note	Min	Typ	Max	Unit
$V_{DD}$	Supply Voltage		3.0	3.3	3.6	V
$I_Q$	Quiescent Current	Static inputs and outputs	--	30	--	µA
$T_A$	Operating temperature		-40	25	85	°C
$V_{AIR}$	Analog Input Voltage Range		0	--	2.2	V
$V_o$	Maximal Voltage Applied to any PIN in High-Impedance State		--	--	VDD	V
$I_o$	Maximal Average or DC Current (note 1)	Per Each Chip Side	--	--	24	mA
$V_{IH}$	HIGH-Level Input Voltage	Logic Input	1.6	--	--	V
$V_{IL}$	LOW-Level Input Voltage	Logic Input	--	--	0.95	V
$V_{OL}$	LOW-Level Output Voltage (note 1)	Push-Pull , Open Drain Logic Level Outputs	0	--	0.4	V
$I_{IH}$	HIGH-Level Input Current	Logic Input Pins; $V_{IN} = VDD$	-100	--	100	nA
$I_{IL}$	LOW-Level Input Current	Logic Input Pins; $V_{IN} = 0V$	-100	--	100	nA
$I_{OL}$	LOW-Level Output Current (note 1)	Open Drain, 1X Driver	--	20	--	mA
$V_{OFFSET}$	Analog Comparator Offset Voltage	Analog Comparator 0	--	±20	--	mV
$V_{HYST}$	Analog Comparator Hysteresis Voltage (note 1)	ACMP 0	--	50	--	mV
$R_{PULL\_UP}$	Internal Pull Up Resistance	Pull up on PIN3	80	100	120	kΩ
$T_{DLY0}$	Time Delay0	Delay0	16	20	24	ms
$T_{DLY2}$	Time Delay2	Delay2	1.6	2.0	2.4	ms
$T_{SU}$	Start Up Time	After VDD reaches 2.5V	--	7	--	ms

1. Guaranteed by Design.




### Description

This is a special oscillator with supervisor system. Three inputs are used to control the oscillator. SENSE (PIN4) controls the voltage supply of the chip. If supply voltage decreases down to the threshold set by EX\_VREF (PIN8), the chip disables the oscillator and sets SMC\_INICK to LOW. When the voltage is bigger than threshold set by EX\_VREF is detected on the SENSE pin, SMC\_RST\_N (PIN7) is set to HIGH with 20 ms delay and enables the oscillator. MBL\_PWRGD\_MR\_N (PIN3) is used for manual reset of SMC\_RST\_N. Use NMI\_GATE (NMI\_GATE) to disable the oscillator.



### 1 Hz Interrupt Generator

#### Timing Diagram






# SILEGO

# SLG7NT4505

## 1 Hz Interrupt Generator

### Typical Application Circuit






# SILEGO

SLG7NT4505

1 Hz Interrupt Generator

---

## Package Top Marking



XX – Part Code Field: identifies the specific device configuration

A – Assembly Code Field: Assembly Location of the device.

DD – Date Code Field: Coded date of manufacture

L – Lot Code: Designates Lot #


R – Revision Code: Device Revision

Datasheet Revision	Programming Code Number	Part Code	Revision	Date
1.0	001	YP	A	01/15/2015




### Package Drawing and Dimensions

#### TDFN-8 Package



Symbol	Min (mm)	NOM (mm)	Max (mm)
A	0.70	0.75	0.80
A1	0.00	--	0.05
A2	--	0.55	--
A3	--	0.20	--
b	0.20	0.25	0.30
D	1.90	2.00	2.10
D2	1.50	1.60	1.70
E	1.90	2.00	2.10
E2	0.80	0.90	1.00
e		0.50 BSC	
L	0.20	0.30	0.40






#### Tape and Reel Specification

Package Type	# of Pins	Nominal Package Size (mm)	Max Units		Reel & Hub Size (mm)	Trailer A		Leader B		Pocket (mm)	
			per reel	per box		Pockets	Length (mm)	Pockets	Length (mm)	Width	Pitch
TDFN 8L 2x2mm Green	8	2x2x0.75	3000	3000	178/60	100	400	100	400	8	4

#### Carrier Tape Drawing and Dimensions

Package Type	Pocket BTM Length (mm)	Pocket BTM Width (mm)	Pocket Depth (mm)	Index Hole Pitch (mm)	Pocket Pitch (mm)	Index Hole Diameter (mm)	Index Hole to Tape Edge (mm)	Index Hole to Pocket Center (mm)	Tape Width (mm)
	A0	B0	K0	P0	P1	D0	E	F	W
TDFN 8L 2x2mm Green	2.3	2.3	1.05	4	4	1.55	1.75	3.5	8



#### Recommended Reflow Soldering Profile

Please see IPC/JEDEC J-STD-020: latest revision for reflow profile based on package volume of 3.00 mm<sup>3</sup> (nominal). More information can be found at [www.jedec.org](http://www.jedec.org).



#### Silego Website & Support

##### **Silego Technology Website**

Silego Technology provides online support via our website at <http://www.silego.com/>. This website is used as a means to make files and information easily available to customers.

For more information regarding Silego Green products, please visit:

<http://greenpak.silego.com/>  
<http://greenpak2.silego.com/>  
<http://greenpak3.silego.com/>  
<http://greenfet.silego.com/>  
<http://greenfet2.silego.com/>  
<http://greenclk.silego.com/>

Products are also available for purchase directly from Silego at the Silego Online Store at <http://www.silego.com/>

##### **Silego Technical Support**

Datasheets and errata, application notes and example designs, user guides, and hardware support documents and the latest software releases are available at the Silego website or can be requested directly at [info@silego.com](mailto:info@silego.com).

For specific GreenPAK design or applications questions and support please send e-mail requests to [GreenPAK@silego.com](mailto:GreenPAK@silego.com)

Users of Silego products can receive assistance through several channels:

##### **Online Training**

Silego Technology has live training assistance and sales support available at <http://www.silego.com/>. Please contact us to schedule a 1 on 1 training session with one of our application engineers.

##### **Contact Your Local Sales Representative**

Customers can contact their local sales representative or field application engineer (FAE) for support. Local sales offices are also available to help customers. More information regarding your local representative is available at the Silego website or send a request to [info@silego.com](mailto:info@silego.com)

##### **Contact Silego Directly**

Silego can be contacted directly via e-mail at [info@silego.com](mailto:info@silego.com) or user submission form, located at the following URL:  
<http://support.silego.com/>

##### **Other Information**

The latest Silego Technology press releases, listing of seminars and events, listings of worldwide Silego Technology offices and representatives are all available at <http://www.silego.com/>

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE

SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. SILEGO TECHNOLOGY DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. SILEGO TECHNOLOGY RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Dialog Semiconductor:](#)

[SLG7NT4505V](#)