

Datasheet revision 1.2 www.chipquik.com

48" Metal Power Strip with 12 Outlets, Surge Protected

Specifications

Power Strip Measurement: L48" x W1.653" x H1.496" (1219 x 42 x 38mm)*

Outlets: 12

Outlet Color: White

Outlet Orientation: Horizontal

Plug / Receptacle Type: NEMA 5-15P / 5-15R

Outlet Spacing: 3-3/4" (95mm) (center to center)

Power Cord: 6' (1.83m) 14/3 AWG, SJT Heavy Duty

Voltage Input/Output: 110-125V 60Hz

Current Input: 15A

Full Load: 1875VA

On/Off Switch: Yes (lighted)

Circuit Breaker: Resettable (built in the switch)

Surge Protection: Up to 400 Joules

Lines Protected: (L-N) (L-G) (N-G)

Response time: Less than 5 nanosecond

Noise Filter: EMI/RFI

Mounting on Back: Yes

Mounting Tabs: On both ends (5/8")

Mounting Clips: 3/4" (19mm) Spring Steel Clips included

Indicator: N/A

Notes

* Measurement is approximate. For installation purposes: The length of the power strip does not include the mounting tabs (approx. 0.624"/15.8mm on both ends), if any; the width does not include the size of screws (min. 0.064"/1.6mm on each side); the height does not include the receptacles (about 0.208"/5.3mm above the surface of the strip).

For use in countries and regions with 110-125V 60Hz only. Not intended for use in or around wet or potentially wet areas.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Chip Quik: EPS4126