



LPS8 LoRaWAN Gateway User Manual

Document Version: 1.0

Firmware Version: LG02_LG08--build-v5.2.1563462324-20190718-2307

Version	Description	Date
1.0	Release	2019-Aug-10

Table of Contents

1	Introduction.....	4
1.1	What is the LPS8.....	4
1.2	Specifications.....	5
1.3	Features.....	5
1.4	Hardware System Structure.....	6
1.5	LPS8 Applications	7
2	Access LPS8.....	8
2.1	Access and Configure the LPS8 via WiFi or Ethernet	8
3	Typical Network Setup	9
3.1	Overview	9
3.2	Use WAN port to access Internet.....	9
3.3	Access the Internet as a WiFi Client.....	10
3.4	Check Internet connection.....	11
4	Example: Configure as a LoRaWAN gateway	12
4.1	Create a gateway in TTN Server	13
4.2	Configure LPS8 to connect to TTN	15
4.3	Configure frequency	16
4.4	Add a LoRaWAN End Device	17
5	Linux System	20
5.1	SSH Access for Linux console	20
5.2	Edit and Transfer files	21
5.3	File System.....	21
5.4	Package maintenance system	22
6	Upgrade Linux Firmware	23
6.1	Upgrade via Web UI	23
6.2	Upgrade via Linux console.....	23

7	FAQ.....	25
7.1	<i>How can I configure for a customized frequency band?.....</i>	<i>25</i>
7.2	<i>Can I make my own firmware for LPS8? Where can I find the source code of LPS8?</i>	<i>30</i>
7.3	<i>Can I use the 868Mhz version for 915Mhz bands?.....</i>	<i>30</i>
7.4	<i>More FAQs about general LoRa questions</i>	<i>30</i>
8	Trouble Shooting.....	31
8.1	<i>I get kernel error when install new package, how to fix?</i>	<i>31</i>
8.2	<i>How to recover the LPS8 if the firmware crashes.....</i>	<i>32</i>
8.3	<i>I configured LPS8 for WiFi access and lost its IP. What to do now?.....</i>	<i>32</i>
9	Order Info	34
10	Packing Info	35
11	Support.....	35
12	Reference.....	35

1 Introduction


1.1 What is the LPS8

The LPS8 is an **open source** LoRaWAN Gateway. It lets you bridge LoRa wireless network to an IP network via **WiFi, Ethernet**. The LoRa wireless allows users to send data and reach extremely long ranges at low data-rates.

The LPS8 uses **Semtech packet forwarder** and fully compatible with LoRaWAN protocol. It includes a **SX1308 LoRa concentrator**, which provides 10 programmable parallel demodulation paths.

LPS8 has **pre-configured standard LoRaWAN frequency bands** to use for different countries. User can also **customized the frequency bands** to use in their own LoRa network.

LPS8 In a LoRaWAN IoT Network:



1.2 Specifications

Hardware System:

Linux Part:

- 400Mhz ar9331 processor
- 64MB RAM
- 16MB Flash

Interface:

- 10M/100M RJ45 Ports x 1
- WiFi : 802.11 b/g/n
- LoRaWAN Wireless
- Power Input: 5V DC, 2A
- USB 2.0 host connector x 1

WiFi Spec:

- IEEE 802.11 b/g/n
- Frequency Band: 2.4 ~ 2.462GHz
- Tx power:
 - ✓ 11n tx power : mcs7/15: 11db mcs0 : 17db
 - ✓ 11b tx power: 18db
 - ✓ 11g 54M tx power: 12db
 - ✓ 11g 6M tx power: 18db
- Wifi Sensitivity
 - ✓ 11g 54M : -71dbm
 - ✓ 11n 20M : -67dbm

LoRa Spec:

- Up to -140 dBm sensitivity with SX1257 Tx/Rx front-end
- 70 dB CW interferer rejection at 1 MHz offset
- Able to operate with negative SNR, CCR up to 9dB
- Emulates 49 x LoRa demodulators and 1 x (G)FSK demodulator
- Dual digital TX & RX radio front-end interfaces
- 10 programmable parallel demodulation paths
- Dynamic data-rate (DDR) adaptation
- True antenna diversity or simultaneous dual-band operation


1.3 Features

- ✓ Open Source OpenWrt system
- ✓ Managed by Web GUI, SSH via WAN or WiFi

- ✓ Emulates 49x LoRa demodulators
- ✓ LoRaWAN Gateway
- ✓ 10 programmable parallel demodulation paths

1.4 Hardware System Structure

LPS8 System Overview:



1.5 LPS8 Applications



2 Access LPS8

2.1 Access and Configure the LPS8 via WiFi or Ethernet

The LPS8 is configured as a WiFi Access Point by factory default. You can access and configure the LPS8 after connecting to its WiFi network, or via its WAN Ethernet port.

WiFi

At the first boot of LPS8, it will auto generate an open WiFi

network called **dragino-xxxxxx**

You can use a PC to connect to this WiFi network. The PC will get an IP address 10.130.1.xxx and the LPS8 has the default IP **10.130.1.1**

Ethernet

Alternatively, you can connect your PC to the LPS8 WAN port via Ethernet cable and obtain an IP address via DHCP.

Web Interface

Open a browser on the PC and type in the address:


<http://10.130.1.1/>

You will see the login interface of LPS8 as shown below.

The account details for Web Login are:

User Name: root

Password: dragino



3 Typical Network Setup


3.1 Overview

The LPS8 supports flexible network set up for different environments. This section describes the typical network topology can be set in LPS8. The network set up includes:

- ✓ **WAN Port Internet Mode**
- ✓ **WiFi Client Mode**
- ✓ **WiFi AP Mode**

3.2 Use WAN port to access Internet

By default, the LPS8 is set to use the WAN port to connect to an upstream network. When you connect the LPS8's WAN port to an upstream router, the LPS8 will get an IP address from the router and have Internet access via the upstream router. The network status can be checked as below:



The screenshot shows the web interface of the LPS8 device. At the top, there is a navigation bar with the device name 'dragino-1b8288' and tabs for 'Status', 'System', 'Network', 'Service', and 'Logout'. The 'Network' tab is selected. Below the navigation bar, there are two tabs: 'WAN' (selected) and 'LAN'. The main content area is titled 'Interfaces - WAN'. It contains a paragraph explaining that users can configure network interfaces, bridge them, or use VLAN notation. Below this is a 'Common Configuration' section with four sub-tabs: 'General Setup', 'Advanced Settings', 'Physical Settings', and 'Firewall Settings'. The 'General Setup' tab is active. It shows the 'Status' of the WAN interface (eth1) with details: Uptime: 0h 4m 40s, MAC: A8:40:41:1B:82:8A, RX: 729.05 KB (8419 Pkts.), TX: 11.43 KB (88 Pkts.), and IPv4: 10.130.2.171/24. The 'Protocol' is set to 'DHCP client'. The 'Hostname to send when requesting DHCP' is 'dragino-1b8288'. At the bottom, there are buttons for 'Back to Overview', 'Save & Apply', and 'Save'.


3.3 Access the Internet as a WiFi Client.

In the WiFi Client Mode, the LPS8 acts as a WiFi client and gets DHCP from an upstream router via WiFi.

The steps to set up as a WiFi Client are as below:

Step1:

In Network -> Wireless, select Radio0 interface and scan.



dragino-1b8288 Status System **Network** Service Logout AUTO REFRESH ON

radio0: Master "dragino-1b8288"

Wireless Overview

radio0

Generic MAC80211 802.11bgn
Channel: 11 (2.462 GHz) | Bitrate: ? Mbit/s

Restart
Scan
Add


0%

SSID: dragino-1b8288 | Mode: Master
BSSID: A8:40:41:1B:82:88 | Encryption: None

Disable
Edit
Remove

Step2:


Select the Wireless AP and join:



dragino-1b8288 Status System Network Service Logout AUTO REFRESH ON

Join Network: Wireless Scan

Signal	SSID	Channel	Mode	BSSID	Encryption	
100%	dragino-office	8	Master	50:64:2B:1A:B8:4D	mixed WPA/WPA2 - PSK	Join Network
84%	ChinaNet-gLnb	2	Master	A4:29:40:66:F4:E7	mixed WPA/WPA2 - PSK	Join Network



dragino-1b8288 Status System Network Service Logout

Joining Network: "dragino-office"

Replace wireless configuration ☐

☒ Check this option to delete the existing networks from this radio.

WPA passphrase *****

☒ Specify the secret encryption key here.

Name of the new network

☒ The allowed characters are: A-Z, a-z, 0-9 and _

Create / Assign firewall-zone wan: wan: 

☒ Choose the firewall zone you want to assign to this interface. Select *unspecified* to remove the interface from the associated zone or fill out the *create* field to define a new zone and attach the interface to it.


Back to scan results
Submit

Step3:

In the Network->Wireless page, disable WiFi AP network. This step is important, the LPS WiFi interface can only WiFi AP or WiFi Client mode at a time.

Note: After doing that, you will lose connection if your PC connects to the LPS8 via LPS8's WiFi network.

After successful association, the WiFi network interface can be seen in the same page:



dragino-1b8288 Status System Network Service Logout AUTO REFRESH ON

WAN WWAN LAN

Interfaces


Interface	Protocol	Uptime	MAC	RX	TX	IPv4	Buttons
LAN br-lan	Static address	2h 0m 4s	A8:40:41:1B:82:8B	1.40 MB (13346 Pkts.)	2.79 MB (10321 Pkts.)	10.130.1.1/24	Restart Stop Edit Delete
WAN eth1	DHCP client		A8:40:41:1B:82:8A	4.30 MB (51840 Pkts.)	55.77 KB (429 Pkts.)		Restart Stop Edit Delete
WWAN Client "dragino-office"	DHCP client	0h 6m 6s	A8:40:41:1B:82:88	549.38 KB (5659 Pkts.)	14.90 KB (94 Pkts.)	10.130.2.169/24	Restart Stop Edit Delete

Add new interface...

Save & Apply Save Reset

3.4 Check Internet connection

You can use the diagnostics page to check and analyze the Internet connection as shown below.



dragino-1b8288 Status System Network Service Logout

Diagnostics

Network Utilities

openwrt.org Traceroute openwrt.org Nslookup

IPV4 Ping

Install iputils-traceroute6 for IPv6 traceroute

```


PING openwrt.org (139.59.209.225): 56 data bytes
64 bytes from 139.59.209.225: seq=0 ttl=45 time=386.898 ms
64 bytes from 139.59.209.225: seq=1 ttl=45 time=401.656 ms
64 bytes from 139.59.209.225: seq=2 ttl=45 time=387.708 ms
64 bytes from 139.59.209.225: seq=3 ttl=45 time=378.894 ms
64 bytes from 139.59.209.225: seq=4 ttl=45 time=384.156 ms

--- openwrt.org ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
round-trip min/avg/max = 378.894/387.862/401.656 ms
    
```

4 Example: Configure as a LoRaWAN gateway

LPS8 is fully compatible with LoRaWAN protocol. It uses the legacy Semtech Packet forwarder to forward the LoRaWAN packets to server. The structure is as below.

LPS8 In a LoRaWAN IoT Network:



This chapter describes how to use the LPS8 to work with

[TheThingsNetwork \(TTN\) LoRaWAN Server](http://www.thethingsnetwork.org) (www.thethingsnetwork.org)

4.1 Create a gateway in TTN Server

Step 1: Get a Unique gateway ID.

Every LPS8 has a unique gateway id. The ID can be found at LoRaWAN page:

dragino-1b8288
Status
System
Network
Service
Logout

LoRa Gateway Settings

Configuration to communicate with LoRa devices and LoRaWAN server

LoRaWAN Server Settings

Server Address

Server Port

Gateway ID


Mail Address

Latitude


Longitude

The example gateway id is: **a840411b8268ffff**


Step 2: Sign up a user account in TTN server



Step 3: Create a Gateway



Click on the Gateways icon to open the page below:



After creating the gateway, you can see the gateway info, as below.



4.2 Configure LPS8 to connect to TTN

You can now configure the LPS8 to let it connect to TTN network.
Make sure your LPS8 has a working Internet Connection first.

Step1: Configure LPS8 to act as raw forwarder

dragino-1b8288

Status ▾System ▾Network ▾Service ▾Logout

IoT Service

IoT Service

Lorawan/RAW forwarder ▾

Debug Level

No debug ▾

Save & Apply

Save

Reset

DRAGINO TECHNOLOGY CO., LIMITED

Step2: Input server info and gateway id

Choose the correct the server address and gateway ID.

dragino-1b8288

Status ▾System ▾Network ▾Service ▾Logout

LoRa Gateway Settings

Configuration to communicate with LoRa devices and LoRaWAN server

LoRaWAN Server Settings

Service Provider

The Things Network ▾

Server Address

ttn-router-eu ▾

Server Port

1700

Gateway ID

a840411b8268fff

Mail Address

edwin@dragino.com

Latitude


22.73

Longitude

114.23


Check Result

After making the above settings, the LPS8 should be able to connect to TTN. Below is the result seen from TTN:



The screenshot shows the TTN Console Gateway Overview for the gateway with ID `eui-a840411b8268ffff`. The gateway is named "Gateway-1" and is owned by "edwin". The status is "connected", which is highlighted with a red box. The frequency plan is "Europe 868MHz" and the router is "ttn-router-eu". The gateway key is displayed in a masked format. The last seen time is "23 seconds ago", and there are 0 received and transmitted messages.

4.3 Configure frequency



The screenshot shows the "LoRa Gateway Settings" page in the "dragino-1b7cdc" interface. The "Radio Settings" tab is selected. The "SX1301 Configure" dropdown is set to "Europe 863_870MHz", which is highlighted with a red box. A yellow callout box with the text "Choose the right frequency plan." points to this dropdown. Other settings include "Service Provider" (The Things Network), "Server Address" (ttn-router-eu), "Server port for upstream" (1700), "Server port for downstream" (1700), "Gateway ID" (a840411b7cdc4150), and "Status keepalive in seconds" (30). There are also checkboxes for "customer radios configure" and "use sx1276 for tx", both of which are unchecked.

After making the settings above, the LPS8 will be able to act as a LoRaWAN gateway.

4.4 Add a LoRaWAN End Device

This section shows how to add a LoRaWAN End device to a LoRaWAN network and see the data from TTN web site.

We use LT-33222-L IO Controller as a reference device - the setup for other LoRaWAN devices will be similar.



Step 1: Create a Device definition in TTN with the OTAA keys from the example LT-33222-L IO Controller device.

Three codes are required to define the device in TTN:

- ✓ DEV EUI - Unique ID code for a particular device.
- ✓ APP EUI - ID code for an Application defined in TTN.
- ✓ APP Key - Unique key to secure communications with a particular device.

A set of these codes are stored in each device by the manufacturer as the default codes for that particular device. Each device is shipped with a sticker with the default Device EUI as shown below.




Note: You may be able to change these codes in a device by using a configuration facility on the device e.g. the LT-33222 uses a serial port access and a series of AT commands. Changing the codes may be necessary in the case where you have to use codes assigned by a LoRa WAN server.

For the TTN server, you can use the codes set in the device as in the following example.


Select **Add Application** to open the screen below.

Note that there is an APP EUI already created by TTN, but this is not the one set in the device. To add the APP EUI for the LT33222 device, select **Manage EUIs** and **Add EUI**, then enter the required code.



Select **Devices** and **Register Device** to open the screen below.

Enter the **Device EUI** and **APP KEY** codes, then select the App EUI from the list. Check that all three codes match those shown on the device label before saving the configuration.



Step 2: Power on LT-33222 device and it will automatically join the TTN network. After joining successfully, it will start to upload messages to the TTN. Select the Data tab and you will see the data appearing in the panel.

Note that it may take some time for the device data to appear in the TTN display.

[Applications](#) > [dragino_test_application1](#) > [Devices](#) > [It-33222-I-5362](#) > [Data](#)
[Overview](#) [Data](#) [Settings](#)
APPLICATION DATA

|| pause || clear

 Filters [uplink](#) [downlink](#) [activation](#) [ack](#) [error](#)

time	counter	port	
16:54:53	0	2	retry payload: 00 02 01 36 04 C1 04 C2 38
16:54:47			dev addr: 26 01 2C 6B app eui: FCDEC9B2D32FA6 61 dev eui: A8 40 41 00
16:54:40			dev addr: 26 01 2C 85 app eui: FCDEC9B2D32FA6 61 dev eui: A8 40 41 00
16:54:33			dev addr: 26 01 2E EC app eui: FCDEC9B2D32FA6 61 dev eui: A8 40 41 00

5 Linux System

The LPS8 is based on the OpenWrt Linux system. It is open source, and users are free to configure and modify the Linux settings.

5.1 SSH Access for Linux console

You can access the Linux console via the SSH protocol. Make sure your PC and the LPS8 are connected to the same network, then use a SSH tool (such as [putty](#) in Windows) to access it.


IP address: IP address of LPS8

Port: 22

User Name: **root**

Password: **dragino** (default)

After logging in, you will be in the Linux console and can enter commands as shown below.



```
1013021 - PuTTY
login as: root
root@10.130.2.1's password:

BusyBox v1.22.1 (2016-10-09 21:13:07 CST) built-in shell (ash)
Enter 'help' for a list of built-in commands.

  DRAGINO
W i F i , L i n u x , M C U , E m b e d d e d

OpenWRT BARRIER BREAKER 14.07
Version: Dragino-v2 IoT-3.4.0
Build Mon Oct 10 08:53:00 CST 2016

www.dragino.com

root@dragino-1347dc:~#
```


5.2 Edit and Transfer files

The LPS8 supports the **SCP protocol** and has a built-in **SFTP server**. There are many ways to edit and transfer files using these protocols.

In Windows, one of the easiest methods is using the [WinSCP](#) utility.

After establishing access via WinSCP to the device, you can use an FTP style window to drag / drop files to the LPS8, or edit the files directly in the windows.

Screenshot is as below:



5.3 File System

The LPS8 has a 16MB flash and a 64MB RAM. The /var and /tmp directories are in the RAM, so contents stored in /tmp and /var will be erased after rebooting the device. Other directories are in the flash and will remain after reboot.

The Linux system uses around 8MB ~10MB flash size which means there is not much room for user to store data in the LPS8 flash.

You can use an external USB flash memory device to extend the size of flash memory for storage.

5.4 Package maintenance system

LPS8 uses the OpenWrt [OPKG package maintenance system](#). There are more than 3000+ packages available in our package server for users to install for their applications. For example, if you want to add the *iperf* tool, you can install the related packages and configure LPS8 to use *iperf*.

Below are some example *opkg* commands. For more information please refer to the [OPKG package maintain system](#) (<https://wiki.openwrt.org/doc/techref/opkg>)

In Linux Console run:

```
root@dragino-169d30:~# opkg update // to get the latest packages list
```

```
root@dragino-169d30:~# opkg list //shows the available packages
```

```
root@dragino-169d30:~# opkg install iperf // install iperf
```

The system will automatically install the required packages as shown below.

```
root@dragino-169d30:/etc/opkg# opkg install iperf
```

```
Installing iperf (2.0.12-1) to root...
```

```
Downloading http://downloads.openwrt.org/snapshots/packages/mips\_24kc/base/iperf\_2.0.12-1\_mips\_24kc.ipk
```

```
Installing uclibcxx (0.2.4-3) to root...
```

```
Downloading http://downloads.openwrt.org/snapshots/packages/mips\_24kc/base/uclibcxx\_0.2.4-3\_mips\_24kc.ipk
```

```
Configuring uclibcxx.
```

```
Configuring iperf.
```

6 Upgrade Linux Firmware

We keep improving the LPS8 Linux side firmware for new features and bug fixes.

The latest firmware can be found on [LoRa Gateway Firmware](#),

(http://www.dragino.com/downloads/index.php?dir=LoRa_Gateway/LG02-OLG02/Firmware)

The Change Log can be found here: [Firmware Change Log](#).

(http://www.dragino.com/downloads/downloads/LoRa_Gateway/LG02-OLG02/Firmware/ChangeLog)

The file named as **xxxxx-xxxxx-squashfs-sysupgrade.bin** is the upgrade Image. There are different methods to upgrade, as below.


6.1 Upgrade via Web UI

Go to the page: **Web → System → Back Up and flash firmware**

Select the required image and click **Flash Image**. The image will be uploaded to the device, and then click **Process Update** to upgrade.

NOTE: You normally need to **uncheck** the **Keep Settings** checkbox when doing an upgrade to ensure that there is no conflict between the old settings and the new firmware. The new firmware will start up with its default settings.

The system will automatically boot into the new firmware after upgrade.



6.2 Upgrade via Linux console

SCP the firmware to the system **/var** directory and then run

```
root@OpenWrt:~# /sbin/sysupgrade -n /var/Your_Image
```

NOTE: it is important to transfer the image in the /var directory, otherwise it may exceed the available flash size.

7 FAQ

7.1 How can I configure for a customized frequency band?

You can customize your LoRaWAN channel on LPS8. For example if you want to set the gateway to meet the India LoRaIT frequency band:

LoRaIT Frequency plan for India

Channel	Frequency	Modulation / BW
0	865.400 MHz	MultiSF 125 kHz
1	865.600 MHz	MultiSF 125 kHz
2	865.800 MHz	MultiSF 125 kHz
3	866.000 MHz	MultiSF 125 kHz
4	866.200 MHz	MultiSF 125 kHz
5	866.400 MHz	MultiSF 125 kHz
6	866.600 MHz	MultiSF 125 kHz
7	866.800 MHz	MultiSF 125 kHz
LoRa	865.700 MHz	SF7 250 kHz
FSK	865.700 MHz	FSK 250 kHz, 64 kbps
RX2 channel (downlink)		
RX2	865.200 MHz	SF12 125 kHz

Step 1: Choose Frequency Band to use “Customized Bands”

LoRa Gateway Settings

Configuration to communicate with LoRa devices and LoRaWAN server

General Settings

Radio Settings

Channels Settings

IoT Service LoRaWAN/RAW forwarder ▼

Debug Level Little message output ▼

Service Provider The Things Network ▼

Server Address ttn-router-eu ▼

Server port for upstream 1700

Server port for downstream 1700

Gateway ID a840411b7e104150

Status keepalive in seconds 30

Frequency Plan Customized Bands ▼

Step 2: Configure Radio 0 & 1 Frequency

The LPS8 has two Radios from SX1308. You can configure these eight channels based on these two radios. Go to the Radio Settings page and enable Radio 0 to 865700000 and enable Radio 1 to 866500000.

General Settings

Radio Settings

Channels Settings

radio 0 enable ☒

Radio_0 frequency 865700000

Radio_0 for tx ☒

Radio_0 tx min frequency 863000000

Radio_0 tx max frequency 870000000

radio 1 enable ☒

Radio_1 frequency 866500000

Radio_1 for tx ☐

Step 3: Configure Channel Frequency.

What we need to configure for LoRa is 0~7 multiSF channel frequency and LoRa frequency as per LoRa frequency plan.

Each Channel Configure include below parameters:

- ✓ Radio used for this channel.
- ✓ Channel IF, frequency shift base on Radio Frequency.

Below are the settings for the LoRa frequency plan:

General Settings	Radio Settings	Channels Settings
Channel 0		
multiSF channel 0 enable	☒	Channel 0 frequency = radio0 - 300000Hz = 865700000 - 300000 = 865.4Mhz
multiSF channel 0 radio	radio0	
multiSF channel 0 IF	-300000	
Channel 1		
multiSF channel 1 enable	☒	Channel 1 frequency = 865.6Mhz
multiSF channel 1 radio	radio0	
multiSF channel 1 IF	-100000	
Channel 2		
multiSF channel 2 enable	☒	Channel 2 frequency = 865.8Mhz
multiSF channel 2 radio	radio0	
multiSF channel 2 IF	100000	

multiSF channel 3 enable ☒

Channel 3 frequency = 866.0Mhz

multiSF channel 3 radio multiSF channel 3 IF multiSF channel 4 enable ☒

Channel 4 frequency = 866.2Mhz

multiSF channel 4 radio multiSF channel 4 IF multiSF channel 5 enable ☒

Channel 5 frequency = 866.4Mhz

multiSF channel 5 radio multiSF channel 5 IF multiSF channel 6 enable ☒

Channel 6 frequency = 866.6Mhz

multiSF channel 6 radio multiSF channel 6 IF multiSF channel 7 enable ☒

Channel 7 frequency = 866.8Mhz

multiSF channel 7 radio multiSF channel 7 IF lorastd channel enable ☒

Channel LoRaSTDfrequency = 865.7Mhz, SF7, BW250Khz

LoRa channel radio LoRa channel IF LoRa channel SF LoRa channel BW

Step 4: Save & Apply & check result in logread page.**Logread**[FreqINFO](#) [Report](#) [RxDJson](#) [ErrorMsg](#)

SX1301 Channels frequency

chan_multiSF_0
LORA MAC, 125kHz, all SF, 865400000 Hz

chan_multiSF_1
LORA MAC, 125kHz, all SF, 865600000 Hz

chan_multiSF_2
LORA MAC, 125kHz, all SF, 865800000 Hz

chan_multiSF_3
LORA MAC, 125kHz, all SF, 866000000 Hz

chan_multiSF_4
LORA MAC, 125kHz, all SF, 866200000 Hz

chan_multiSF_5
LORA MAC, 125kHz, all SF, 866400000 Hz

7.2 Can I make my own firmware for LPS8?

Where can I find the source code of LPS8?

Yes, You can make your own firmware for the LPS8 for branding purposes or to add customized applications.

The LPS8 source code and compile instructions can be found at:

https://github.com/dragino/openwrt_lede-18.06

7.3 Can I use the 868Mhz version for 915Mhz bands?

It is possible but the distance will be very short, you can select US915 frequency band in 868Mhz version hardware. It will work but you will see the performance is greatly decreased because the 868Mhz version has an RF filter for band 863~870Mhz, and all other frequencies will have high attenuation.

7.4 More FAQs about general LoRa questions

We keep updating more FAQs in our WiKi about general questions.

The Wiki link is here:

http://wiki.dragino.com/index.php?title=LoRa_Questions

8 Trouble Shooting

8.1 I get kernel error when install new package, how to fix?

In some cases, when installing a package with **opkg**, it will generate a kernel error such as below due to a mismatch in the kernel ID:

```
root@dragino-16c538:~# opkg install kmod-dragino2-si3217x_3.10.49+0.2-1_ar71xx.ipk
Installing kmod-dragino2-si3217x (3.10.49+0.2-1) to root...
Collected errors:
* satisfy_dependencies_for: Cannot satisfy the following dependencies for kmod-dragino2-si3217x:
*   kernel (= 3.10.49-1-4917516478a753314254643facdf360a) *
* opkg_install_cmd: Cannot install package kmod-dragino2-si3217x.
```

In this case, you can use the `--force-depends` option to install such package as long as the actual kernel version is the same.


```
Opkg install kmod-dragino2-si3217x_3.10.49+0.2-1_ar71xx.ipk --force-depends
```

8.2 How to recover the LPS8 if the firmware crashes

LPS8 provides the user with full control on its Linux system, so it is possible that the device will brick and can't boot after an improper modification in some boot files. In this case, the user can recover the whole Linux system by uploading a new firmware via Web Failsafe mode.

Procedure is as below:

- Use an RJ45 cable to connect the PC to LPS8's WAN port directly.
- Set the PC to a static IP of 192.168.255.x, Netmask 255.255.255.0
- Press and hold the toggle button and power on the device.
- All LEDs of the device will blink, release the toggle button after **four** blinks
- All LEDs will then blink very fast once, this means that the device has detected a network connection and will enter into the Web-Failsafe mode. Your PC should be able to ping 192.168.255.1 after device enters this mode.
- Open 192.168.255.1 in web browser.
- Select a [squashfs-sysupgrade](#) type firmware and update firmware.



Note: If you see all LEDs blink very fast in Step 5, this means the network connection is established. If in this case, the PC is still not able to see the web page, you can debug as follows:

- ✓ Try different browser.
- ✓ Check if your PC is set to static IP address of 192.168.255.x
- ✓ Check if you have connected two RJ45 cables to device. If so, remove the unused one

8.3 I configured LPS8 for WiFi access and lost its IP. What to do now?


The LPS8 has a fall-back IP address on its WAN port. This IP is always enabled so you can use the fall-back IP to access LPS8 no matter what the WiFi IP is. The fall back IP is useful for connecting and debug the unit.

(Note: fallback IP can be disabled in the WAN and DHCP page)

Steps to connect via fall back IP:

1. Connect PC's Ethernet port to LG01's WAN port
2. Configure PC's Ethernet port has
IP: 172.31.255.253 and
Netmask: 255.255.255.252

As below photo:



3. In the PC, use IP address 172.31.255.254 to access the LPS8 via Web or Console.

9 Order Info

PART: LPS8-XXX-YYY:

XXX: Frequency Band

- **868**: valid frequency: 863Mhz ~ 870Mhz. for band EU868 or IN865.
- **915**: valid frequency: 902Mhz ~ 928Mhz. for bands US915, AU915, AS923 or KR920

10 Packing Info

Package Includes:

- ✓ LPS8 LoRa Gateway x 1
- ✓ Stick Antenna for LoRa RF part. Frequency is one of 470 or 868 or 915Mhz depends the model ordered
- ✓ Packaging with environmental protection paper box

Dimension and weight:

- ✓ Device Size: 12 x 12 x 2.5 cm
- ✓ Device Weight:
- ✓ Package Size / pcs :
- ✓ Weight / pcs :
- ✓ Carton dimension:
- ✓ Weight / carton :

11 Support

- Try to see if your questions already answered in the [wiki](#).
- Support is provided Monday to Friday, from 09:00 to 18:00 GMT+8.
Due to different timezones we cannot offer live support. However, your questions will be answered as soon as possible in the before mentioned schedule.
- Provide as much information as possible regarding your enquiry (product models, accurately describe your problem and steps to replicate it etc) and send a mail to:

support@dragino.com

12 Reference

- ✧ Source code for LPS8 LoRa Gateway
https://github.com/dragino/openwrt_lede-18.06
- ✧ OpenWrt official Wiki
<http://www.openwrt.org/>
- ✧ Firmware
http://www.dragino.com/downloads/index.php?dir=LoRa_Gateway/LPS8-OLPS8/Firmware/

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Seeed Studio:](#)

[110991331](#)