



Enhanced Universal Platform ARM9™ System-on-Chip Processor High-Performance Design Includes PCMCIA I/F, Graphics Accelerator and IDE

EP9315

The EP9315 is a highly integrated system-on-chip processor that paves the way for a multitude of next-generation consumer and industrial electronic products. Designers of digital media servers and jukeboxes, telematic control systems, thin clients, set-top boxes, point-of sale terminals, industrial and building controls, biometric security

systems, NAS, security, DVR, VOIP, fitness equipment, home automation and GPS devices will benefit from the EP9315's integrated architecture and advanced features. In fact, with amazingly agile performance provided by a 200 MHz ARM920T processor, and featuring an incredibly wide breadth of peripheral interfaces, the EP9315 is well suited to

an even broader range of high volume applications. Furthermore, by enabling or disabling the EP9315's peripheral interfaces, designers can reduce development costs and accelerate time to market by creating a single platform that can be easily modified to deliver a variety of differentiated end products.

EP9315 FEATURES

- **200 MHz ARM920T Processor**
 - 16 KB data cache and 16 KB instruction cache
 - MMU enabling Linux® and Windows CE®
 - 100 MHz system bus
- **MaverickCrunch™ Math Engine**
 - Floating point, integer and signal processing instructions
 - Hardware interlocks allow in-line coding
- **MaverickKey™ IDs for Digital Rights Management or Design IP Security**
 - 32-bit unique ID and 128-bit random ID
- **Integrated Peripheral Interfaces**
 - PCMCIA interface
 - Graphics accelerator
 - EIDE, up to 2 devices
 - 1/10/100 Mbps Ethernet MAC
 - Three-port USB 2.0 Full Speed host (OHCI)
 - Three UARTs (16550 Type)
 - IrDA interface, slow and fast mode
 - LCD interface with dedicated SDRAM channel
 - Touch screen interface
 - SPI™ port
 - AC'97 interface
 - I2S interface, up to 6 channels
 - 8x8 keypad scanner
- **External Memory Options**
 - 32-bit SDRAM interface, up to four banks
 - 32/16/8-bit SRAM/Flash/ROM I/F
 - Serial EEPROM interface
- **Internal Peripherals**
 - Real-Time clock with software trim
 - 12 DMA channels for data transfer that maximizes system performance
 - Boot ROM
 - Dual PLLs control all clock domains
 - Watchdog timer
 - Two general purpose 16-bit timers
 - General purpose 32-bit timer
 - 40-bit debug timer
- **General-Purpose I/Os**
 - 16 enhanced GPIOs including interrupt capability
 - 49 additional optional GPIOs on peripherals

OVERVIEW

High-Performance ARM920T Processor Core

The EP9315 features an advanced ARM920T processor design with an MMU that supports Linux®, Windows CE®, and many other embedded operating systems. The ARM920T's 32-bit microcontroller architecture, with a five-stage pipeline, delivers impressive performance at very low power. The included 16 KB instruction cache and 16 KB data cache provide zero-cycle latency to the current program and data, or can be locked to provide guaranteed no-latency access to critical instructions and data. For applications with instruction memory size restrictions, the ARM920T's compressed Thumb® instruction set provides a space-efficient design that maximizes external instruction memory usage.

MaverickCrunch™ Math Engine for Ultra-Fast Math Processing

The MaverickCrunch engine is an advanced mixed-mode math coprocessor that greatly accelerates the single and double-precision integer and floating-point processing capabilities of the ARM920T processor core. The engine simplifies the end-user's programming task by using predefined coprocessor instructions, by utilizing standard ARM compiler tools, and by requiring just one debugger session for the entire system. Furthermore, the integrated design provides a single instruction stream and the advantage of zero latency for cached instructions. To emulate this capability, competitors' solutions add a DSP to the system, which requires separate compiler/linker/debugger tool sets. This additional DSP requires programmers to write two separate programs and debug them simultaneously, which can result in frustration and costly delays.

The single-cycle integer multiply-accumulate instruction in the MaverickCrunch engine allows the EP9315 to offer unique speed and performance while encoding digital audio and video formats, processing data via Ethernet, and performing other math-intensive computing and data-processing functions in consumer and industrial electronics.

Graphics Accelerator

The EP9315 contains a hardware graphics acceleration engine that improves graphic performance by handling block copy, block fill and hardware line draw operations. The graphics accelerator is used in the system to offload graphics operations from the processor.

PCMCIA Interface

The PCMCIA interface supports two 8-bit or one 16-bit PCMCIA PC card. These devices are credit-card-sized peripherals that add memory, mass storage, and I/O capabilities to computer systems, and can be used to further broaden the options of a designer's platform.

MaverickKey™ Unique ID Secures Digital Content and OEM Designs

MaverickKey unique hardware programmed IDs provide an excellent solution to the growing concern over secure Web content and commerce. With Internet security playing an important role in the delivery of digital media such as books or music, traditional software methods are quickly becoming unreliable. The MaverickKey unique IDs provide OEMs with a method of utilizing specific hardware IDs for DRM (Digital Rights Management) mechanisms.

Both a specific 32-bit ID as well as a 128-bit random ID is programmed into the EP9315 through the use of laser probing technology. These IDs can then be used to match secure copyrighted content with the ID of the target device that the EP9315 is powering, and then deliver the copyrighted information over a secure connection. In addition, secure transactions can benefit by matching device IDs to server IDs.

MaverickKey IDs can also be used by OEMs and design houses to protect against design piracy by presetting ranges for unique IDs. For more information on securing your design using MaverickKey, please contact your Cirrus Logic sales representative.

Integrated Three-port USB 2.0 Full Speed Host with Transceivers

The EP9315 integrates three USB 2.0 Full Speed host ports. Fully compliant to the OHCI USB 2.0 Full Speed specification (12 Mbps), the host ports can be used to provide connections to a number of external devices including mass storage devices, external portable devices such as audio players or cameras, printers or USB hubs. Naturally, the three-port USB host also supports the USB 2.0 Low Speed standard. This provides the opportunity to create a wide array of flexible system configurations.

Support for a Wide Array of Display Interfaces with a Flexible Raster Controller

The EP9315 processor provides timing and interface signals for digital LCD, TFT, and CRT displays. It is fully programmable for either non-interlaced or dual-scan color and grayscale flat panel displays, with up to 18 bits-per-pixel of color resolution.

System performance is enhanced with a separate dedicated data path to the SDRAM-based frame buffer, which supports resolutions up to 1024x768. A 16-bit PWM provides control for LCD panel contrast.

In addition, the EP9315 provides direct timing and interface signals for TV displays, with support for both NTSC and PAL formats through either RGB or YCrCb outputs.

Integrated Drive Electronics (IDE) Interface Reduces BOM Costs

With the EP9315's built-in IDE interface, the processor can connect directly with multiple hardware devices such as hard drives, CD drives and DVD drives. This saves designers money by minimizing their BOM costs, reduces their product size by shrinking board space and gets their products to market faster by saving design time. The IDE interface provides an industry standard connection to two AT Advanced Packet Interface (ATAPI) compliant devices. A single IDE port attaches to both master and slave devices. The interface supports three transfer modes corresponding to a range of transfer rates. These modes are Polled I/O, Multiword DMA and Ultra DMA.

High Quality Sound Delivered in Multiple Audio Configurations

The EP9315 delivers SPI, I2S and AC'97 serial interface support. The processor can be configured to provide up to six-channel I2S 24-bit audio. The AC'97 port supports multiple CODECs for cost-effective stereo audio output. Cirrus Logic provides high-performance audio decode and encode algorithms for a number of popular formats including MP3, Windows Media® Audio and AAC.

Integrated Ethernet MAC Reduces BOM Costs

The EP9315 integrates a 1/10/100 Mbps Ethernet Media Access Controller (MAC) on board. With a simple connection to an MII-based external PHY, an EP9315-based system has easy, high-performance, cost-effective Internet capability.

General-Purpose Memory Interface (SDRAM, SRAM, ROM, & FLASH)

The EP9315 features a unified memory address model in which all memory devices are accessed over a common address/data bus. A separate internal port is dedicated to the read-only Raster/Display refresh engine, while the rest of the memory accesses are performed via the high-speed processor bus. The SRAM memory controller supports 8, 16 and 32-bit devices and accommodates an internal boot ROM concurrently with a 32-bit SDRAM memory.

16-Bit Analog-to-Digital Converter (ADC) Provides an Integrated Touch-Screen Interface or General ADC Functionality

The EP9315 includes a 16-bit ADC, which can be utilized either as a touch-screen interface or for general ADC functionality. The touch-screen interface performs all sampling, averaging, ADC range checking and control for a wide variety of analog-resistive touch screens. To improve system performance, the controller only interrupts the processor when a meaningful change occurs. The touch-screen hardware may be disabled, and the switch matrix and ADC controlled directly for general ADC usage if desired.

8x8 Keypad Interface Reduces BOM Costs

The keypad circuitry scans an 8x8 array of 64 normally open, single pole switches. Any one or two keys depressed will be de-bounced and decoded. An interrupt is generated whenever a stable set of depressed keys is detected. If the keypad is not utilized, the 16 column/row pins may be used as general-purpose I/Os.

Multiple Booting Mechanisms Increase Flexibility

The processor includes a 16 KB boot ROM to set up standard configurations. Optionally, the processor may be booted from FLASH memory, over the SPI serial interface or through the UART. This boot flexibility makes it easy to design user-controlled, field-upgradable systems.

Abundant General Purpose I/Os Build Flexible Systems

The EP9315 includes both enhanced and standard general-purpose I/O pins (GPIOs). The 16 different enhanced GPIOs may individually be configured as inputs, outputs or interrupt-enabled inputs. There are an additional 49 standard GPIOs that may individually be used as inputs, outputs or open-drain pins. The standard GPIOs are multiplexed with peripheral function pins, so the number available depends on the utilization of peripherals. Together, the enhanced and standard GPIOs facilitate easy system design with external peripherals not integrated on the EP9315.

The Cirrus Logic ARM9™ Embedded Processor Family

EP9315

Premium-Featured Solutions

Connected, high-performance graphics system with mass storage

EP9312

EP9307

Full-Featured Solutions

Connected, high-performance graphics terminals

EP9302

EP9301

Entry-Level Solutions

Non-graphical terminals, standard connectivity



CORPORATE HEADQUARTERS

Cirrus Logic, Inc.
2901 Via Fortuna
Austin, TX 78746
USA
Tel +1-512-851-4000
Toll-Free +1-800-888-5016
Fax +1-512-851-4977

INTERNATIONAL OFFICES

ASIA PACIFIC

Cirrus Logic International Ltd.
RM 1112-1113
11F, Tower 6
The Gateway
9 Canton Road
Kowloon, Hong Kong
China
Tel +852-2376-0801
Fax +852-2412-5178

EUROPE

Cirrus Logic (U.K.) Ltd.
1st Floor Offices
Park House, Mere Park
Dedmere Road
Marlow, Buckinghamshire SL71FJ
United Kingdom
Tel +44-0-1628-891-300
Fax +44-0-1628-891-988

JAPAN

Cirrus Logic K.K.
Aioi Sonpo, Building 6F
5-6 Niban-cho
Chiyoda-ku
Tokyo, Japan 102-0084
Tel +81-3-5226-7757
Fax +81-3-5226-7677

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cirrus Logic:](#)

[EP9315-CBZ](#) [EP9315-IBZ](#)