

January 7, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

AXIAL LEADED HERMETICALLY SEALED SUPERFAST RECTIFIER DIODE

- Very low reverse recovery time
- Hermetically sealed in Metoxilite fused metal oxide
- Low switching losses
- Low forward voltage drop
- Soft, non-snap off, recovery characteristics


QUICK REFERENCE DATA

- $V_R = 50 - 150V$
- $I_F = 1.8A$
- $t_{rr} = 30ns$
- $V_F = 1.2V$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Working reverse voltage	V_{RWM}	50	100	150	V
Repetitive reverse voltage	V_{RRM}	50	100	150	V
Average forward current (@ 55°C, lead length = 0.375")	$I_{F(AV)}$	← 1.8 →			A
Repetitive surge current (@ 55°C, lead length = 0.375")	I_{FRM}	← 14.0 →			A
Non-repetitive surge current ($t_p = 8.3ms$, @ V_R & T_{jmax})	I_{FSM}	← 35.0 →			A
Storage temperature range	T_{STG}	← -65 to +150 →			°C
Operating temperature range	T_{OP}	← -65 to +150 →			°C

MECHANICAL



These products are qualified to MIL-S-19500/503.

They can be supplied fully released as JAN, JANTX, and JANTXV versions.

These products are qualified in Europe to DEF STAN 59-61 (PART 80)/029 available to F and FX levels.

January 7, 1998

ELECTRICAL CHARACTERISTICS (@ 25°C unless otherwise specified)

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Average forward current max. (pcb mounted; $T_A = 55^\circ\text{C}$) for sine wave	$I_{F(AV)}$	← 0.85 →			A
for square wave ($d = 0.5$)	$I_{F(AV)}$	← 0.90 →			A
Average forward current max. $T_L = 70^\circ\text{C}$; $L = 0"$ $T_L = 55^\circ\text{C}$; $L = 3/8"$ for sine wave	$I_{F(AV)}$	← 3.0 →			A
for square wave	$I_{F(AV)}$	← 1.7 →			A
	$I_{F(AV)}$	← 1.8 →			A
I^2t for fusing ($t = 8.3\text{ms}$) max.	I^2t	← 5.0 →			A ² S
Forward voltage drop max. @ $I_F = 1.5\text{A}$, $T_j = 25^\circ\text{C}$	V_F	← 1.2 →			V
Reverse current max. @ V_{RWM} , $T_j = 25^\circ\text{C}$	I_R	← 1.0 →			μA
@ V_{RWM} , $T_j = 100^\circ\text{C}$	I_R	← 50 →			μA
Reverse recovery time 0.5A I_F , 1.0A I_R , 0.25A I_{RR} .	t_{rr}	← 30 →			nS
Junction capacitance typ. @ $V_R = 5\text{V}$, $f = 1\text{MHz}$	C_j	← 28 →			pF

THERMAL CHARACTERISTICS

	Symbol	1N6073 FF05	1N6074 FF10	1N6075 FF15	Unit
Thermal resistance - junction to lead Lead length = 0.375"	$R_{\theta JL}$	← 46 →			°C/W
Lead length = 0.0"	$R_{\theta JL}$	← 13 →			°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	$R_{\theta JA}$	← 95 →			°C/W

January 7, 1998




Fig 1. Forward voltage drop as a function of forward current.




Fig 2. Maximum power versus lead temperature.




Fig 3. Transient thermal impedance characteristic.








Fig 4. Typical junction capacitance as a function of reverse voltage.

January 7, 1998



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Semtech:](#)

[JAN1N6075](#) [JANTX1N6074](#) [JAN1N6074](#) [JANTX1N6075](#) [JAN1N6073](#) [JANTX1N6073](#) [JANTXV1N6074](#)
[JANTXV1N6073](#) [JANTXV1N6075](#)