



Revision Number: 007.0

Issue date: 08/04/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE X33-04 known as X33-04
LOW SOLID FLUX 5GA BX

Product type/use: Cleaner

Restriction of Use: None identified

Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 479668

Item number: M00347

Region: United States

Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

This product contains one or more components regulated under a Significant New Use Rule (SNUR) by the US EPA. See Section 15 for more information.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 479668

Product name: LOCTITE X33-04 known as X33-04 LOW SOLID FLUX 5GA BX
 Page 1 of 6

Hazardous Component(s)	CAS Number	Percentage*
2-Propanol	67-63-0	80 - 100
Bis(2-butoxyethyl)ether	112-73-2	5 - 10
Hydroxy-2-methylpentan-4-on-2	123-42-2	5 - 10
adipic acid	124-04-9	1 - 5
Ethanol	64-17-5	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Thermal decomposition can lead to release of irritating gases and vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Evacuate personnel to safe areas. Ventilate area. Remove all sources of ignition. Wear suitable protective clothing, gloves and eye/face protection. Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Keep away from heat, spark and flame. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full.

Storage: Store away from ignition sources. Keep away from heat, spark and flame. Store in original container until ready to use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Bis(2-butoxyethyl)ether	None	None	None	None
Hydroxy-2-methylpentan-4-on-2	50 ppm TWA	50 ppm (240 mg/m3) PEL	None	None
adipic acid	5 mg/m3 TWA	None	None	None
Ethanol	1,000 ppm STEL	1,000 ppm (1,900 mg/m3) PEL	None	None

Engineering controls: Ensure adequate ventilation, especially in confined areas. Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Colorless
Odor:	Alcoholic
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	44 mm hg (25 °C (77°F))
Boiling point/range:	82 °C (179.6 °F)
Melting point/ range:	Not determined
Specific gravity:	0.805
Vapor density:	Heavier than air.
Flash point:	12 °C (53.6 °F)
Flammable/Explosive limits - lower:	2 %
Flammable/Explosive limits - upper:	12.7 %
Autoignition temperature:	399 °C (750.2 °F)
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Miscible
Partition coefficient (n-octanol/water):	Not available.
VOC content:	100 %; 790 g/l
Viscosity:	1.0 mPa.s
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use. Electrostatic charge may build-up during handling. Grounding of equipment is recommended.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Thermal decomposition can lead to release of irritating gases and vapors.
Incompatible materials:	Oxidizing agents. Acids.
Reactivity:	Not available.
Conditions to avoid:	Keep away from open flames, hot surfaces and sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of processing fumes may be harmful. Vapor overexposure may cause drowsiness. Dizziness.
Skin contact:	May cause skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Bis(2-butoxyethyl)ether	None	Irritant, Reproductive
Hydroxy-2-methylpentan-4-on-2	Oral LD50 (Rat) = 4.0 g/kg	Blood, Central nervous system, Irritant, Kidney, Liver
adipic acid	Oral LD50 (Mouse) = 1,900 mg/kg Oral LD50 (Rabbit) = > 11,000 mg/kg Oral LD50 (Rat) = > 11,000 mg/kg	Irritant, Kidney, Liver, Nervous System, Respiratory
Ethanol	Oral LD50 (Rat) = 9.9 g/kg Oral LD50 (Rat) = 6.2 g/kg Oral LD50 (Rat) = 17.8 g/kg Oral LD50 (Rat) = 11.5 g/kg Oral LD50 (Mouse) = 3,450 mg/kg Oral LD50 (Rat) = 10.6 g/kg Oral LD50 (Rat) = 7,060 mg/kg Inhalation LC50 (Rat, 4 h) = 133.8 mg/l Inhalation LC50 (Rat, 4 h) = 124.7 mg/l Inhalation LC50 (Rat, 4 h) = > 115.9 mg/l Inhalation LC50 (Rat, 4 h) = 130.7 mg/l Inhalation LC50 (Rat, 4 h) = 128.2 mg/l Inhalation LC50 (Rat, 4 h) = 116.9 mg/l Inhalation LC50 (Mouse, 4 h) = 39 mg/l	Central nervous system, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2-Propanol	No	No	No
Bis(2-butoxyethyl)ether	No	No	No
Hydroxy-2-methylpentan-4-on-2	No	No	No
adipic acid	No	No	No
Ethanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Isopropanol solution
Hazard class or division: 3
Identification number: UN 1219
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Isopropanol solution
Hazard class or division: 3
Identification number: UN 1219
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ISOPROPANOL solution
Hazard class or division: 3
Identification number: UN 1219
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 5(a) SNUR: This product contains the following component(s) subject to a Significant New Use Rule (SNUR) by the US EPA:
Bis(2-butoxyethyl)ether (CAS # 112-73-2). The SNUR is codified at Section number: 40 CFR 721.10229

TSCA 12 (b) Export Notification: Bis(2-butoxyethyl)ether (CAS# 112-73-2).

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Bis(2-butoxyethyl)ether (CAS# 112-73-2).

CERCLA Reportable quantity: 2-Propanol (CAS# 67-63-0) 100 lbs. (45.4 kg)
Ethanol (CAS# 64-17-5) 100 lbs. (45.4 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 1,2,3,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/04/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Loctite:](#)

[479668](#)