## Safety Data Sheet



Revision Number: 005.0 Issue date: 09/16/2020

## 1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE ECCOBOND FP4549G known IDH number: **Product name:** 

as FP4549G 6OZ HIGH PEFOR. UF

FP0100-A33A1 Product type/use: Encapsulant Item number: Restriction of Use: United States None identified Region:

Company address: **Contact information:** Henkel Corporation

Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center One Henkel Way Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

555611

Internet: www.henkelna.com

This product contains an epoxy resin CAS # 27610-48-6 that is covered by a USEPA Significant New Use Requirement (SNUR) (40CFR 721.5192) that limits its use to binding fibers in aerospace composites or for encapsulating electronic devices. It is a violation of the SNUR to use this product for any other application.

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE DAMAGE.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

SUSPECTED OF CAUSING GENETIC DEFECTS.

SUSPECTED OF CAUSING CANCER.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

| HAZARD CLASS              | HAZARD CATEGORY |
|---------------------------|-----------------|
| SKIN IRRITATION           | 2               |
| SERIOUS EYE DAMAGE        | 1               |
| RESPIRATORY SENSITIZATION | 1               |
| SKIN SENSITIZATION        | 1               |
| GERM CELL MUTAGENICITY    | 2               |
| CARCINOGENICITY           | 2               |
| REPRODUCTIVE TOXICITY     | 2               |

#### PICTOGRAM(S)



#### **Precautionary Statements**

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear

respiratory protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to Response:

fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get

medical attention. Take off contaminated clothing.

Storage: Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local Disposal:

governmental regulations.

IDH number: 555611 Product name: LOCTITE ECCOBOND FP4549G known as FP4549G 6OZ HIGH PEFOR. UF

Page 1 of 6

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                   | CAS Number  | Percentage* |
|--|-------------|-------------|
| Aluminium oxide - non fibrous form       | 1344-28-1   | 30 - 60     |
| hexahydromethylphthalic anhydride        | 25550-51-0  | 10 - 30     |
| 6-glycidyloxynapht-1-yl oxymethyloxirane | 27610-48-6  | 10 - 30     |
| Epoxy resin                              | Proprietary | 10 - 30     |
| Epoxy resin                              | Proprietary | 1-5         |
| Carbon black                             | 1333-86-4   | 0.1 - 1     |

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

**Skin contact:** Immediately flush skin w ith plenty of w ater (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention. Wash clothing

before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Hydrocarbons. Toxic

and irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Releases of this product may not be made into U.S. waters without primary

and secondary wastewater treatment.

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Isolate area.

Keep unnecessary personnel away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Store in a closed container until ready for disposal. Refer to Section 8 "Exposure Controls /

Personal Protection" prior to clean up.

IDH number: 555611 Product name: LOCTITE ECCOBOND FP4549G known as FP4549G 6OZ HIGH PEFOR. UF

Page 2 of 6

## 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do

not taste or sw allow. Keep container closed. Refer to Section 8.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                   | ACGIH TLV                           | OSHA PEL   | AIHA WEEL | OTHER       |
|--|-------------------------------------|--|-----------|-------------|
| Aluminium oxide - non fibrous form       | 1 mg/m3 TWA<br>Respirable fraction. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None      | None        |
| hexahydromethylphthalic anhydride        | None                                | None   | None      | None        |
| 6-glycidyloxynapht-1-yl oxymethyloxirane | None                                | None   | None      | 0.1 ppm TWA |
| Epoxy resin                              | None                                | None   | None      | None        |
| Epoxy resin                              | None                                | None   | None      | None        |
| Carbon black                             | 3 mg/m3 TWA Inhalable fraction.     | 3.5 mg/m3 PEL  | None      | None        |

Engineering controls: Provide adequate local exhaust ventilation to maintain w orker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

show ers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. 4H gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:GrayOdor:Mild

Odor threshold:Not available.pH:Not applicableVapor pressure:Not available.Boiling point/range:Not available.Melting point/ range:Not available.Specific gravity:1.8Vapor density:Not available.

> 130 °C (> 266°F) Flash point: Flammable/Explosive limits - lower: Not available. Flam mable/Explosive limits - upper: Not available. Not available. Autoignition temperature: Flam mability: Not applicable Evaporation rate: Not available. Insoluble Solubility in water: Partition coefficient (n-octanol/water): Not available.

 Partition coefficient (n-octanol/water):
 Not available.

 VOC content:
 Not available.

 Viscosity:
 Not available.

IDH number: 555611 Product name: LOCTITE ECCOBOND FP4549G known as FP4549G 6OZ HIGH PEFOR. UF

Page 3 of 6

**Decomposition temperature:** Not available.

#### 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Hydrocarbons. Irritating vapors.

Incompatible materials: Oxidizing agents. Acids and bases. Peroxides. Amines. Mercaptans. Alcohols. Water.

Reactivity: Not available.

Conditions to avoid: Exposure to moisture. High temperatures. Heat, flames, sparks and other sources of ignition.

Store aw ay from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Product toxicity data: The U.S. Environmental Protection Agency (EPA) has identified certain substances that are

structurally similar to the epoxy resin component with CAS# 27610-48-6. These analogues are phenylglycidylether and diglycidylether of resorcinol. Based on the results of animal bioassays on these analogues, the EPA finds that the epoxy resin component (CAS# 27610-48-6) may be carcinogenic and may cause reproductive effects. The epoxy resin is expected to be

absorbed via all routes.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. May cause allergic respiratory reaction. Coughing.

Wheezing. Shortness of breath.

Skin contact: Causes skin irritation. May cause allergic skin reaction. Repeated or prolonged exposure may

cause skin burns.

Eye contact: Causes serious eye damage. Prolonged contact may cause eye burns and corneal injury.

**Ingestion:** May cause irritation to the gastrointestinal tract, mouth and mucous membranes.

| Hazardous Component(s)                  | LD50s and LC50s                 | Immediate and Delayed Health Effects          |
|---|---------------------------------|---|
| Aluminium oxide - non fibrous form      | None                            | Irritant, Nuisance dust, Corrosive            |
| hexahydromethylphthalic anhydride       | None                            | Allergen, Respiratory, Irritant               |
| 6-glycidyloxynapht-1-yloxymethyloxirane | None                            | Irritant, Allergen, Blood, Reproductive       |
| Epoxy resin                             | None                            | Allergen, Irritant                            |
| Epoxy resin                             | None                            | No Target Organs                              |
| Carbon black                            | Oral LD50 (Rat) = > 8,000 mg/kg | Respiratory, Some evidence of carcinogenicity |

| Hazardous Component(s)                   | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Aluminium oxide - non fibrous form       | No             | No              | No                                       |
| hexahydromethylphthalic anhydride        | No             | No              | No                                       |
| 6-glycidyloxynapht-1-yl oxymethyloxirane | No             | No              | No                                       |
| Epoxy resin                              | No             | No              | No                                       |
| Epoxy resin                              | No             | No              | No                                       |
| Carbon black                             | No             | Group 2B        | No                                       |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 555611

## 13. DISPOSAL CONSIDERATIONS

#### Information provided is for unused product only.

Recommended method of disposal: Any process stream associated with the use of this product must be disposed

of by incineration or in a landfill. This provision, how ever, does not supersede

any applicable federal, state or local laws and regulations.

**Hazardous waste number:**Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Exceptions: Up to 6 oz. max per inner/primary package when shipped as originally packaged

only

Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

**Exceptions:** Up to 6 oz. max per inner/primary package when shipped as originally packaged

only

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 5 (a) (2) SNUR:

This product contains an ingredient for w hich a Significant New Use Rule (SNUR) has been promulgated by the USEPA under the Toxic Substances Control Act (TSCA) section

5(a)(2). This SNUR (40CFR 721.5192) limits its use to binding fibers in aerospace composites or for encapsulating electronic devices. It is in violation of the SNUR to use this product for any other application. Manufacture, import, distribution, use and disposition of this product is restricted to the requirements listed in 40 CFR.

TSCA 12 (b) Export Notification: Substituted 1,6-dihydroxy naphthalene (CAS# 27610-48-6).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

IDH number: 555611 Product name: LOCTITE ECCOBOND FP4549G known as FP4549G 6OZ HIGH PEFOR. UF

Page 5 of 6

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,11,16

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 09/16/2020

IDH number: 555611

**DISCLAIM ER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirmthat the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Loctite: 555611