



Revision Number: 004.0

Issue date: 05/09/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LOCTITE CAT 50 AMB known as CATALYST 50 AMB 15 GR</b>	<b>IDH number:</b>	1188193
<b>Product type:</b>	Catalyst	<b>Region:</b>	United States
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	
<b>Company address:</b>	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com		
Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067			

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** FLAMMABLE LIQUID AND VAPOR.  
TOXIC IF SWALLOWED.  
CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
ACUTE TOXICITY ORAL	3
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
<b>Storage:</b>	Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Butoxydibutylchlorostannane	14254-22-9	80 - 90
2-Butoxyethanol	111-76-2	5 - 10
Hydrochloric acid	7647-01-0	1 - 5
n-Butyl alcohol	71-36-3	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide. Do not use water.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
<b>Hazardous combustion products:</b>	Oxides of carbon, oxides of nitrogen, irritating organic vapors. Hazardous decomposition products include chlorine compounds. Hydrocarbons. Oxides of tin.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Butoxydibutylchlorostannane	0.1 mg/m <sup>3</sup> TWA (as Sn) 0.2 mg/m <sup>3</sup> STEL (as Sn) (SKIN) (as Sn)	0.1 mg/m <sup>3</sup> PEL (as Sn)	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m <sup>3</sup> ) PEL (SKIN)	None	None
Hydrochloric acid	2 ppm Ceiling	5 ppm (7 mg/m <sup>3</sup> ) Ceiling	None	None
n-Butyl alcohol	20 ppm TWA	100 ppm (300 mg/m <sup>3</sup> ) PEL	None	None

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Yellow
<b>Odor:</b>	Pungent
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	< 10 mm hg
<b>Boiling point/range:</b>	121 °C (249.8 °F)
<b>Melting point/ range:</b>	Not applicable
<b>Specific gravity:</b>	1.25
<b>Vapor density:</b>	> 1.0 (Air = 1)
<b>Flash point:</b>	42 °C (107.6 °F) Pensky Martens closed cup
<b>Flammable/Explosive limits - lower:</b>	1.4 %
<b>Flammable/Explosive limits - upper:</b>	11.2 %
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not determined
<b>VOC content:</b>	110 g/l

Viscosity:  
Decomposition temperature:

Not available.  
Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours. Hazardous decomposition products include chlorine compounds. Hydrocarbons. Oxides of tin.
<b>Incompatible materials:</b>	Strong acids and strong bases. Oxidizing agents. Water Incompatible with ferrous metals. Reactive metals.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Avoid moisture. High temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	May cause respiratory tract irritation. Breathing high concentrations of vapor may cause anesthetic effects. May cause central nervous system effects with nausea, dizziness and headache.
<b>Skin contact:</b>	Causes skin irritation. Prolonged or repeated contact with this product may dry and/or defat the skin.
<b>Eye contact:</b>	Causes serious eye damage.
<b>Ingestion:</b>	Toxic if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Butoxydibutylchlorostannane	None	No Records
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat, 4 h) = 486 ppm Inhalation LC50 (Rat, 4 h) = 450 ppm	Blood, Central nervous system, Irritant, Kidney, Liver
Hydrochloric acid	Oral LD50 (Rabbit) = 900 mg/kg Dermal LD50 (Mouse) = 1,449 mg/kg	Irritant, Corrosive, Kidney
n-Butyl alcohol	Oral LD50 (Rat) = 790 mg/kg Dermal LD50 (Rabbit) = 3,400 mg/kg Inhalation LC50 (Rat, 4 h) = 8000 ppm	Allergen, Central nervous system, Ear, Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Butoxydibutylchlorostannane	No	No	No
2-Butoxyethanol	No	No	No
Hydrochloric acid	No	No	No
n-Butyl alcohol	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Flammable liquids, corrosive, n.o.s. (Butoxydibutylchlorostannane, 1-Butanol)  
Hazard class or division: 3 (8)  
Identification number: UN 2924  
Packing group: III

### International Air Transportation (ICAO/IATA)

Proper shipping name: Flammable liquid, corrosive, n.o.s. (Butoxydibutylchlorostannane, 1-Butanol)  
Hazard class or division: 3 (8)  
Identification number: UN 2924  
Packing group: III

### Water Transportation (IMO/IMDG)

Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Butoxydibutylchlorostannane, 1-Butanol)  
Hazard class or division: 3 (8)  
Identification number: UN 2924  
Packing group: III

## 15. REGULATORY INFORMATION

### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
TSCA 12 (b) Export Notification: None above reporting de minimis  
CERCLA/SARA Section 302 EHS: Hydrochloric acid (CAS# 7647-01-0).  
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire  
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Butoxyethanol (CAS# 111-76-2). Hydrochloric acid (CAS# 7647-01-0). n-Butyl alcohol (CAS# 71-36-3).  
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Tricia Voghell, Regulatory Affairs Specialist

**Issue date:** 05/09/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Loctite:](#)

[1188193](#)