



Revision Number: 003.0

Issue date: 10/13/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: HHD8540 PART A BULK
Product type/use: Acrylate adhesive
Restriction of Use: None identified
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 1913950
Region: United States
Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: EXTREMELY FLAMMABLE LIQUID AND VAPOUR.
 CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE DAMAGE.
 MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	1
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methyl methacrylate	80-62-6	30 - 60
Methacrylate ester	Proprietary	10 - 30
methacrylic acid	79-41-4	5 - 10
Silica, amorphous, fumed, cryst.-free	112945-52-5	1 - 5
Methacrylate ester	Proprietary	0.1 - 1
Triphenylphosphine	603-35-0	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Keep container closed.

Storage:

For safe storage, store between 2 °C (35.6 °F) and 8 °C (46.4 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight. Maintain head space in storage containers to support oxygen requirements of the inhibitor(s).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl methacrylate	50 ppm TWA 100 ppm STEL (Dermal sensitization)	100 ppm (410 mg/m3) PEL	None	50 ppm
Methacrylate ester	None	None	None	None
methacrylic acid	20 ppm TWA	None	None	None
Silica, amorphous, fumed, cryst.-free	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Methacrylate ester	None	None	None	None
Triphenylphosphine	None	None	None	None

Engineering controls:

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Acrylate
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	>= 35 °C (>= 95°F)
Melting point/ range:	Not available.
Specific gravity:	0.98
Vapor density:	Not available.
Flash point:	< 23 °C (< 73.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.

VOC content: Not available.
Viscosity: 30,000 mPa.s
Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Polymerization may occur at elevated temperatures or upon depletion of inhibitor.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Toxic fumes. Irritating vapors.

Incompatible materials: Bases. Acids. Reducing agents. Oxidizing agents. Peroxides.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Loss of polymerization inhibitor. Loss of dissolved air. Do not mix in batches greater than 100 grams (0.22 pounds) unless you plan to use immediately.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Not available.

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Drowsiness. Dizziness.
Skin contact: Causes skin irritation. May cause an allergic skin reaction.
Eye contact: Causes serious eye damage.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methyl methacrylate	Oral LD50 (Rat) = 7,800 mg/kg Oral LD50 (Rabbit) = 6,000 mg/kg Oral LD50 (Rat) = 9,400 mg/kg	Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory
Methacrylate ester	None	Irritant, Allergen
methacrylic acid	Oral LD50 (Mouse) = 1,332 mg/kg Oral LD50 (Mouse) = 1,600 mg/kg Oral LD50 (Mouse) = 1,250 mg/kg Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Rat) = 1,060 mg/kg Oral LD50 (Rat) = 2,224 mg/kg Dermal LD50 (Rabbit) = 500 mg/kg	Corrosive, Irritant, Allergen
Silica, amorphous, fumed, cryst.-free	None	No Data
Methacrylate ester	None	Irritant, Allergen
Triphenylphosphine	Inhalation LC50 (Rat, 4 h) = 12.5 mg/l	Irritant, Nervous System, Mutagen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl methacrylate	No	No	No
Methacrylate ester	No	No	No
methacrylic acid	No	No	No
Silica, amorphous, fumed, cryst.-free	No	No	No
Methacrylate ester	No	No	No
Triphenylphosphine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II
DOT Hazardous Substance(s): Methyl methacrylate

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Fire, Immediate Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methyl methacrylate (CAS# 80-62-6).

CERCLA Reportable quantity: Methyl methacrylate (CAS# 80-62-6) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,9,13,15

Prepared by: Rena Petrides, Regulatory Affairs Specialist

Issue date: 10/13/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Loctite:](#)

[1914249](#)