

Revision Number: 002.0 Issue date: 10/26/2016

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:Loctite HHD 3890 s CR260G ECJIDH number:1991723Product type:Hotmelt adhesiveItem number:45850Restriction of Use:None identifiedRegion:United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (tollfree) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (tollfree) or 1-703-527-3887

Internet: w ww.henkelna.com

Contact information:

## 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND

RESPIRATORY TRACT IRRITATION.

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR

FLAMMABLE VAPORS MAY CAUSE IGNITION.

	HAZARD CLASS	HAZARD CATEGORY
None		None

Γ	PICTOGRAM(S)
	None

#### **Precautionary Statements**

Prevention:Not prescribedResponse:Not prescribedStorage:Not prescribedDisposal:Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Polypropylene glycol	25322-69-4	1-5
Carbon black	1333-86-4	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Cool skin rapidly with cold water after contact with molten material. Cover

affected areas with clean sheeting or gauze and seek immediate medical

attention.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not

remove adhesive. Seek medical attention.

**Ingestion:** Do not induce vomiting. Seek medical advice.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: w ater, carbon dioxide, foam, pow der

Special firefighting procedures: Not available.

Unusual fire or explosion hazards: Not available.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Sw eep up spilled material. Avoid creating dust. Keep in suitable and closed

containers for disposal.

## 7. HANDLING AND STORAGE

**Handling:** Do not place wet or damp solid into melt tank. Follow suggested application

temperature. Alw ays be careful around molten material. Avoid skin contact with molten resins. Do not wear contact lenses. Avoid dust formation.

Storage: Keep cool in accordance with information on label and in Technical Data

Sheets.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polypropylene glycol	None	None	10 mg/m3 TWA Aerosol.	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None

Engineering controls: Use adequate ventilation to remove molten vapors or fumes.

Respiratory protection: Solid Resin: Dust safety masks are recommended when the potential for dust

inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator

with an organic vapor cartridge.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Do not wear

contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when

w orking with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Black Slightly Odor: Odor threshold: Not available. Not applicable pH: Vapor pressure: Not available. Boiling point/range: Not available. Melting point/range: Not available. Specific gravity: 1.10 - 1.20 Vapor density: Not available. Flash point: Not applicable Flam mable/Explosive limits - low er: Not available. Flam mable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flam mability: Not applicable Evaporation rate: Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. 0.00 % **VOC** content: Viscosity: Not available. Decomposition temperature: Not available.

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

Incompatible materials: Acids. Bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Excessive heat.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Molten adhesive., Skin, Eyes

#### Potential Health Effects/Symptoms

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts

from solid adhesive may cause irritation.

**Skin contact:** Molten adhesive may cause severe burns. Solid adhesive has no hazards.

Eye contact: Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical

irritation if dusts are generated.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Polypropylene glycol	None	Allergen, Cardiac, Central nervous system, Irritant
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polypropylene glycol	No	No	No
Carbon black	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

IDH number: 1991723 Product name: Loctite HHD 3890 s CR260G ECJ

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 10/26/2016

**DISCLAIM ER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1991723 Product name: Loctite HHD 3890 s CR260G ECJ

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Loctite: 1991723