### **Data Sheet**

# Control Cable AISG 0.5m 86010054

#### Description

Installation Equipment for Special Communication Antennas: Connecting Cable For Remote Electrical Tilt (RET) System



#### **Technical Data**

#### Mechanical Data


The male and female connectors are compatible components which are designed to operate under the environmental conditions as described in ETS 300 019-1-4 class 4.1 E.

#### **Environmental Data**

For indoor and outdoor use Related Documents Security instruction

DOC-0000278984

Description	RET Cable
Connectors	ACS C091 over molded f/m connector IEC 601309
Mating torque	0.5 – 1 Nm (The connector should be tightened by hand )
Operating temperature	-40 °C to +80 °C, (fixed position)
Protection class	IP 67 (connected)
Signal	2xAWG24 (twisted pair 100 Ω/1 MHz)
Power	3x AWG18 (4A)
Color	Black
Diameter	7.2mm
Flamability	UL 1581-1061, UL 1685 CM, IEC603221-3-24
Bending Radius	45mm



PIN	Assignment according AISG
1	+13 V DC (+12 V DC nominal)
2	not connected
3	RS485 B
4	not connected
5	RS485 A
6	+29 V DC (+24 V DC nominal)
7	DC Return
8	not connected

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

## **HUBER+SUHNER**

### **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: <u>86010054</u>