Data Sheet



Sencity Rail Antenna 87010009

Description

Railway rooftop multi-band antenna for 430-470 MHz and 870-960 MHz.

The antenna can be operated in all frequency ranges simultaneously.

Multiple Antenna installations support Cellular MIMO.

Rugged design, meets EN 50155 railway standard.

Fire retardant acc. to EN 45545-2. Works also on non-metallic surfaces.



Product Configuration

Technical Data

Electrical Data

	Band 1	Band 2
Frequency (MHz)	430 - 470	870 - 960
VSWR	1.5	1.5
Impedance (Ohm)	50	50
Gain (dBi)	3.5	4.5
Ambient temperature (°C)	25	25

Ports

	Port 1
Port name	Tetra/Cell
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

Connections

	Band 1	Band 2
Port 1	X	X

General Data

Indicated VSWR values are valid for a metallic ground plane of 1M x 2M or larger.

Mechanical Data

Dimensions (mm) 150 x 145 x 85 (Heigth x Width x Depth) Weight (kg) 0.5

Radiator: Copper and brass.

Flange: Aluminum. Radome: Fiberglass.

All screws and nuts: Stainless steel.

Colour: Grey.

Sealing: Neoprene and silicon.

This antenna, tested by an independent institute, is DC grounded to protect against lightning and short circuit with high voltage lines.

Packaging size (outside): 150 x 90 x 190 mm

Data Sheet



Sencity Rail Antenna 87010009

Environmental Data

Environmental conditions outdoor
Operation temperature (°C) -40 to 85
Storage temperature (°C) -40 to 85
IP rating IP66
Flammability rating EN 45545-2
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Lead-free soldered y

WEEE 2012/19/EU no special marking needed

REACH 1907/2006/EC compliant

Environmental tests: EN 50155:2018-05 Flammability rating: EN 45545-2.

Material Data

Radome colour grey
Back plate/base plate colour black
Back plate/base plate material Aluminium

Related Products

2501.17.0091 Diplexer 80 - 520 / 694 - 2700 MHz can be used to operate both frequencies simultaneously.

Related Documents

 Mounting instruction
 DOC-0000864326

 Painting instruction
 DOC-0000256180

 Security instruction
 DOC-0000278984

 Outline drawing
 DOU-00389218

 3D-model
 DOC-0000864321

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 87010009