# **Data Sheet**



## **Sencity Rail Antenna** K702061

## **Description**

Railway rooftop multi-band antenna for 450-470 MHz and 790-960 MHz.

The antenna can be operated in all frequency ranges simultaneously.

Multiple Antenna installations support Cellular MIMO.

Rugged design, meets EN 50155 railway standard.

Fire retardant acc. to EN 45545-2. Works also on non-metallic surfaces.



## **Product Configuration**

#### **Technical Data**

#### **Electrical Data**

	Band 1	Band 2
Frequency (MHz)	450 - 470	790 - 960
VSWR	1.4	1.5
Impedance (Ohm)	50	50
Gain (dBi)	4	3.5
Ambient temperature (°C)	25	25

## **Ports**

	Port 1
Port name	Tetra/Cell
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

## Connections

	Band 1	Band 2
Port 1	X	X

## **General Data**

Indicated VSWR values are valid for a metallic ground plane of 0.5M x 0.5M or larger

#### **Mechanical Data**

Dimensions (mm) 142 x 145 x 80 (Heigth x Width x Depth) Weight (kg)

Radiator and Flange: Aluminum. Radome: Fiberglass, colour: Light grey. All screws and nuts: Stainless steel. Sealing: Neoprene and rubber.

This antenna, tested by an independent institute, is DC grounded to protect against lightning and short circuit from high voltage lines.

Packaging size (outside): 151 x 87 x 210 mm

#### **Environmental Data**

**Environmental conditions** outdoor Operation temperature (°C) -40 to 85

# **Data Sheet**



## Sencity Rail Antenna K702061

Storage temperature (°C) -40 to 85
IP rating IP66
Flammability rating EN 45545-2
2011/65/EU (RoHS - including compliant
2015/863 and 2017/2102)

Lead-free soldered ye

WEEE 2012/19/EU no special marking needed

REACH 1907/2006/EC compliant

Environmental tests: EN 50155:2018-05

Flammability rating: DIN 5510-2, UL94 HB, EN45545

#### **Material Data**

Radome colour grey
Back plate/base plate colour black
Back plate/base plate material Aluminium

#### **Related Products**

2501.17.0091 Diplexer 80 - 520 / 694 - 2700 MHz can be used to operate both frequencies simultaneously.

#### **Related Documents**

 Mounting instruction
 DOC-0000862954

 Painting instruction
 DOC-0000256180

 Security instruction
 DOC-0000278984

 Outline drawing
 DOU-00394144

 3D-model
 DOC-0000864676

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS.

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: K702061