HUBER+SUHNER® DATA SHEET RF ATTENUATOR: Type 5920_N-50-200/19-_N

Rev.: D

Description

Standard Attenuator, High Power

Product Configuration

Connectors (side 1 / side 2)

Interface standard

N plug (male) / N jack (female)

IEC 60169-16 MIL-STD-348A/304 CECC 22210

Technical Data

Electrical Data

Nominal impedance 50Ω Nominal attenuation 20 dB DC to 4 GHz Frequency range

Frequency sub range (GHz) DC to 1.5 1.5 to 2.5 2.5 to 4 Attenuation deviation (±dB) 0.75 1.5 1 VSWR max. 1.15 1.25 1.35

200 Watt average power up to 25 °C ambient temperature, linearly derated to 40 Watt at Power rating

125 °C ambient temperature.

Free airflow convection necessary to ensure power performances. Unit is unidirectional, therefore don't swap input with output (note: input is usually on the male side, otherwise

follow instructions on the heatsink)

2000 Watt peak power, 5 µs pulse, 0.05 % duty cycle

Mechanical Data

Weight kg

Environmental Data

Operating temperature (°C) -54 to 125 2002/95/EC (RoHS) compliant

Material Data

Piece Part (side 1) Material

Centre contact Copper Beryllium Alloy

Outer contact Stainless Steel Body Aluminium Coupling nut Stainless Steel

Piece Part (side 2) Material

Centre contact Copper Beryllium Alloy

Stainless Steel Outer contact Body Aluminium

Related Documents

Outline drawing DOU-00122366

Ordering Information

Single packaging 5920_N-50-200/19-_NE **Surface Plating**

Gold Plating (without Nickel underplating)

Passivated (Plating)

Anodized

Passivated (Plating)

Surface Plating

Gold Plating (without Nickel underplating)

Passivated (Plating)

Anodized

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVERI

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only

HUBER+SUHNER – Excellence in Connectivity Solutions

RF Industrial 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11

HUBER+SUHNER AG

HUBER+SUHNER

+41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000279943 H Issued: 28.11.2011 16:39:22 Uncontrolled Copy Page 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 5920_N-50-200/19-_NE