



Industrial



SL POWER PW180KB SERIES

15.4 Watts Single Output
Industrial Grade

Advanced Energy's SL Power PW180KB AC-DC power supplies are available with a nominal main output 48 V, which have self contained midspan power injector and support power over ethernet up to 15.4 Watts. PW180KB series has 90 VAC to 265 VAC input voltage range and regulated output with low ripple, which is IEEE802.3af compliant.

AT A GLANCE

Total Power

15.4 Watts

Input Voltage

90 to 265 VAC

of Outputs

Single

SPECIAL FEATURES

- Power over Ethernet (PoE)
- Self Contained Midspan Power Injector
- 90 to 265 VAC Input Range
- Desktop Style
- Single Output up to 15.4 Watts
- Regulated Output with Low Ripple
- Complies with EMI/RFI Regulations
- IEEE802.3af Compliant
- CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking and Custom Designs Available
- 3 Years Warranty

SAFETY

- UL/EN/IEC/CSA62368-1



ELECTRICAL SPECIFICATIONS

Input	
Input Range	90 to 265 VAC, 47 to 63 Hz, 1Ø
Input Current	0.5A max at 90 VAC
Protection	Internal primary current fuse, inrush limiting
Inrush Current	450 mA max
Leakage Current	Less than 0.75 mA at 265 VAC 50 Hz
Output	
Output Voltage	48 VDC typical, 44 VDC to 57 VDC
Ripple and Noise	f < 500 Hz 500 Hz to 150 kHz 150 kHz to 500 kHz 500 kHz to 1 MHz 500 mVpk-pk 200 mVpk-pk 150 mVpk-pk 100 mVpk-pk
Load Regulation	±4% (Maximum deviation from nominal voltage for all loading conditions)
Transient Response	500 µs response time for return to within 0.5% of final value for a 50% load step change
Output Current	0.35 A max.

SAFETY

EN/IEC/UL	EN/IEC/UL 60950-1
CE Mark	Yes
Dielectric Withstand	3,000 VAC or 4250 VDC primary to secondary
EMC	EN55022/55024/61000

PROTECTION

Overload Current Detection	(15.4W/Vport) min./ 400mA max.
Overload Time Limit	50 to 75 mS
Short Circuit Protection	400 to 450 mA max.

GENERAL SPECIFICATIONS

Topology	Switching-fixed Frequency Flyback
Dimensions (L x W x H)	3.98 x 2.40 x 1.35 (in), 101.0 x 61.5 x 34.2 (mm)
Weight	5.95 ounces, 170 g
Spacing	6.4mm primary to secondary
Case	Desktop type
Case Material	Black 94V0 polycarbonate
Cord and Connectors	Dual RJ45 Jacks built into the enclosure
Power Mode LED (Two Colors)	Amber Green Power on, detection mode Injecting full power, power up mode


ORDERING INFORMATION TABLE 1

Model Number	Output Voltage	Output Current		Max Watts	Ripple & Noise
		min	max		
PW180KB4800_01	48 V	0.00 A	0.35 A	15.4 W	480 mVpk-pk


ORDERING INFORMATION TABLE 2

PW180	K	B	48	00	-	01
Product Family Name	Manufacturing Location	Design Revision Changes	Voltage DC	Connector Number	Input Configuration/Model Type F: IEC320 with ground C14 N: Shaver C8	Standard (no modifications or special packaging)

INPUT CONFIGURATION




IEC320 w/ground C14 (F)



Shaver C8 (N)

PIN ASSIGNMENTS

Connector	PW180KB	
J1	PIN 1	Data Pair 1
	PIN 2	Data Pair 1
	PIN 3	Data Pair 2
	PIN 4	+ VDC
	PIN 5	+ VDC
	PIN 6	Data Pair 2
	PIN 7	- VDC
	PIN 8	- VDC
J2	PIN 1	Data Pair 1
	PIN 2	Data Pair 1
	PIN 3	Data Pair 2
	PIN 4	No Connection
	PIN 5	No Connection
	PIN 6	Data Pair 2
	PIN 7	No Connection
	PIN 8	No Connection



J1

J2



For international contact information,
visit advancedenergy.com.

powersales@aei.com (Sales Support)
productsupport.ep@aei.com (Technical Support)
+1 888 412 7832

ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than three decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE | TRUST

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2024 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, and AE® are U.S. trademarks of Advanced Energy Industries, Inc.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advanced Energy:](#)

[PW180KB4800N01](#) [PW180KA4800N01](#) [PW180KB4800F01](#) [PW180KA4800F01](#)