## Specification of Quartz Crystal Units



NDK Part Number 1 NX2520SD-24MHZ-EXS00A-CS06352 2 Chipset Maker Please contact us. 3 Application Suitable for application processor with wider temperature range. 4 Chipset Name Please contact us. 5 **NDK Specification Number** EXS00A-CS06352 6 Type NX2520SD **Electrical Characteristics** 7 7.1 Nominal Frequency  $(f_{nom})$ 24.000 MHz 7.2 Overtone order **Fundamental** ±15 ×10<sup>-6</sup> (at +25 °C) 7.3 Adjustment tolerance ±15 ×10<sup>-6</sup> (at -30 to +85 °C) 7.4 Tolerance over the temperature range 50  $\Omega$  Max. 7.5 Equivalent Series Resistance  $(R_r)$ 7.6 200 μW Maximum Drive Level  $\pm 5 \times 10^{-6}$  / Year 7.7 Aging (at +25 °C) 8 Measurement Circuit 8.1 Frequency Measurement Measuring Instrument IEC  $\pi$ -Network 8.1.1 8.1.2 Load Capacitance (C<sub>L</sub>) 12 pF 10 μW 8.1.3 Level of Drive 8.2 **Equivalent Resistance Measurement** 8.2.1 Measuring Instrument IEC  $\pi$ -Network 8.2.2 Load Capacitance (C<sub>L</sub>) Series 10 µW 8.2.3 Level of Drive 9 Operating Temperature Range -30 to +85 °C 10 Storage Temperature Range -40 to +85 °C 11 Dimension (Unit: mm) Land pattern ( Typical ) [TOP VIEW] TERMINAL LAND CONNECTIONS 2.5 +/-0.1 -0.1 3 Terminal #1 and #3 : Xtal Terminal #2 and #4 : GND (Connection Cover 1.7 Cover BASE Alumina Ceramics C 0.3 Tungsten Metalize ( Au plating on Ni plating )

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## NDK:

NX2520SD-24MHZ-EXS00A-CS06352 CS06352-24M