

NX3225GA

For OA / AV

■ Features

A small surface-mount type crystal unit, especially suited for small-sizing requirements.

- Compact and thin. (3.2 x 2.5 x 0.75 mm typ.)
- Excellent environmental characteristics, including heat and shock resistance.
- Excellent electrical performance for OA (office automation) and AV (audiovisual) applications.
- Meets the requirements for re-flow profiling using lead-free solder.



RoHS Compliant
Directive 2011/65/EU

■ Specifications

Item	Model	NX3225GA
Nominal frequency		9.840 to 50 MHz
Overtone order		Fundamental
Frequency tolerance (25 ±3 °C)		±20 × 10 ⁻⁶
Frequency versus temperature characteristics (with reference to +25 °C)		±30 × 10 ⁻⁶
Operating temperature range		-10 to +70 °C
Storage temperature range		-40 to +85 °C
Equivalent series resistance		Refer to *1
Level of drive		10 µW (Max. 200 µW)
Load capacitance		8 pF

The above specifications are standard for this NDK product.

Custom-made specifications such as load capacitance and temperature characteristics are also available.

Please contact NDK sales with your enquiries.


■ How to Specify an Order

When ordering our products, specify them with an "Ordering Code" that consists of the following :

[Model name] - [Frequency (Max : 9 digits)] M - [Number for specifying an order] Example NX3225GA-27.000M-STD-CRG-1

If you have any queries concerning our standard frequencies and numbers for specifying orders, please contact our sales representatives or visit our homepage (<http://www.ndk.com/>).

■ Dimensions



*1 Equivalent Series Resistance

Nominal frequency (MHz)	Equivalent Series Resistance max. [Ω]
9.840 to 12	200
12 to 13	100
13 to 20	80
20 to 50	50

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NDK:](#)

[NX3225GA-27.000M-STD-CRG-1](#) [NX3225GA-20.000M-STD-CRG-1](#) [NX3225GA-25.000M-STD-CRG-1](#) [NX3225GA-12MHZ-STD-CRG-1](#) [NX3225GA-26.000M-STD-CRG-1](#) [NX3225GA-14.7456M-STD-CRG-1](#) [NX3225GA-16.000M-STD-CRG-1](#) [STDCRG1-14.7456M](#) [STDCRG1-20M](#) [STDCRG1-25M](#) [STDCRG1-26M](#) [STDCRG1-16M](#) [STDCRG1-12M](#) [STDCRG1-27M](#)