

Features


Package	3in1 Top Viewing type Outline dimension 3.0 x 2.8 x 0.6mm (L x W x H)
Product features	<ul style="list-style-type: none"> • Ultra-thin • RGB tri-color emitting LED • Lead-free soldering compatible • RoHS compliant

Recommended applications


Light source for automotive interior, various illumination, etc.

Outline dimensions

CRGB1314ASE-500-TR



Pin Connection




Unit : mm

Weight : 10mg

Tolerance : ± 0.1

No.	PART NAME	REMARKS	QTY.
①	LED die	AlGaInP, InGaN	3
②	Protection diode	Silicon	2
③	Mold resin	Silicone resin	1
④	Substrate (Electrode: Au plating)	Glass fabrics	1

Recommended pad



Unit : mm

Specifications

CRGB1314ASE-500-TR

【 Product overview 】

	LED Die (1)	LED Die (2)	LED Die (3)
Material	AlGaInP	InGaN	InGaN
Emitting color	Red	Green	Blue
Lens color	Milky white		

【 Absolute maximum ratings 】

(Ta=25℃)

ITEM		SYMBOL	LED Die (1) Red	LED Die (2) Green	LED Die (3) Blue	UNITS
Power Dissipation		P _d	90	105	105	mW
Total Value of Power Dissipation		P _d	260			mW
Forward Current (1 LED emitted)		I _F	30	25	25	mA
Forward Current (2 or 3 LEDs emitted)		I _F	30	25	20	mA
Repetitive Peak Forward Current (1 LED emitted)		I _{FRM}	100	100	100	mA
<div> <div>Current Derate Linearly</div> <div> <div>Derate Linearly From 80℃</div> </div> </div>	DC (1 LED emitted)	ΔI _F	0.75	0.65	0.65	mA/℃
	DC (2 or 3 LEDs emitted)		0.75	0.65	0.50	mA/℃
	Pulse (1 LED emitted)	ΔI _{FRM}	2.5	2.5	2.5	mA/℃
Reverse Voltage		V _R	5	—	—	V
Reverse Current		I _R	—	70	70	mA
Operating Temperature		T _{opr}	-40 ~ +100			℃
Storage Temperature		T _{stg}	-40 ~ +120			℃
Junction Temperature		T _j	120			℃

Notes

※1. All LEDs emitted , forward current should not exceed Max. total value of power dissipation.
Total value of power dissipation at Ta=80℃ or more, please refer to technical data.

※2. IFRM Conditions : Pulse width ≤ 1ms, Duty ≤ 1/20

【 Thermal characteristics 】

ITEM	SYMBOL	TYP.	UNITS
Thermal resistance 【Junction - Ambient】(One LED emitted)	R _{th(j-a)}	450	℃/W
Thermal resistance 【Junction - Ambient】(2 or 3 LEDs emitted)	R _{th(j-a)}	500	℃/W
Thermal resistance 【Junction - Solder point】(One LED emitted)	R _{th(j-s)}	350	℃/W
Thermal resistance 【Junction - Solder point】(2 or 3 LEDs emitted)	R _{th(j-s)}	400	℃/W

※3,4 R_{th(j-a)} Measurement conditions

• Substrate:FR4 (t=1.6mm)

• Pattern size : 16mm²

Specifications

CRGB1314ASE-500-TR

【 Electro-Optical characteristics 】

LED die (1) Red (Ta=25°C)

ITEM	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	$I_F = 22\text{mA}$	1.6	2.1	2.8	V
Reverse Current	I_R	$V_R = 5\text{V}$	—	—	50	μA
Luminous Intensity	I_V	$I_F = 22\text{mA}$	560	820	1,000	mcd
Dominant Wavelength	λ_d	$I_F = 22\text{mA}$	614	622	632	nm

LED die (2) Green (Ta=25°C)

ITEM	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	$I_F = 23\text{mA}$	2.6	3.2	3.9	V
Luminous Intensity	I_V	$I_F = 23\text{mA}$	1,500	2,080	2,700	mcd
Dominant Wavelength	λ_d	$I_F = 23\text{mA}$	515	532	540	nm

LED die (3) Blue (Ta=25°C)

ITEM	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	$I_F = 14\text{mA}$	2.4	3.1	3.7	V
Luminous Intensity	I_V	$I_F = 14\text{mA}$	100	300	470	mcd
Dominant Wavelength	λ_d	$I_F = 14\text{mA}$	460	469	480	nm

All LED emitted (Ta=25°C)


ITEM	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total Luminous Intensity	I_V	RED : $I_F=22\text{mA}$ GREEN : $I_F=23\text{mA}$ BLUE : $I_F=14\text{mA}$	2,060	3,100	4,070	mcd
Chromaticity Coordinates	x		—	0.30	—	—
	y		—	0.32	—	—

※1

※1. Please refer to chromaticity coordinate rank chart.



【Sorting chart for chromaticity coordinates】





Chromaticity coordinates is sorted out into the following chat.







Rank	Left down		Left upper		Right upper		Right down		CONDITIONS
	x	y	x	y	x	y	x	y	
A2	0.265	0.360	0.265	0.385	0.290	0.390	0.290	0.365	Red I _F =22mA
A4	0.265	0.335	0.265	0.360	0.290	0.365	0.290	0.340	
B1	0.290	0.365	0.290	0.390	0.315	0.400	0.315	0.375	
B2	0.315	0.375	0.315	0.400	0.340	0.410	0.340	0.385	
B3	0.290	0.340	0.290	0.365	0.315	0.375	0.315	0.350	
B4	0.315	0.350	0.315	0.375	0.340	0.385	0.340	0.360	Green I _F =23mA
D2	0.265	0.310	0.265	0.335	0.290	0.340	0.290	0.315	
D4	0.265	0.285	0.265	0.310	0.290	0.315	0.290	0.290	
E1	0.290	0.315	0.290	0.340	0.315	0.350	0.315	0.325	Blue I _F =14mA
E2	0.315	0.325	0.315	0.350	0.340	0.360	0.340	0.335	
E3	0.290	0.290	0.290	0.315	0.315	0.325	0.315	0.300	
E4	0.315	0.300	0.315	0.325	0.340	0.335	0.340	0.310	
G2	0.265	0.260	0.265	0.285	0.290	0.290	0.290	0.265	
H1	0.290	0.265	0.290	0.290	0.315	0.300	0.315	0.275	
H2	0.315	0.275	0.315	0.300	0.340	0.310	0.340	0.285	

Notes Above chromaticity coordinates sorting values are values measured on Stanley’s production line.
2017.9.28 (Tolerance : ±0.02)













Technical data (LED die 2: Green)

CRGB1314ASE-500-TR






Technical data (LED die 2: Green)

CRGB1314ASE-500-TR


Forward voltage vs. Ambient temperature

Condition : $I_F = 5$ to 25mA




Maximum Forward current vs. Ambient temperature

Repetition frequency : $f \geq 50\text{Hz}$




Dominant wavelength vs. Forward current



Condition : $T_a = 25^\circ\text{C}$











Ambient temperature vs. Dominant wavelength



Condition : $I_F = 20\text{mA}$















Technical data (3 LEDs emitted : White)

CRGB1314ASE-500-TR




【Soldering precaution】

(acc.to EIAJ-4701/300)

- Heat stress during soldering will influence the reliability of LEDs, however that effect will vary with heating method. Also, if components with different shapes need to be mounted together, it is recommended to set the soldering pad temperature according to the component most vulnerable to heat stress (ex. SMT LED). (Recommended Condition: Soldering Pad temp. > Package temp.)
- LED parts including the resin are not stable immediately after soldering (when they are not at room temperature), any mechanical stress may cause damage to the product. Please avoid such stress after soldering, especially stacking of the boards which may cause the boards to warp and any other types of friction with hard materials.).
- Recommended temperature profile for the Reflow soldering is listed as the temperature of the resin surface. Temperature distribution varies on heating method, PCB material, other components in the assembly, and mounting density .
Please do not repeat the heating process in Reflow process more than twice.

【Recommended reflow soldering condition.】



Note 1

Recommended temperature profile for the reflow soldering is listed as the temperature of the resin surface. This should be the maximum temperature for soldering. Lowering the heating temperature and decreasing heating time is very effective in achieving higher reliability.

Note 2

The reflow soldering process should be done up to twice(2 times Max).
 When second process is performed, interval between first and second process should be as short as possible to prevent absorption of moisture to resin of LED.
 The second soldering process should not be done until LEDs have returned to room temperature (by nature-cooling) after first soldering process.

Soldering conditions

CRGB1314ASE-500-TR

4. If soldering manually, Stanley recommends using a soldering iron equipped with temperature control. During the actual soldering process, make sure that the soldering iron never touches the LED itself, and avoid the LED's electrode heating temperature reaching above the heating temperature of the solder pad. All repairs must be performed only once in the same spot, and please avoid reusing components.
5. In soldering process, immediately after iron tip is cleaned, please make sure that the soldering iron reaches the appropriate temperature, before using. Also, please avoid applying any types of pressure to the soldered components before the solder has been cooled and hardened, as it may deteriorate solder performance and solder quality.

【Recommended manual soldering condition.】

Temperature of iron tip	350°C MAX.
Soldering duration, Time	3sec. Max., 1 time

6. When using adhesive material for tentative fixatives, thermosetting resin or Ultraviolet radiation (UV) setting resin with heat shall be recommended. 《The curing condition, Temperature: 150°C Max./Time: 120sec. Max.》
7. Flow soldering (dip soldering) is not recommended for this product.
8. Isopropyl alcohol is recommended for cleaning. Some chemicals, including Freon substitute detergent could corrode the lens or the casing surface, which cause discoloration, cloud, crack and so on. Please review the reference chart below for cleaning. If water is used to clean (including the final cleaning process), please use pure water (not tap water), and completely dry the component before using.

Cleaning agents	Recommended / Not recommended
Isopropyl alcohol	✓ Recommended
Trichloroethylene	x Not recommended
Chloroethene	x Not recommended
Acetone	x Not recommended
Thinner	x Not recommended

【 For electric static discharge (ESD) 】

This kind of LED lamp is highly sensitive to surge voltage generated by the On/Off status change and discharges of static electricity through frictions with synthetic materials, which may cause severe damage to the die or undermine its reliability. Damaged products may experience conditions such as extremely high reverse voltage, or a decrease of forward rise voltage, deteriorating its optical characteristic.

Stanley products are designed to withstand up to 1,000V under the EIAJ ED-4701/300 Test #304 (HBM), and are packed with anti-static components. However, the following precautions and measures are vital in ensuring product quality during shipment.

EIAJ ED-4701/300 (304/HBM) Electrification model: $C=100\text{pF}$, $R_2=1.5\text{K}\Omega$

1. Electrification/Static electricity protection

Stanley recommends the following precautions in order to avoid product (die) damage from static electricity, when an operator and other materials electrified by friction coming in contact with the product.

- ① Do not place electrified non-conductive materials near the LED product.
Avoid LED products from coming into contact with metallic materials.(Should the metallic material be electrified, the sudden surge voltage will most likely damage the product.)
- ② Avoid a working process which may cause the LED product to rub against other materials.
- ③ Install ground wires for any equipment, where they can be installed, with measures to avoid static electricity surges.
- ④ Prepare a ESD protective area by placing a conductive mattress ($1\text{M}\Omega$ MAX.) and ionizer to remove any static electricity.
- ⑤ Operators should wear a protective wrist-strap.
- ⑥ Operators should wear conductive work-clothes and shoes.
- ⑦ To handle the products directly, Stanley recommends the use of ceramic, and not metallic, tweezers.

2. Working environment


- ① A dry environment is more likely to cause static electricity. Although a dry environment is ideal for storage state of LED products, Stanley recommends an environment with approximately 50% humidity after the soldering process.
- ② Recommended static electricity level in the working environment is less than 150V, which is the same value as integrated circuits (which are sensitive to static electricity).

【 Other precautions 】


1. Stanley LEDs have semiconductor characteristics and are designed to ensure high reliability. However, the performance may vary depending on usage conditions
2. Absolute maximum ratings are set to prevent LEDs from failing due to excess stress (temperature, current, voltage, etc.). Usage conditions must not exceed the ratings for a moment, nor do reach one item of absolute maximum ratings simultaneously.
3. In order to ensure high reliability from LEDs, variable factors that arise in actual usage conditions should be taken into account for designing. (Derating of Typ., Max. forward voltage, etc.)
4. Please insert straight protective resistors into the circuit in order to stabilize LED operation and to prevent the device from igniting due to excess current.
5. Please avoid the stick of foreign material because molding resin in the products have adhesiveness. And please don't touch lens portion.
6. Please check the actual performance in the assembly because the specification sheets are described for LED device only.
7. Please refrain from looking directly at the light source of LED at high output, as it may harm your vision.
8. The products are designed to operate without failure in recommended usage conditions. However, please take the necessary precautions to prevent fire, injury, and other damages should any malfunction or failure arise.
9. The products are manufactured to be used for ordinary electronic equipment. Please contact our sales staff beforehand when exceptional quality and reliability are required, and the failure or malfunction of the products might directly jeopardize life or health (such as for airplanes, aerospace, transport equipment, medical applications, nuclear reactor control systems and so on).
10. The formal specification sheets shall be valid only by exchange of documents signed by both parties

【 Handling precautions for product mounting 】

<Recommendation>

1. Pick up point : Lamp housing of the product ( area) (Shown below)

The picking up point should be within lamp housing portion, because the silicone resin used for the lens is soft. (If the nozzle makes contact with the lens, the products might be destroyed)



2. Load : Less than 5N

Please adjust the load, the pick up point, the nozzle diameter etc. before mounting, because lamp housing might get destroyed due to overload and improper shape of nozzle.
 Please set up vacuum breaker or air blower to make sure that product being putted down on soldering pad after it being picked up by nozzle.

This product is baked (moisture removal) before packaging, and is shipped in moisture-proof packaging (as shown below) to minimize moisture absorption during transportation and storage. However, with regard to storing the products, Stanley recommends the use of dry-box under the following conditions is recommended. Moisture-proof bag as the packaging is made of anti-static material but packaging box is not.

【Recommended storage condition / Products warranty period 】

Temperature	+5～30℃
Humidity	Under 70%

In the case of the package unopened , **6 months under 【 Recommended Storage Condition 】**.
Please avoid rapid transition from low temp. condition to high temp. condition
and storage in corroding and dusty environment.

【Time elapsed after package opening.】

The package should not be opened until immediately prior to its use, and please keep the time frame between package opening and soldering which is **【maximum 672h】**.
If the device needs to be soldered twice, both soldering operations must be completed within the 672h.

If any components should remain unused, please reseal the package and store them under the conditions described in the **【 Recommended Storage Condition 】** above.

This product must be required to perform baking process (moisture removal) for **at 48h(MIN.). to 72h(MAX.) at 60±5 degrees Celsius** if following conditions apply.


1. In the case of silica gel (blue) which indicates the moisture level within the package,
changes or loses its blue color.
2. In the case of time passes for 672h after the package is opened once.

Baking process should be performed after LED having been taken out of the package.

Baking may be performed in the tape-reel form , however if it is performed with the reel stacked over one another, it may cause deformation of the reels and taping materials and later obstruct mounting.


Please handle only once it has returned to room temperature. Provided that, baking process shall be 2 times max.

【 Moisture-proof packaging specification 】



NO.	PART NAME	MATERIALS	REMARKS
①	Moisture-proof bag with Aluminum layer	PET+Al+PE	with ESD protection

【 Flow chart-package opening to mounting 】



Allowable leaving time means the maximum allowable leaving time after opening package, which depends on each LED type.

The allowable leaving time should be calculated form the first opening of package to the time when soldering process is finished.

When judging if the allowable leaving time has exceeded or not, please subtract the soldering time. The allowable leaving time after reopening should be calculated form the first opening of package, or from the time when baking process is finished.


【 Packing box 】

(RoHS・ELV Compliant)

Box type	Outline dimension L × W × H (mm)	Capacity of the box
Type A	280 × 265 × 45	3 reels
Type B	310 × 235 × 265	15 reels
Type C	440 × 310 × 265	30 reels

The above measure is all the reference value.

The box is selected out of the above table, by shipping quantity.



Type A

Material / box : Cardboard C5BF

Type B,C

Material / box : Cardboard K5AF
Partition : Cardboard K5BF


NO.	PART NAME	MATELRIAL	REMARKS
②	Packing box	Corrugated cardboard	without ESD protection

【Label specification】

(acc.to JIS-X0503(Code-39))

A


Product Label



- A. Parts number
- B. Bar-code for parts number
- C. Parts code (In-house identification code for each parts number)
- D. Packed parts quantity
- E. Bar-Code for packed parts quantity
- F. Lot number & Rank
 - (refer to Lot Number Notational System for details)
- G. Bar-Code for Lot number & Rank

B

Opto Device Label



- A. Customer Name
- B. Parts Type
- C. Parts Code
- D. Parts Number
- E. Packed Parts Quantity
- F. Carton Number
- G. Shipping Date
- H. Bar-Code for In-house identification Number

<Remark>


Bar-code font : acc.to Code-39(JIS-X0503)

Taping and reel specifications

CRGB1314ASE-500-TR

(acc.to JIS-C0806)

【Appearance】



Note
"-TR" means Cathode Side of LEDs should be placed on the sprocket-hole side.

Items		Specifications	Remarks
Leader area	Cover-tape	Cover-tape shall be longer than 300mm without carrier-tape	The end of cover-tape shall be held with adhesive tape.
	Carrier-tape	Empty pocket shall be more than 25pieces.	Please refer to the above figure for Taping & reel orientation.
Trailer area		Empty pocket shall be more than 40pieces.	The end of taping shall be inserted into a slit of the hub.

Taping and reel specifications

CRGB1314ASE-500-TR

【Qty. per reel】

4,000 parts/reel (Note1)

Note1 Minimum Qty. per reel might be 500 parts when getting less than 4,000 parts. In such case, parts of 500-unit-qty. shall be packed in a reel and the qty. shall be identified on the label.

【 Mechanical strength】

Cover-tape adhesive strength shall be 0.1 ~ 1.0N

(An angle between carrier-tape and cover-tape shall be 170 deg.)

Both tapes shall be so sealed that the contained parts will not come out from the tape when it is bent at a radius of 15mm.

【Others】

Reversed-orientation, Up-side down placing, side placing and out of spec. parts mix shall not be held. Max qty. of empty pocket per reel shall be defined as follows.

Qty./reel	Max. qty. of empty pocket	Remarks
500	1	-
1,000	1	-
1,500	1	-
2,000	2	No continuance
2,500	2	No continuance
3,000	3	No continuance
3,500	3	No continuance
4,000	4	No continuance

CRGB1314ASE-500-TR

Unit :mm

Technical drawing of a mechanical part, showing front and side views with dimensions and callouts.

Front View (Left):

- Overall width: 4 ± 0.1
- Overall height: 8 ± 0.2
- Top edge features three circular holes with diameter $\phi 1.5^{+0.1}_0$.
- Bottom edge features a central hole with diameter $\phi 1.1$ and a square feature with a circular hole.
- Dimensions for the top holes: 1.75 ± 0.1 (from top edge to center of first hole), 3.5 ± 0.05 (from center of first hole to center of last hole), and 2 ± 0.05 (from center of last hole to bottom edge).
- Dimensions for the bottom features: 4 ± 0.1 (from left edge to center of central hole), 2 ± 0.05 (from center of central hole to right edge), and 4 ± 0.1 (from left edge to center of square feature).
- Callout ① points to the top holes.
- Callout ② points to the central hole.
- Callout (CENTER HOLE) points to the square feature.

Side View (Right):

- Overall width: 0.2
- Overall height: 0.75
- Dimensions for the side features: 0.2 (from top edge to center of first hole), 3.3 (from center of first hole to center of last hole), and 2 (from center of last hole to bottom edge).
- Callout ② points to the central hole.
- Callout (CENTER HOLE) points to the square feature.

Technical drawing of a circular mechanical part, showing front and side views with dimensions.


Front View (Right):

- Overall diameter: $\phi 180 \begin{smallmatrix} 0 \\ -3 \end{smallmatrix}$
- Inner circular feature diameter: $\phi 21 \pm 0.8$
- Distance from top edge to center of inner feature: 2 ± 0.5
- Feature 3 is indicated by a circled number 3 and a leader line pointing to a hole in the upper right quadrant.
- Four radial slots are present, each with a width of 0.5 and a depth of 0.5 .

Side View (Left):

- Overall height: $\phi 60 \pm 0.1$
- Distance from top edge to center of inner feature: 13 ± 0.2
- Distance from bottom edge to center of inner feature: 9 ± 0.2
- Distance from bottom edge to the start of the radial slots: 11.4 ± 0.1

NO.	PART NAME	REMARKS
①	Carrier-tape	with ESD protection
②	Cover-tape	without ESD protection
③	Carrier-real	with ESD protection



① - 1digit : Production location (Mark identify alphabet) : : : : :

② - 1digit : Production year (Last digit of production year 2020→0, 2021→1, 2022→2, 2023→3, 2024→4 …)

③ - 2digits : Production month (Jan. to Sep. , shall be indicated as 01,02,03,……)

④ - 2digits : Production date

⑤ - 3digits : Serial number

⑥ - 2digits : Tape and Reel following number

⑦ - 2digits : Luminous intensity rank.
 (If luminous intensity rank is 1 digit, "-" shall be dashed on the place for the second digit.
 If there is no l identified intensity rank, "- -" is used to indicate.)

⑧ - 2digits : Chromaticity rank
 (If chromaticity rank is 1 digit, "-" shall be dashed on the place for the second digit.
 If there is no identified intensity rank, "- -" is used to indicate.)

⑨ - 1digit : Optional rank (Stanley normally indicates "-".)

Correspondence to ELV • RoHS instruction

CRGB1314ASE-500-TR

This product is in compliance with RoHS •ELV.

Prohibition substance and it's criteria value of RoHS •ELV are as follows.

- ELV instruction Refer to following (1)~(4).
- RoHS instruction Refer to following (1)~(6).

	Substance group name	Criteria value
(1)	Lead and its compounds	1,000ppm Max
(2)	Cadmium and its compounds	100ppm Max
(3)	Mercury and its compounds	1,000ppm Max
(4)	Hexavalent chromium	1,000ppm Max
(5)	PBB	1,000ppm Max
(6)	PBDE	1,000ppm Max

Reliability test results

CRGB1314ASE-500-TR

Test Item	Standard	Test Condition	Duration	Failure
Room temperature operating life	EIAJ ED-4701 /100(101)	Ta=25°C I _F (Red)=30mA, (Green)=25mA, (Blue)=20mA	1,000h	0 / 20
High temperature operating life	EIAJ ED-4701 /100(101)	Ta=85°C I _F (Red)=26.25mA, (Green)=21.75mA, (Blue)=17.5mA	1,000h	0 / 20
Low temperature operating life	EIAJ ED-4701 /100(101)	Ta=-40°C I _F (Red)=30mA, (Green)=25mA, (Blue)=20mA	1,000h	0 / 20
Wet high temperature operating life	EIAJ ED-4701 /100(102)	Ta=60°C Rh=90% I _F (Red)=30mA, (Green)=25mA, (Blue)=20mA	1,000h	0 / 20
High temperature storage life	EIAJ ED-4701 /200(201)	Ta=120°C	1,000h	0 / 20
Low temperature storage life	EIAJ ED-4701 /200(202)	Ta=-40°C	1,000h	0 / 20
Wet high temperature storage life	EIAJ ED-4701 /100(101)	Ta=60°C Rh=90%	1,000h	0 / 20
Thermal shock	EIAJ ED-4701 /100(105)	Ta=-40°C ~ 120°C (each 15min)	1,000 cycles	0 / 20
Thermal shock operating	EIAJ ED-4701 /100(105)	Ta=-40°C(Off) ~ 85°C(On ※) ※On : I _F (Red)=26.25mA, (Green)=21.75mA, (Blue)=17.5mA (each 15min)	1,000 cycles	0 / 20
Cycled temperature humidity operating life	EIAJ ED-4701 /200(203)	Ta=-30°C(2h) ~ 80°C 95%(2h) 8h/cycle I _F (Red)=26.25mA, (Green)=21.75mA, (Blue)=17.5mA 5min on-off	30 cycles	0 / 20
Resistance to reflow soldering	EIAJ ED-4701 /300(301)	Moisture soak : 30°C 70% 672h Preheating : 150~180°C 90-120sec Soldering : 260°C peak	2times	0 / 20
Electrostatic discharge (ESD) ※	EIAJ ED-4701 /300(304)	C=100pF R2=1.5kΩ ±2,000V	3 times of each polarity	0 / 10
Vibration, Variable frequency	EIAJ ED-4701 /400(403)	98.1m/s ² (10G) 100~2,000Hz 20min sweep XYZ direction	2h of each direction	0 / 10

※ Reference test

Failure criteria

Item	Symbol	Condition	Failure criteria
Luminous intensity	I _V	I _F : Value of each emitted color's luminous intensity	Testing Min. Value < Standard Min. Value × 0.5
Forward voltage	V _F	I _F : Value of each emitted color's luminous intensity	Testing Max. Value ≥ Standard Max. Value × 1.2
Cosmetic Appearance	-	-	Notable discoloration, deformation and cracking

Special notice to customers using the products and technical information shown in this data sheet

- 1) The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products. It does not constitute the warranting of industrial property nor the granting of any license.
- 2) For the purpose of product improvement, the specifications, characteristics and technical data described in the data sheets are subject to change without prior notice. Therefore it is recommended that the most updated specifications be used in your design.
- 3) When using the products described in the data sheets, please adhere to the maximum ratings for operating voltage, heat dissipation characteristics, and other precautions for use. We are not responsible for any damage which may occur if these specifications are exceeded.
- 4) The products that have been described to this catalog are manufactured so that they will be used for the electrical instrument of the benchmark (OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument).
The application of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. needs a high reliability and safety, and the breakdown and the wrong operation might influence the life or the human body. Please consult us beforehand if you plan to use our product for the usages of aircrafts, space borne application, transportation equipment, medical equipment and nuclear power control equipment, etc. except OA equipment, telecommunications equipment, AV machine, home appliance and measuring instrument.
- 5) In order to export the products or technologies described in this data sheet which are under the “Foreign Exchange and Foreign Trade Control Law,” it is necessary to first obtain an export permit from the Japanese government.
- 6) No part of this data sheet may be reprinted or reproduced without prior written permission from Stanley Electric Co., Ltd.
- 7) The most updated edition of this data sheet can be obtained from the address below:
<http://www.stanley-components.com/en>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Stanley Electric:

[CRGB1314ASE-500-TR](#)