

CRYSTEK
MICROWAVE
A DIVISION OF CRYSTEK CORPORATION

Low Pass Filter
50Ω SMA
7th Order




Part Number: CLPFL-0500

Low Pass Range
DC to 500 MHz



Schematic



Features:


- 7th Order Butterworth Response
- 50Ω SMA Connectors

Applications:

- Test Equipment
- Lab Use

Maximum Ratings:

- +36dBm (4 Watts)
- Operating Temperature: -40°C to 85°C
- Storage Temperature: -55°C to 100°C



Crystek's new line of Low Pass Filters are designed in a rugged SMA housing. This filter line has excellent out-of-band rejection. Designed for Test Equipment and General Lab Use.


Rev C

Page 1 of 3




CRYSTEK
CORPORATION


12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM




500 MHz Insertion Loss




Male Side Return Loss



Female Side Return Loss





FREQ (MHz)	INSERTION LOSS (dB)	Male Return Loss (dB)	Female Return Loss (dB)
0.3	0.06	44.53	44.82
15.3	0.06	35.82	35.86
30.3	0.12	31.25	31.36
45.3	0.14	28.60	28.69
60.3	0.16	26.74	26.94
75.3	0.21	25.42	25.72
90.3	0.20	24.58	24.73
105	0.24	23.74	24.19
120	0.24	23.42	23.86
135	0.27	23.05	23.76
150	0.30	23.17	23.68
165	0.29	23.29	24.02
180	0.31	23.70	24.72
195	0.35	24.48	25.81
210	0.30	25.45	27.07
225	0.37	27.06	29.31
240	0.33	29.25	32.68
255	0.37	32.23	40.16
270	0.40	34.88	42.38
285	0.41	32.00	31.85
300	0.44	27.61	27.03
330	0.47	21.36	20.74
405	0.90	12.34	12.25
450	1.59	8.74	8.73
510	2.27	5.14	5.17
585	6.09	2.36	2.47
705	15.09	0.83	1.03
810	24.16	0.51	0.51
900	32.22	0.33	0.16
1005	44.82	0.23	-0.21
1245	46.09	0.06	-0.51
1500	44.09	0.03	-0.54
1755	43.83	0.07	-0.44
1995	44.15	0.11	-0.18
2250	45.13	0.23	0.05
2505	46.30	0.33	0.25
2745	47.77	0.46	0.37
3000	49.50	0.58	0.51

Product Control:

Crystek Part Number:	CLPFL-0500	Release Date:	04-Aug-2015
Revision Level:	C	Responsible:	K. Piotrowicz

Rev C

Page 3 of 3



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Crystek:](#)

[CLPFL-0500](#)