



PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			79	MHz
Upper Frequency:	111			MHz
Tuning Voltage:	0.5		4.5	VDC
Supply Voltage:	4.47	4.7	4.93	VDC
Output Power:	0	+5.0	+10.0	dBm
Supply Current:		20		mA
Harmonic Suppression (2 nd Harmonic):		-10	-5	dBc
Pushing:		1.0	2.0	MHz/V
Pulling, all Phases:		1.0	2.0	MHz pk-pk
Tuning Sensitivity:		11		MHz/V
Phase Noise @ 10kHz offset:		-112		dBc/Hz
Phase Noise @ 100kHz offset:		-134		dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			100	pF
Operating Temperature Range:	-10		+70	°C
Storage Temperature Range:	-45		+90	°C

Phase Noise (1 Hz BW, Typical)





Tuning Curve (Typical)



Product Control:


Crystek Part Number:	CVCO45CL-0079-0111	Release Date:	02-Nov-2016
Revision Level:	L	Responsible:	C. Vales





- Unless otherwise specified, Dimensions are in: IN (mm)
- Pad Location Dimensions are in: Inches

TAPE AND REEL



Drawing not to scale

Product Control:

Crystek Part Number:	CVCO45CL-0079-0111	Release Date:	02-Nov-2016
Revision Level:	L	Responsible:	C. Vales

Specification is subject to change without notice

Page 2 of 2



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Crystek:](#)

[CVCO45CL-0079-0111](#)