


Für diese Unterlage behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustererteilung. Sie darf ohne unsere vorherige schriftliche Zustimmung weder vervielfältigt noch sonstwie benutzt, noch Drillen zugänglich gemacht werden.

Nur rol gestempelte oder auf Laufkarte gedruckte Dokumente unterliegen dem Änderungsdienst und sind zur Fertigung freigegeben. Only red stamped or on jobcard printed documents are managed. These documents are approved for production.


All Rights reserved, including possible patents or trademarks. Documents shall not be provided to a third party or duplicated in any form without prior written permission.

CAD: Pro/ENGINEER


Additional coding
View in direction B



G81YBR-P14WCD0-000L
Mechanical coding: B
Color coding: red





G81YCR-P14WCD0-000L
Mechanical coding: C
Color coding: blue




G81YDR-P14WCD0-000L
Mechanical coding: D
Color coding: green



Panel cut-out




G81YAR-P14WCD0-000L
Mechanical coding: A
Color coding: light brown



Delivery condition
2:1



Only insert and earth tag
View in direction A
6:1




Technical information

- Solder contacts: AWG26
- Current load: 5A@t40° (Single contact)
2.5A@t40° (Insert)
- Test voltage: 900V (acc. SAE AS 13441:1998, Contact to contact)
- Rated voltage: 300V (acc. SAE AS 13441:1998) 2)

- For more technical information and accessories see catalogue (www.odu.de/amc)

- 1) ODU recommend an additional locking of the nut with adhesive (e.g. Loctite 2701) to the screw thread.
- 2) Maximal operating voltage at sea level up to 2.000m. Rated voltage applies no other electrical safety standard. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. This must be evaluated in the frame of equipment engineering.

All shown connectors are according to DIN EN 61984:2009 connectors without breaking capacity (COC) !

				Dimensions without tolerances acc. to middle DIN ISO 2768			PE-modell-nr.:		
							CAD-nr.:	00050838	sheet.:
				2011	date	name	designation:		scale:
				prep.	19.10.	M. Meier	Receptacle style 8 AMC Standard Version		3:1
				app.					
				norm.					
				 otto dunkel gmbh			drawing nr.:	copy	
							G81Y.R-P14WCD0-000L		
index	notice	date	name				replacement for:		nr.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ODU USA:

G81YAR-P14WCD0-000L