K22K0C-P26LCC0-850S

$series_k$

type_k2




General information


Part number	K22K0C-P26LCC0-850S	
Termination	solder	
Size	2	
Locking principle	break, push	
Coding	0_key	Illustrations may differ fro Dimensions, unless other
Cable Diameter	cable_mini_85	Differences, unless outer
Cable outlet	bend_relief	



Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.







The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	26
Contact type	sockets
Contact diameter	05mm
Insulator material	peek
Wire cross section	28_awg
Termination	solder
Termination diameter	045mm

reverse_gender_on_request

Technical information

Max. creepage and air clearance distance	06_mm	08_mm
Nominal current single contact	04_a	iec_60512_5_2
Test voltage	09_kv_ac	sae_13441

safety_text

Mechanical and environmental data

Degree of protection*	ip68
Operating temperature	40_120_c
Mating cycles	5000

mated

Material and surface treatments

Housing	m_chrome
Contact	cu_alloy_gold

safety_text_2 ul_text illustrative_text

K22K0C-P26LCC0-850S type_k2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ODU:

K22K0C-P26LCC0-850S