

7	8	
Spanmutter Back nut Anzugsdrehmoment: torque value	1.0 Nm	A
SW10		В
		C
*) Darstel	lung nur Beispiel!	D
view on only for example! S21LOC-P06MFG0-770S min. 7.0 max. 7.7 S21LOC-P06MFG0-720S min. 6.0 max. 7.2 S21LOC-P06MFG0-620S min. 5.0 max. 6.2 S21LOC-P06MFG0-520S min. 4.0 max. 5.2 S21LOC-P06MFG0-420S min. 3.0 max. 4.2 S21LOC-P06MFG0-320S min. 2.0 max. 3.2 S21LOC-P06MFG0-220S min. 1.5 max. 2.2 Artikelnummer KabelØ Partnumber CableØ		$ \begin{array}{c} 1x . 7 . 2 \\ 1x . 6 . 2 \\ 1x . 5 . 2 \\ 1x . 4 . 2 \\ 1x . 3 . 2 \\ 1x . 2 . 2 \end{array} E $
	Rohgew.: PE-Modell-	
00037686		Bl.:
- Stecker		Ma∩stab:
		4:1
Zeichnungs Nr.: S21LOC - PO6MFGOOS		Vervielf. Pause
Ersatz für: Nr.		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ODU: <u>S21L0C-P06MFG0-620S</u>