



Laird Connectivity's OC24005 is a 2400-2500 MHz omnidirectional, collinear, vertically polarized array especially designed to complement interior- or exterior-mounted wireless network systems. An integrated RF connector is embedded in the antenna base cap for direct AP mounting. Special venting permits either upright or inverted orientation in outdoor locations. The antenna may also be pole-mounted when separation from the AP is required for optimum positioning.

### FEATURES AND BENEFITS

- Vertically polarized omnidirectional
- Indoor and outdoor usage
- Rugged, lightweight, and water resistant
- Direct to radio mounting

### APPLICATIONS

- Offices, hotels, college campuses
- Airports and hospitals
- Museums, libraries, retail malls
- Transportation centers
- Wi-Fi hot spots
- Cellular off-loading

### ELECTRICAL SPECIFICATIONS

Model Name	OC24005
Operating Frequency (MHz)	2400-2500
VSWR – Max	1.7:1
Gain (dBi)	5
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	50
Polarization	Linear, vertical
Vertical Plane 3 dB Beamwidth	30°
Horizontal Plane 3 dB Beamwidth	Omnidirectional

### MECHANICAL SPECIFICATIONS

Dimensions – mm (inches)	297 x 32 (11.7 x 1.26)
Weight – kg (lbs.)	0.14 (0.31)
Radome Material	Polycarbonate, UV white
Connector	Model-specific
Mounting	Connector fixed or mast mount kit (upright/inverted orientations)


### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature – °C (°F)	-30 to +70°C (-22 to +158°F)
Storage Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)
Ingress Protection Rating	IP54
Material Substance Compliance	RoHS


### CONFIGURATION

PART NUMBER	CONNECTOR
OC24005-FNF	Type N female
OC24005-FNM	Type N male

### RADIATION PATTERNS



H Plane 2.45 GHz



E Plane 2.45 GHz



Laird Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird Connectivity product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials rests with the end user, since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to the fitness, merchantability or suitability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity shall not be liable for incidental or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2020 Laird Connectivity All Rights Reserved. Laird Connectivity, the Laird Connectivity logo, and other marks are trademarks or registered trademarks of Laird Connectivity or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Connectivity or any third party intellectual property rights.

sales@lairdconnect.com  
support@lairdconnect.com  
www.lairdconnect.com



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Laird Connectivity:

[OC24005-FNF](#) [OC24005-FNM](#)