
CPI0805E4R7R-10

PHYSICAL DIMENSIONS:

A 2.00 [.079] ± 0.20[.008]

D 0.50 [.020] ± 0.20[.008]




ELECTRICAL CHARACTERISTICS:										
	L (μΗ) @ 1MHz ± 20%	DCR (Ω)	l (Max)							
Nom	4.7									
Min	3.8									
Max	5.6	0.375	500mA							

NOTES: UNLESS OTHERWISE SPECIFIED


- 1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, PAPER TAPE.
- 2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
- 3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
- 4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
- 5. Operation Temperature TEMP: -55°C~+125°C. (INCLUDING SELF-HEATING)

Ls vs Frequency

Ls vs DC BIAS Current




LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.763 [0.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS





DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird					_			
			Tech. and is loaned in confidence subject to return upon request of									
					with the understanding that no copies shall be made without the	Laird						
					written consent of Laird Tech. A							
					rights to design or invention are reserved.							
					PROJECT/PART NUMBER:	_						
					PROJECT/PART NUMBER:	ין	REV	PART T	rPE:	DRAWN BY:		
	С	CHANGE PLASTIC TAPE TO PAPER TAPE	04/17/14	QU	CPI0805E4R7R-10	1	С	CO-FIRE		QU		
	В	UPDATE LAIRD LOGO AND NOTES 5	08/05/13		L							
	0	OPDATE LAIRD LOGO AND NOTES 5					SCALE: NTS		SHEET:			
	Α	ORIGINAL DRAFT	03/01/11	QU					Ι.			
	REV	DESCRIPTION	DATE	INT					1 of 1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>Laird Performance Materials</u>: CPI0805E4R7R-10